

## SAFETY DATA SHEET

## FOAM CLEANER

CP0434 v4.0 RS 569-341

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

PRODUCT NAME FOAM CLEANER  
PRODUCT NO. 569-341  
SUPPLIER RS Components Ltd,  
Birchington Road,  
Corby,  
Northants,  
NN17 9RS.  
Tel: ☐ +44 (0) 1536 402888  
Fax: ☐ +44 (0) 1536 401588

**2 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
ISOBUTANE	200-857-2	75-28-5	1-5%	F+;R12
POTASSIUM HYDROXIDE	215-181-3	1310-58-3	< 1%	C;R35 Xn;R22
POTASSIUM SILICATE		1312-76-1	1-5%	Xi;R38,R41.
PROPANE	200-827-9	74-98-6	1-5%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

**3 HAZARDS IDENTIFICATION**

Extremely flammable.

CLASSIFICATION F+;R12.

**4 FIRST-AID MEASURES**

## GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

## INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

## INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

## SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

## EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5 FIRE-FIGHTING MEASURES**

## EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

## SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## UNUSUAL FIRE &amp; EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

**6 ACCIDENTAL RELEASE MEASURES**

## SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

**7 HANDLING AND STORAGE**

**FOAM CLEANER****CP0434 v4.0 RS 569-341****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
POTASSIUM HYDROXIDE	OES				2 mg/m3
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating
BUTANE	OES	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
ISOBUTANE	OES	800 ppm		800 ppm	

**INGREDIENT COMMENTS**

OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

**PROTECTIVE EQUIPMENT****ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit. Use chemical cartridge protection with appropriate cartridge.

**HAND PROTECTION**

Use protective gloves.

**EYE PROTECTION**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol
COLOUR	White
ODOUR	Characteristic
SOLUBILITY	Soluble in water
FLAMMABILITY LIMIT - LOWER(%)	0.8
FLAMMABILITY LIMIT - UPPER(%)	9.0

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

**11 TOXICOLOGICAL INFORMATION****INHALATION**

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

**INGESTION**

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

## SKIN CONTACT

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

## EYE CONTACT

Irritating to eyes. May cause chemical eye burns.

## ROUTE OF ENTRY

Inhalation. Skin and/or eye contact.

## 12 ECOLOGICAL INFORMATION

## ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

## 13 DISPOSAL CONSIDERATIONS

## DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION



UK ROAD CLASS	2		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2	ADR CLASS	Class 2: Gases
ADR PACK GROUP	Not Applicable	ADR LABEL NO.	2.1
CEPIC TEC(R) NO.	20G53	RID CLASS NO.	2
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2	IMDG PACK GR.	Not Applicable
EMS	2-13	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
ICAO CLASS	2.1	AIR PACK GR.	Not Applicable

## 15 REGULATORY INFORMATION

## LABELLING



Extremely Flammable

## RISK PHRASES

R12 Extremely flammable.

## SAFETY PHRASES

S16 Keep away from sources of ignition - No smoking.  
 S51 Use only in well-ventilated areas.  
 S2 Keep out of the reach of children  
 S23 Do not breathe vapour/spray.

## UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

## STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health.

Chemicals (Hazard Information and Packaging) Regulations.

REVISION DATE: 07/03/2005

## FOAM CLEANER

**CP0434 v4.0 RS 569-341**

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Occupational Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

---

### 16 OTHER INFORMATION

---

REVISION DATE 07/03/2005

REV. NO./REPL. SDS GENERATED 1

#### RISK PHRASES IN FULL

R12	Extremely flammable.
R22	Harmful if swallowed.
R35	Causes severe burns.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.