

WILLIAM



RANSOM

William Ransom & Son plc
Bancroft, Hitchin, Hertfordshire SG5 1LY England
Telephone: 01462 437615 Fax: 01462 420628

Technical Data Sheet

ISOPROPYL ALCOHOL BP

CHARACTERISTICS	A clear, colourless liquid.
IDENTIFICATION	COMPLIES
SOLUBILITY	COMPLIES
WEIGHT PER ML AT 20°C	0.783 - 0.787 g/ml
REFRACTIVE INDEX AT 20°C	1.376 - 1.379
ACIDITY OR ALKALINITY	COMPLIES
APPEARANCE	COMPLIES
GAS CHROMATOGRAPHY	COMPLIES
NON-VOLATILE MATTER	NMT 20ppm
PEROXIDES	COMPLIES
WATER	NMT 0.50%w/w
BENZENE AND RELATED SUBSTANCES	NMT 2ppm

STORAGE Store in well filled, well-closed containers, protected from light and at a temperature not exceeding 25°C.

SHELF-LIFE Three years (unopened container)

Approved by SR
AL/00/000/TDS-2-7/5/98



William Ransom & Son plc
Bancroft, Hitchin, Hertfordshire SG5 1LY England
Telephone: 01462 437615 Fax: 01462 420528

PRODUCT SAFETY DATA SHEET

1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND MANUFACTURER

1.1 PRODUCT NAME	ISOPROPYL ALCOHOL BP
1.2 PRODUCT CODE	AL/00
1.3 MANUFACTURER	William Ransom and Son plc.
1.4 ADDRESS	104 Bancroft, HITCHIN, Hertfordshire, SG5 1LY, United Kingdom.
1.5 TELEPHONE/FAX NUMBER	01462 437615 / 01462 420528

2. COMPOSITION / INFORMATION ON INGREDIENTS

2.1 COMPOSITION	A solution of Isopropyl Alcohol (CAS No. 67-63-0). ISOPROPANOL.
2.2 HAZARDOUS COMPONENTS	Isopropyl Alcohol (CAS No. 67-63-0) (F)
2.3 CAS NUMBER	CAS No. 67-63-0.

3. HAZARD IDENTIFICATION

3.1 PRIMARY HAZARDS

HIGHLY FLAMMABLE.

3.2 HEALTH EFFECTS

EYES

Will cause conjunctival irritation, corneal damage and iritis (inflammation of the iris).

INGESTION

A fatal dose in man can be as low as 100ml. Principle effect is rapid central nervous system depression and coma, which may be prolonged. Will also cause nausea, vomiting, muscular incoordination, gastritis (inflammation of the lining of the stomach), haemorrhage (escape of blood from a ruptured blood vessel), loss of consciousness and respiratory failure. Aspiration (sucking liquid into lungs) during swallowing or vomiting will damage lungs.

INHALATION

Vapour concentrations in excess of the occupational exposure limit may cause irritation of the eyes, nose and throat. High concentrations will produce central nervous system depression and symptoms and effects similar to those for ingestion.

SKIN

Repeated or prolonged contact may symptoms similar to those for ingestion. It may also cause defatting and possible dermatitis.

4. FIRST AID MEASURES

4.1 EYES

Remove contact lenses if possible. Irrigate eye(s) with plenty of fresh water for at least five minutes, holding eye open. Obtain medical attention IMMEDIATELY.

4.2 INGESTION

Wash mouth out thoroughly with water. DO NOT INDUCE VOMITING. Keep warm and at rest. If there is difficulty with breathing, give oxygen. If breathing stops or shows signs of failing, apply mouth to mouth ventilation. Seek medical assistance IMMEDIATELY.

4.3 INHALATION

Remove to fresh air, keep warm and at rest. If there are any difficulties with breathing give oxygen; if breathing stops or gives signs of failing apply artificial respiration. Seek medical assistance immediately.

4.4 SKIN

Remove contaminated clothing, this should not be worn again until it has been laundered. Wash contaminated skin with soap and water. Seek medical assistance if discomfort persists.

4.5 ADVICE TO PHYSICIANS

Isopropanol is twice as toxic as ethanol.

5. FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Water spray, AFFF foam, chemical dry powder or carbon dioxide.

5.2 UNSUITABLE

EXTINGUISHING MEDIA

Do not use water jet.

5. FIRE FIGHTING MEASURES (continued)

- 5.3 SPECIAL HAZARDS** Burning produces acrid smoke, irritating fumes, carbon monoxide and carbon dioxide.
- 5.4 PROTECTIVE EQUIPMENT** Self contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 PERSONAL PRECAUTIONS** Extinguish sources of ignition, ventilate area.
- 6.2 ENVIRONMENTAL PRECAUTIONS** Do not allow product to enter drains and watercourses.
- 6.3 SPILLAGE** Extinguish sources of ignition. Absorb spillage using a proprietary absorbent or sand, scoop up and place in a suitable open-topped container leave in a safe place in open air for alcohol to evaporate. Dispose of through licensed waste disposal contractor. Wash contaminated area thoroughly with water and detergent. Ventilate area thoroughly.

7. HANDLING AND STORAGE

- 7.1 HANDLING** Use in a well-ventilated area. Avoid inhaling vapour. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use.
- 7.2 STORAGE** Store in well closed containers, away from heat and source of ignition, at a temperature not exceeding 25°C. Attention is drawn to the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 for the storage of containers of over 500ml in size.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

- 8.1 OCCUPATIONAL EXPOSURE STANDARDS** 400ppm or 980mg/m³ 8 hour TWA skin notation (Isopropanol)
500ppm or 1225mg/m³ 10 minute STEL & skin notation (Isopropanol)
- 8.2 ENGINEERING CONTROL MEASURES** Local exhaust ventilation.
- 8.3 EYE PROTECTION** Goggles or face-shield
- 8.4 GENERAL PROTECTION** Overalls.
- 8.5 RESPIRATORY PROTECTION** Dust/Fume respirator.
- 8.6 SKIN/HAND/PROTECTION** PVC or rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

- 9.1 PHYSICAL STATE** Liquid
- 9.2 COLOUR** Colourless.
- 9.3 ODOUR** Characteristic of Isopropanol.
- 9.4 pH** No test data.
- 9.5 BOILING POINT °C** 82
- 9.6 FLASH POINT °C** 10°C (closed cup)
- 9.7 EXPLOSION LIMITS** Lower Limit 2.0%v/v Upper Limit 12.0%v/v for Isopropanol.
- 9.8 SOLUBILITY IN WATER** Miscible.
- 9.9 SOLUBILITY IN** Alcohol, chloroform and ether.
- 9.10 VAPOUR PRESSURE (hPa)** No test data.
- 9.11 WEIGHT (g/ml)** 0.83g/ml at 20°C.
- 9.12 FLAMMABILITY** Flammable.
- 9.13 AUTO-IGNITION (°C)** 399.
- 9.14 EXPLOSIVE PROPERTIES** Moderate/severe in an enclosed space in the presence of a source of ignition.
- 9.15 OXIDISING PROPERTIES** None reported.
- 9.16 VISCOSITY (cSt)** 3.057 at 20°C
- 9.17 VAPOUR DENSITY (AIR=1)** 2.08
- 9.18 DECOMPOSITION TEMPERATURE (°C)** No test data.
- 9.19 DUST EXPLOSION DATA** Not applicable.

10 STABILITY AND REACTIVITY**10.1 STABILITY****10.2 CONDITIONS TO AVOID**

Stable under normal conditions. No unusual reactivity. Hygroscopic.

Exposure to sources of ignition, water, moisture and temperatures above 25°C.

10.3 MATERIALS TO AVOID

Incompatible with oxidising agents

10.4 HAZARDOUS**DECOMPOSITION PRODUCTS**

Decomposition will produce acrid smoke, irritating fumes, carbon monoxide and/or carbon dioxide.

11 TOXICOLOGICAL INFORMATION**11.1 ACUTE TOXICITY**

Oral rat LD50 4700 – 5500mg/kg (Isopropanol)

11.2 EYE IRRITANT

Yes

11.3 SKIN IRRITANT

Possibly.

11.4 SKIN SENSITISATION

No.

11.5 SUB-ACUTE/SUBCHRONIC TOXICITY

Treatment related changes have been observed in laboratory animals after repeated inhalation exposure.

11.6 CHRONIC TOXICITY/**CARCINOGENITY**

None reported.

11.7 GENOTOXICITY

None reported.

11.8 REPRODUCTIVE/**DEVELOPMENTAL TOXICITY**

None reported..

11.9 HUMAN DATA

No data available.

11.10 ADDITIONAL DATA

Nil

12 ECOLOGICAL INFORMATION**12.1 MOBILITY**

Mobile liquid.

12.2 PERSISTANCE/**DEGRADABILITY**

Bio-degradable.

12.3 BIO-ACCUMULATION

Not expected to bioaccumulate.

12.4 ECOTOXITY

No data available.

13 DISPOSAL**13.1 PRODUCT DISPOSAL**

Through licensed waste disposal contractor.

13.2 CONTAINER DISPOSAL

Wash out container, remove labels and send for recycling.

14 TRANSPORT INFORMATION

	NUMBER	PROPER SHIPPING NAME	CLASS	SUBSIDIARY RISK	PACK GROUP	
14.1 ADR INFO	1219 isopropanol		3		(b)	Item Number 2301-3° Hazard Ident No. 33
14.2 IMDG INFO	1219	ISOPROPANOL	3.2		II	Page 3244 EmS 3-06 MPAG 305
14.3 IATA INFO	1219	isopropanol	3		II	Packaging instructions 305 & Y305 passenger aircraft Packaging instructions 307 cargo aircraft.
14.4 CDG ROAD	1219	ISOPROPANOL	3		II	Emergency Code 2YE Tremcard Number 30G30

15 REGULATORY INFORMATION**15.1 EC CLASSIFICATION****HEALTH**

Not classified

PHYSICO**CHEMICAL PROPERTIES****HIGHLY FLAMMABLE****ENVIRONMENTAL**

Not classified

15.2 RISK PHRASES

R11

Highly flammable

15.3 SAFETY PHRASES

S9

Keep container in a well ventilated place.

S16

Keep away from sources of ignition – No smoking.

16 NATIONAL LEGISLATION

- 16.1 CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) (Amendment) REGULATIONS 1998
16.2 THE CARRIAGE OF DANGEROUS GOODS BY ROAD AND RAIL (CLASSIFICATION AND LABELLING) REGULATIONS 1994.
16.3 HIGHLY FLAMMABLE LIQUIDS AND LIQUEFIED PETROLEUM GASES REGULATIONS 1972.

17 OTHER INFORMATION**17.1 REFERENCES USED**

1. Martindale 30th edition page 798 (Isopropyl Alcohol).
2. Sax's Dangerous Properties of Industrial Materials, eighth edition, page 2040 INJ000 (Isopropyl Alcohol).
3. Micromedex Poisindex(R) Substance Identification (Isopropyl Alcohol).
4. Hayman Limited Safety Data Sheet XIPAX 4.00 GB Current 13.06.1994 (Isopropanol).

17.2 PRODUCT SAFETY DATA SHEET FIRST ISSUED

07 September 1988.

17.3 PRODUCT SAFETY DATA SHEET REVISED

19 August 1999.


17.4 REASON FOR REVISION

Changes to transport codes and Risk and Safety phrases.

17.5 ISSUE STANDARD

3.

17.6 APPROVED BY


Technical Services Director

The information contained herein is, to the best of our knowledge, true and accurate. Any recommendations or suggestions are made without obligation on our part and the Company can accept no liability to any customer, their employees or any other person whatsoever for any loss, injury or damage whether direct or consequential, which may be caused by an error or omission from this sheet if negligent or otherwise.