

LITTEL-JAX® PHONE JACKS



Switchcraft®
Harsh Environment Connectivity Solutions
A HEICO Company




11, C11X



13



12A



12B, C12BX

Feature notched insulating washers that mechanically interlock springs and solder lugs. "V" bend in tip spring firmly holds mating phone plug, listed in table below; *ordered separately on pages 999-1000*. Mount in single 0.375" hole in panels up to 0.156" thick, except **mfg. part no. L-11** in panels up to 0.25" thick. **C11X** and **C12BX** have locating pin (non-turn device).

➤ CONTINUED ➤

TINI-JAX® MINIATURE PHONE JACKS



Switchcraft®
Harsh Environment Connectivity Solutions
A HEICO Company

Miniature two-conductor phone jacks are 1/2 the size of "Littel-Jax" jacks, but similar in construction. Mount in 0.25" diameter hole in panels up to 0.125" thick. Mate with **mfg. part no. 750** 0.141" diameter tip plug; *order separately on page 1000*.



41

Mfg. Part No.	Stock No.	Price Each
		1-9
● 41	39F744	2.84
● 42A	39F745	3.40
● 43A	39F689	4.78

(8951)

LITTEL-PLUG® PHONE PLUGS



Switchcraft®
Harsh Environment Connectivity Solutions
A HEICO Company



Fig. 1



Fig. 2



Fig. 3

2- and 3-conductor plugs with screw or solder terminals. Molded plastic or shielded nickel-plated brass handle. Fit standard 0.25" (6.35) ID phone jacks. **Mfg. part no. 299** phone plug includes larger cable clamp wings for improved strain relief on large cable. Modified brass, electrotin-plated terminals for easier soldering. *Order mating jacks separately on this page.*

2-CONDUCTOR PLUGS

Mfg. Part No.	Fig.	Mating Jack	Terminals	Stock No.	Price Each
					1-9
● 240*	1	11	Screw	39F760	5.17
● 250*	1	11	Solder	39F763	6.39
● 280‡	2	11	Solder	39F764	10.02

3-CONDUCTOR PLUGS

● 260*	1	12B	Screw	39F675	17.29
● 267*	1	12B	Solder	39F771	10.17
● 290‡	...	12B	Screw	39F766	18.70

➤ CONTINUED ➤