

(a). Sensor	(b). App'	©. Pressure (atm)	(d). Range	(e). Accuracy	(f). Response	(g). Operating Temp	(h). Storage Temp	(i). Output (STP)	(j). Load (kΩ)	(k). Temp Comp	(l). Shelf life (month)	(m). Warranty (month)	(n). Life (month)
B1 *	I/M		0-100%	+/- 1%	< 7 sec	0 - 40°C	0 - 40°C	285 - 635µA		Y: ±2.5%	24	6	8
B2 *													
B3 *	I/M		0-100%	+/- 1%	< 13 sec	0 - 40°C	0 - 50°C	240 - 390µA		Y: ±2.5%	24	12	12
B9 *													
C1R	M	0 – 1	0-100%	+/- 1%	< 30 sec	0 - 40°C	0 - 50°C	160 - 240µA		N: 2.5%/°C	24	24	18
C2R	M	0 - 1	0-100%	+/- 1%	< 30 sec	0 - 40°C	0 - 50°C	160 - 240µA		N: 2.5%/°C	24	6	DOA
C3 *	I/M		0-100%	+/- 1%	< 30 sec	0 - 40°C	0 - 40°C	150 - 250µA		Y: ±2.5%	24	12	18
C6 *	M		0-100%	+/- 1%	< 7 sec	0 - 40°C	0 - 40°C	150 - 250µA		Y: ±2.5%	24	12	18
J1 *	M										12	16	
K1	D	0 – 2	0-100%	+/- 1%	< 10 sec	0 - 40°C	0 - 50°C	10.0 - 14.0mV	0.180	Y: ±5%	24	24	15
KE25 *	M	0 - 1	0-100%	+/- 1%	< 12 sec	5 – 40°C	NS	11.0 - 15.0mV	1.0	Y: ±9%			60
MAX-01 *	M	0.6 - 1.75	0-100%	+/- 1%	< 13 sec	0 - 40°C	-20 - 60°C	14.0 - 19.0mV	0.3				33
MAX-02 *	M		0-100%	+/- 1%	< 15 sec	5 - 40°C	-15 - 50°C	<18.4mV	0.309				66
MAX-08	M	0.5 – 1.2	0-100%	+/- 1%	< 15 sec	5 - 40°C	0 - 45°C	41.7 - 73.1µA		Y: 2.9±0.2%			53
MAX-09 *	M/D		0-100%	+/- 1%	< 11 sec	0 - 40°C	0 - 50°C	26.4 - 44.0mV	0.088	Y: ±5%			33
MAX-10	M	0.5 – 0.8	0-100%	+/- 0.5%	< 15 sec	23°C +/- 2°C	-15 - 50°C	8.0 - 12.0mV		Y: ±1.5%			60
MAX-11 *	M/D	0.6 - 1.75	0-100%	+/- 1%	< 13 sec	0 - 40°C	-20 - 60°C	14.0 - 19.0mV	0.6				33
MAX-11i *	M	0.6 - 1.75	0-100%	+/- 1%	< 12 sec	0 - 40°C	-20 - 60°C	14.0 - 20.0mV	0.6				50
MAX-12 *	M/D	0.6 - 1.75	0-100%	+/- 1%	< 13 sec	-10 - 50°C	-20 - 60°C	13.0 - 16.0mV					66
MAX-12F *													
MAX-13 *	M/D	0.6 - 1.75	0-100%	+/- 1%	< 13 sec	0 - 40°C	-20 - 60°C	13.0 - 17.0mV					66
MAX-13250 *	M		0-100%	+/- 1%	< 15 sec	5 - 40°C	-15 - 50°C	12.0 - 17.0mV		Y: ±3%			60
MAX-13F *													
MAX-14 *	M/D	0.6 - 1.75	0-100%	+/- 1%	< 13 sec	0 - 40°C	-20 - 60°C	9.0 – 13.0mV					66
MAX-15 *	M		0-100%	+/- 1%	< 20 sec	5 - 40°C	-15 - 50°C	45.0 - 55.0mV		Y: ±2.5%			26
MAX-16 *	M	0.6 - 1.75	0-100%	+/- 1%	< 15 sec	10 - 51°C	-20 - 60°C	8.5 - 15.0mV					100
MAX-17	M	0.6 - 1.75	0-100%	+/- 1%	< 5 sec	0 - 45°C	-20 - 60°C	0.3 - 0.5µA		Y: ±5%			33
MAX-17250 *	M												
MAX-18 *	M												
MAX-19 *	M	0.6 - 1.75	0-100%	+/- 1%	< 10 sec	0 - 40°C	-20 - 60°C	170 - 230µA	0.1				16
MAX-22CC *	M		0-100%	+/- 1%	< 5 sec	0 - 50°C	-20 - 60°C	12.5 - 16.5mV		Y: ±3.5%			33
MAX-250 *	M/D		0-100%		< 15 sec	5 - 40°C	-15 - 50°C	10.0 - 15.5mV		Y: ±3%			60
MAX-250E *	M/D		0-100%		< 15 sec	5 - 40°C	-15 - 50°C	10.0 - 15.5mV		Y: ±3%			60
MA-250ESF*	M		0-100%	+/- 1%	< 5 sec	0 - 50°C	-20 - 60°C	10.0 - 14.0mV		Y: ±3.5%			33
(a). Sensor	(b). App'	©. Pressure (atm)	(d). Range	(e). Accuracy	(f). Response	(g). Operating Temp	(h). Storage Temp	(i). Output (STP)	(j). Load (kΩ)	(k). Temp Comp	(l). Shelf life (month)	(m). Warranty (month)	(n). Life (month)

MAX-50 *	M												
MAX-J1 *	M												
MAX-T4 *	M												
MAXVTI122*	N/S												
R10DN	D	0 - 1.3	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	6.0	Y: ±5%	24	24	36
R10DS	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	6.0	Y: ±5%	24	24	36
R10DV	D	0 - 1	0-100%	+/- 2%	< 30 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	6.0	Y: ±5%	24	12	18
R13	M	0 - 1	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	0.3 - 0.5μA		Y: ±5%	24	16	12
R15	M	0 - 1	0-100%	+/- 1%	< 15 sec	0 - 40°C	0 - 50°C	48.0 - 70.0μA	0.6	N: 2.5%/°C	24	16	36
R17A	A	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%		24	36
R17AH	A	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	10.5 - 13.5mV	10.0	Y: ±5%		24	36
R17D	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R17D	D	0 - 2	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R17MED	M	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R17VAN	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R21A	A	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%		24	36
R22-2BUD	D		0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	8.0 - 13.0mV	10.0	Y: ±5%		24	36
R22A	A	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%		24	36
R22AH	A	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	10.5 - 13.5mV	10.0	Y: ±5%		24	36
R22D	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R22D	D	0 - 2	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R22DHO	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	14.0 - 26.0mV	3.2	Y: ±5%	24	24	36
R22DN	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	36
R22MED	M	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%		24	36
R23MED	M	0 - 1	0-100%	+/- 1%	< 20 sec	0 - 40°C	0 - 50°C	24.0 - 33.0μA	0.6	N: 2.5%/°C		24	36
R24MED	M	0 - 1	0-100%	+/- 2%	< 10 sec	0 - 40°C	0 - 50°C	7.0 - 17mV	10.0	Y: ±5%	24	24	24
R24SIE	M	0 - 1	0-100%	+/- 2%	< 10 sec	0 - 40°C	0 - 50°C	10.0 - 17mV	10.0	Y: NS	24	24	
R26MED	M	0 - 1	0-100%	+/- 1%	< 10 sec	0 - 40°C	0 - 50°C	7.0 - 13.0mV	10.0	Y: ±5%	24	24	24
R29IMED	M	0 - 1	0-100%	+/- 1%	< 15 sec	5 - 40°C	-15 - 50°C	10.0 - 15.0mV	1000	Y: NS	24	24	60
R29MED	M	0 - 1	0-100%	+/- 1%	< 15 sec	5 - 40°C	-15 - 50°C	10.0 - 16.0mV	1000	Y: ±2%		12	60
R30MED	M	0 - 1	0-100%	+/- 1.5%	< 15 sec	10 - 40°C	-15 - 50°C	8.0 - 12.0mV		Y: NS		12	60
R31MED	M	0 - 1	0-100%	+/- 2%	< 15 sec	5 - 40 °C	-15 - 50°C	12.0 - 18.4mV		Y: NS		18	66
R32MED	M	0 - 1	0-100%	+/- 2%	< 15 sec	5 - 40 °C	-15 - 50°C	12.0 - 18.4mV		Y: NS		18	66
R33D	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	10.0	Y: ±5%	24	24	36
(a). Sensor	(b). App'	(c). Pressure (atm)	(d). Range	(e). Accuracy	(f). Response	(g). Operating Temp	(h). Storage Temp	(i). Output (STP)	(j). Load (kΩ)	(k). Temp Comp	(l). Shelf life (month)	(m). Warranty (month)	(n). Life (month)
R33D	D	0 - 2	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	10.0	Y: ±5%	24	24	36
R33D1	D	0 - 1	0-100%	+/- 1%	< 6 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	10.0	Y: ±5%	24	24	36

VIAMED.

30/04/15.

VM3/COP/37.99.

R33D1	D	0 - 2	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	23.0 - 27.0mV	10.0	Y: ±5%	24	24	36
R33VAN *	D												
T1	M	0 - 1	0-100%	+/- 1%	< 30 sec	0 - 40°C	0 - 50°C	160 – 240µA		N: 2.5%/°C	24	16	18
T2	M	0 - 1	0-100%	+/- 1%	< 30 sec	0 - 40°C	0 - 50°C	160 – 240µA		N: 2.5%/°C	24	6	DOA
T3 *	M										24	16	
T4	M	0 - 1	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	0.2 - 0.6µA		Y: ±5%	12	16	6
T5A	M	0 - 1	0-100%	+/- 1%	< 30 sec	0 - 40°C	0 - 50°C	54.0 - 80.0µA		N: 2.5%/°C	6	12	12
T6 *	M										12	16	
T7	M	0 - 1	0-100%	+/- 2%	< 6 sec	0 - 40°C	0 - 50°C	0.3 - 0.5µA		Y: ±5%	24	12	36
UFO130-1 *	M	0 - 1	0-100%	+/- 1%	< 130 msec	10 - 50°C	0 - 50°C	3.2 - 3.8V			12	6	6
UFO130-2 *	M	0 - 1	0-100%	+/- 1%	< 130 msec	15 - 40°C	0 - 40°C	3.0 - 3.8V				24	24

M = Medical.

D = Diving.

A = Auto.

I = Industrial.

NS = Not Stated.

* = Not all info available