Test Certificate

regarding

Electrical Safety, Electromagnetic Compatibility and Environmental Conditions Requirements



CEcert GmbH, Alter Holzhafen 19, 23966 Wismar (Germany) Test Laboratory

Certificate No.: 609.212.3

License Holder: bluepoint MEDICAL GmbH & Co. KG

An der Trave 15

23923 Selmsdorf, Germany

Product identification:: Multifunction patient monitor (SpO2, CO2)

Type/Model/Parameters: CapnoTrue ASP

P/N: 3090112002

Applied standards: IEC 60601 1:1988 +A1:1991 + A2:1995 (except clause 48)

IEC 60601-1-2:2007 IEC 60601-1-4:2000 IEC 60601-1-8:2006

ISO 9919:2005 (except clause 50)

ISO 21647:2009 (except clause 46, 51 and 101) **DIN EN 1789:2007** (sub-clause 6.4.1 and 6.4.2)

Test report(s): Electrical safety: 409.212.2, 409.107.3A, 409.107.5A,

409.107.6A, 409.107.7A

EMC: 409.212.1

Mechanical requirements: 409.212.5, 409.212.6A

Test result: PASS

This test certificate is relevant exclusively to the item(s) submitted for testing.

Consider the test report specified in this certificate and the safety indications specified in the technical documentation to the product.

Head of test laboratory

Akkreditierungsstelle D-PL-12049-01-01

Wismar, Monday, 28 February 2011

Dipl.-Ing. Bernd Schmidt

see 'Attachment 1' for more details

Attachment 1 to certificate 609.212.3 CECOT

Classification:

Ratings: power supply unit: primary: 100 - 240 V, 50 - 60 Hz, 250 mA

secondary: 6.0 Vdc, 1.4 A

internal battery: 4 x 1.5 Vdc (AA) or 3.7 Vdc, 2500 mAh (Li-ion)

Electrical safety: Protection class: Class II (external power supply),

Internal battery powered (CapnoTrue ASP),

Type BF (not defibrillation proof)

not intended to be used in presence of oxygen Clinical environment:

enriched environments or flammable aesthetic

mixtures

Protection by enclosure: IPX1 (with spillage testing of sub-clause 44.3)

Installation and use: hand-held

Supply connection: external power supply: plug-in monitor: internally powered

Temperature of applied part: < 41 ℃

Sterilization: none Alarms: yes

EMC: Emission class: Group 1, Class B

Immunity class not life-supporting

equipment to be used during patient transport outside the healthcare facility (if internally powered)

Environmental conditions:

Transportation: equipment to be used during patient transport

outside healthcare facility

The conditions of acceptability listed in the related test reports have to be considered.

End of Listing!