

VIAMED Ltd.

15 Station Road, Cross Hills, Keighley, West Yorkshire, BD20 7DT, UK. Website: www.viamed.co.uk. Email: info@viamed.co.uk. Tel: +44 (0)1535 634542. Fax: +44 (0)1535 635582.

TOM THUMB CALIBRATION / SERVICE SHEET.

Description.Tom Thumb.Serial No.\/ (ΝΑ) acctModel.TT 480.Time & Date of Service / Calibration.\(| / o - 7 \)Record the manometer reading in millibars below, ensuring the TT480 meets the limits specified.

		Visual check. Lat	Visual check. All mir	Visual check. Gau	Visual check. Gau with	Manometer Pre		Manometer Pre-		Manometer Adj		Manometer Adj		Snoop liquid. Checl leaks.		Test reduibment Test
		Labels are attached.	All adjustable settings are set to a minimum.	Gauge appears straight.	Gauge cannot be removed without tools.	Pressure Gauge Test: @ 30 cmH ₂ O.	****	Precision Valve: @ 10 Lpm.		Adjustable Valve: @ 10 Lpm.		Adjustable Valve: @ 10 Lpm		Check all ports / connections for leaks.		
Tom Thumb Label	Serial No. Label.	CE Label.				Tolerance: ≥29 & ≤ 31 cmH2O		Maximum: +3.0 cmH ₂ O over the adjustable valve setting.		Tolerance: $\geq 43 \& \leq 47 \text{ cmH}_2\text{O}$.	Name of the Control o	Minimum: $\leq 8 \text{ cmH}_2\text{O}$.		No bubbling.		Specification
~	_	_	~		<	298		9.87	<i>(</i> =	5.47		7.93	li de	V		Calibration
		P	P	P	P	P		Þ.		þ		þ		P	\$ \frac{1}{2}	T.M.

Service.	Parts Replaced.
Changed "O" Rings √	Diamond Copper Washer
Re-greased Adjustable Valve Internal Parts	Adjustable Valve
Re-calibrated Tom Thumb √	Adjustable Valve Internal Parts
Approx A Addition to Commercial Additional Addition to Commercial Ad	Safety Valve
The state of the s	Safety Valve Internal Parts
	Pressure gauge
	Pressure Gauge Face
	"0" Rings V
	Outlet
	Inlet
district dis	Blanking Bolts
A STATE OF THE STA	Rail Clamp
A decree and a dec	Main Body Block

Calibration: ...E. Senurowski ...

... Signed: