

automotive

# 'R' Series O<sub>2</sub> Sensors

**Range includes:**

R-17A-LV

R-17A, R-21A, R-22A

R-17AV, R-21AV, R-22AV

R-17AH, R-22AH

As used by most automotive emissions testing equipment manufacturers.



- PTB, BAR90, BAR97 and CE product approval
- Accurate measurement performance
- Exceeds industry requirements
- Long life in the field
- Fast response time
- Consistent linear response
- Stable zero
- Choice of connector and thread options

The 'R' series of Oxygen Sensors from Viamed feature special Rhodium plating on the cathode resulting in greater resistance to the effects of CO<sub>2</sub>, increasing the life of the sensor when used in exhaust emissions testing.

 **VIAMED**

# 'R' Series O<sub>2</sub> Sensors

## Sensor models

R-17A-LV, R-17A, R-21A, R-22A, R-17AV, R-21AV, R-22AV, R-17AH, R-22AH

## Output range

A-LV Model:	7 - 11.5 mV
A Models (R-17A, R-22A):	7 - 13 mV
A Model (R-21A):	9 - 14 mV
AV Models:	9 - 13 mV
AH Models:	10.5 - 13.5 mV
Outputs in air at 25°C, sea level	

<b>Range</b>	0 to 100% O <sub>2</sub>
<b>Resolution</b>	Better than 0.1% O <sub>2</sub>
<b>Linearity</b>	± 1% of full scale at constant temperature and pressure
<b>Expected life</b>	36 months at 20.9% O <sub>2</sub> , 25°C, 50% RH
<b>Response time</b>	30 seconds or less 20.9% O <sub>2</sub> to 0.1% O <sub>2</sub> : (actual response of sensor is < 6 seconds 0 to 90% O <sub>2</sub> )
<b>Humidity</b>	0 - 99% RH, non-condensing
<b>Operating temperature range</b>	0°C to +50°C
<b>Temperature compensation</b>	± 5% of reading over operating range (at thermal equilibrium)
<b>Cross interference</b>	Less than 0.1% O <sub>2</sub> response to: 15% CO <sub>2</sub> , balance N <sub>2</sub> 7% CO, balance N <sub>2</sub> 3000 ppm NO, balance N <sub>2</sub> 3000 ppm Hexane, balance N <sub>2</sub>
<b>Connectors</b>	3 pin Molex (R-21A, R-22A, R-21AV, R-22AV, R-22AH) Switchcraft mini phone jack (R-17A-LV, R-17A, R-17AV, R-17AH)
<b>Approvals</b>	PTB, BAR90, BAR97, CE EN60601 (89/336/EEC)
<b>Connecting thread</b>	R-17A-LV, R-17A, R-17AV, R-17AH Metric Thread, M16 R-21A, R-21AV American Thread, 5/8-24 UNEF R-22A, R-22AV, R-22AH Metric Thread, M16

## Manufactured By



Specification Subject to Change

Distributed by:



# VIAMED

**Viamed Limited** · 15 Station Road · Cross Hills  
Keighley · West Yorkshire · BD20 7DT · United Kingdom  
Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582  
Email: [info@viamed.co.uk](mailto:info@viamed.co.uk) Website: [www.viamed.co.uk](http://www.viamed.co.uk)



**R-17A-LV**  
0110107



**R-17A**  
0110117



**R-21A**  
0110121



**R-22A**  
0110122



**R-17AV**  
0110127



**R-21AV**  
0110131



**R-22AV**  
0110132



**R-17AH**  
0110137



**R-22AH**  
0110142



Part Number: 0190061  
Date: 01/17