

Order Information



| Product Name | Product Images | Order Code | Packaging | Compatible Models | Adapter Images | Order Code |
|------------------------------------|----------------|------------|-----------|----------------------|----------------|------------|
| 4-electrode BIS Sensor (Adult) | | 9902040904 | 10pcs/bag | 2-Channel BIS Module | | B0050I |
| 4-electrode BIS Sensor (Pediatric) | | 9902040502 | 10pcs/bag | | | |
| BIS Bilateral Sensor | | 9902060902 | 10pcs/bag | 4-Channel BIS Module | | B0052A |
| Entropy Index Sensor | | 9903030901 | 10pcs/bag | Entropy Index Module | | B0051A |
| IOC Sensor | | / | 10pcs/bag | IOC Index Module | | B0050A |
| PSI Sensor | | 9902060903 | 65pcs/bag | Masimo Module | | B0061A |
| CSI Sensor | | / | 10pcs/bag | CSI Module | | B0065I |
| Waterproof Cover | | SL2139A | Optional | / | / | / |
| Waterproof Adhesive Cover | | HL0804A | Optional | / | / | / |



Disposable Non-Invasive EEG Sensor



Shenzhen Med-link Electronics Tech Co.,Ltd
Address:Zone A of 1st and 2nd Floor, and 3rd Floor, Building A, No. 7, Tongsheng Industrial Park Road, Shanghenglang Community, Dalang Street, Longhua District, 518109 Shenzhen, PEOPLE'S REPUBLIC OF CHINA
Tel: 86-400-058-0755 / 86-0755-61120299
Website: www.med-linket.com



Declaration: Shenzhen Med-Link Electronics Tech Co., Ltd. ("MedLinket") hereby declares that all registered trademarks, product names, model numbers, etc., mentioned in this document belong to respective original owners or manufacturers. The information referenced herein is intended to clearly describe the compatibility features of MedLinket products for reference only and should not be construed as an operational guideline for medical institutions or related entities. If any adverse consequences cause from misunderstandings or incorrect use of the information, MedLinket shall not be held liable.

SP-100CN
V1.0 20250331

Disposable Non-invasive EEG Sensor

Rapid Identification

The 2nd - generation identification chip ensures the compatibility of the sensor

Stable Connection

Each transparent PC plug's thickness tolerance can be controlled precisely within ± 0.02 mm.

Durable Performance

Enhanced connector design with thickened copper for better elasticity and lifetime, reduced contact impedance.

Quick Pouduction

The unique tines designed on the electrode allow for quick penetration of the stratum corneum. Patented conductive gel with lower contact impedance.

Waterproof Design

Protect connector from fluid effect, ensuring patient and equipment safety.

Other Options

Disposable non-invasive EEG sensors with different technologies are available to meet diverse patient monitoring equipment demands in hospitals.




Entropy Index (EI) / Neurotechnology Index (NTI)



Cerebral State Index (CSI)



Index of Consciousness (IOC)



Patient State Index (PSI)