

Connection to Sensors with PCB Pins

Under no circumstances should CiTiceL pins be soldered to, as this can result in leakage of electrolyte and subsequent sensor failure. Connection should be made via a PCB mounting socket. Alternatively, the sidetag version of the 3-Series CiTiceL may be purchased, which is designed for solder connection.

WARNING: SOLDERING TO PINS WILL VOID THE SENSOR'S WARRANTY.

Recommended sockets can be purchased from either Wearnes Cambion Ltd or ANDON Electronics Corporation. Details are as follows

Wearnes Cambion Ltd

Peveril House
Mill Bridge
Castleton
Hope Valley
S33 8WR

Tel: +44 (0) 1433 621555
E-mail: cambionsales@cambion.co.uk
<http://www.cambion.co.uk>

CiTiceL Range Order Codes	4-Series / 5-Series	450-3326-01-xx-00
	3-Series / 7-Series	450-5301-01-xx-00

ANDON Electronics Corporation

4 Court Drive
Lincoln
RI 02865
USA

Tel: +1 401 333 0388
E-mail: info@andonelect.com
<http://www.andonelectronics.com>

Socket details and part numbers are available on the ANDON website.

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement City Technology Limited reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale. The products are always subject to a programme of improvement and testing which may result in some changes in the characteristics quoted. As the products may be used by the client in circumstances beyond the knowledge and control of City Technology Limited, we cannot give any warranty as to the relevance of these particulars to an application. It is the clients' responsibility to carry out the necessary tests to determine the usefulness of the products and to ensure their safety of operation in a particular application.

Performance characteristics on this data sheet outline the performance of newly supplied sensors. Output signal can drift below the lower limit over time

