

oxygen monitoring catalogue



UK
2026



VIAMED

The Leading Medical Oxygen Monitoring Supplier

Contact Us



01535 634 542



01535 635 582



**15 Station Road
Cross Hills
Keighley
West Yorkshire, BD20 7DT
United Kingdom**



info@viamed.co.uk



www.viamed.co.uk



www.viamed.co.uk/xref



VIAMED

Oxygen Sensors



OEM and compatible oxygen sensors for use with most oxygen analysers, oxygen monitors, anaesthesia systems, ventilators, incubators, oxygen concentrators... see page 4



RoHS compliant lead-free sensors see page 20

Lead-Free Cross Reference see page 25

Gas Sensors



Carbon Monoxide, Nitric Oxide and Nitrogen Dioxide Gas Sensors from City Technology see page 26

Oxygen Monitors/Analysers



A range of oxygen monitors and analysers for use in a variety of applications...

see page 28

Oxygen Monitoring Accessories



Accessories for use with oxygen sensors, patient circuits and oxygen analysers/monitors...

see page 35



Oxygen Sensors

EXPERIENCE

Viamed has been providing Oxygen Sensors since 1977. Speak to us regarding any of your oxygen sensor requirements.

WIDEST RANGE

Viamed have the widest range available on the market - we supply OEM and compatible oxygen sensors.

LATEST TECHNOLOGY

Sensors utilize the latest technology - providing high performance, reliability and accuracy.

RoHS Compliant Lead-free sensors now available see page 20.

FREE UK DELIVERY* & QUANTITY DISCOUNTS

on all oxygen sensors

**No minimum order value &
no order processing charge**

NHS Credit Facility available

**Viamed's online short-form cross reference can
be used to check compatibility, as well as for
details of additional oxygen sensors:**

www.viamed.co.uk/xref

**Alternatively, or if your oxygen sensor or equipment is not listed,
please contact us and we will check our comprehensive database.**

**Free oxygen sensor
disposal service**

**for the safe disposal of
any of your depleted
oxygen sensors**

0110051
T-1


Main OEM: Teledyne
OEM Sensor Part No.: A37016
Output Connector: Slip rings, 2
Sensor Output: $200 \pm 40 \mu\text{A}$
Sensor Life: 18 months
Response Time: ≤ 30 seconds
Warranty: 12 months

0110017
R-17MED


Main OEM: Teledyne
OEM Sensor Part No.: C43690
Output Connector: Phone jack, 0.141"
Sensor Output: 7.0 - 13.0 mV
Sensor Life: 36 months
Response Time: ≤ 6 seconds
Warranty: 15 months

0110018
R-17V


Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: OOM103-1
Output Connector: Phone jack, 3.5 mm
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 5 seconds
Warranty: 15 months



**For our range of
Oxygen Monitors and
Analysers go to page 28**

0110019
R-17Vi


Main OEM: Viamed
Application: Incubators
Output Connector: Phone jack, 3.5 mm
Sensor Output: 9.0 - 14.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months

0110022
R-22MED


Main OEM: Teledyne
OEM Sensor Part No.: C-44611
Output Connector: Molex, 3 pin plug
Sensor Output: 7.0 - 13.0 mV
Sensor Life: 36 months
Response Time: ≤ 6 seconds
Warranty: 15 months



0110021
R-22MEDV



Main OEM: Dräger
OEM Sensor Part No.: 83 620 30
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 5 seconds
Warranty: 12 months



0110039
R-22VA



Main OEM: Atom Medical
OEM Sensor Part No.: C81828-R22MATOM
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110073
R-22VA
(Matched Pair)



Main OEM: Atom Medical
OEM Sensor Part No.: 60859
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110020
R-22Vi



Main OEM: Viamed
Application: Incubators
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 14.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110072
R-22Vi
(Matched Pair)



Main OEM: Viamed
Application: Incubators
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 14.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110023
R-23V



Main OEM: Dräger
OEM Sensor Part No.: 6850645
Output Connector: Slip rings, 3
Sensor Output: 24 - 32 μ A
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110026
R-26MED



Main OEM: Respirationics
OEM Sensor Part No.: 8-100412-00
Output Connector: Phone jack, 0.141"
Sensor Output: 7.0 - 13.0 mV
Sensor Life: 24 months
Response Time: ≤ 10 seconds
Warranty: 12 months



0110040
R-30V



Main OEM: GE Healthcare
OEM Sensor Part No.: 6050-0004-110
Output Connector: Phone socket, 6P4C
Sensor Output: 10.0 - 12.0 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110041
R-41V



Main OEM: Airshields
OEM Sensor Part No.: 6735142
Output Connector:
 Phone socket, 3.5 mm
Sensor Output: 13.0 - 16.0 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110042
R-42V



Main OEM: Stephan
OEM Sensor Part No.: 130060001
Output Connector: AMP plug, 2 pin
Sensor Output: 9.0 - 11.5 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110043
R-43V
Pack of 2



Main OEM: Datex-Ohmeda
OEM Sensor Part No.: 6600-1278-600
Output Connector: Slip rings, 2
Sensor Output: 28.0 - 50.0 mV
Sensor Life: ≥ 500,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 6 months



0110044
R-44V



Main OEM: MSA
OEM Sensor Part No.: 806572
Output Connector: Molex socket, 3 way
Sensor Output: 9.0 - 13.0 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110045
R-45V

 VIAMED

Main OEM: Datascope
OEM Sensor Part No.: 0600-00-0002
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110047
R-47V

 VIAMED

Main OEM: Acutronic
OEM Sensor Part No.: OOM204
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.5 mV (2 channels)
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110049
R-49V

 VIAMED

Main OEM: Siemens
OEM Sensor Part No.: 64 19 332 E380E
Output Connector: Molex, 3 pin plug
Sensor Output: 13.0 - 16.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110057
T-7

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS

Main OEM: Teledyne
OEM Sensor Part No.: A51327
Output Connector: Phone socket, 4 way
Sensor Output: 0.4 ± 0.1 μ A
Sensor Life: 36 months
Response Time: ≤ 6 seconds
Warranty: 12 months



0110081
UFO 130-2

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: Spacelabs
OEM Sensor Part No.: 010-1120-01
Output Connector: DIL, 10 pin
Sensor Output: 3.4 ± 0.4 V @ 100% oxygen
Sensor Life: 24 months
Response Time: ≤ 130 milliseconds
Warranty: 12 months



0110401
MAX-1

 **maxtec**
A SALAERA COMPANY

Main OEM: Analytical Industries
OEM Sensor Part No.: PSR-11-915
Output Connector: Slip rings, 3
Sensor Output: 17.0 ± 3.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 13 seconds
Warranty: 12 months



0110402
MAX-2



**Longer life
alternative to R-23V**

Main OEM: Dräger
OEM Sensor Part No.: 6850645
Maxtec REF: R107P20
Output Connector: Slip rings, 3
Sensor Output: 12.2 - 18.1 mV
Sensor Life: ≥ 2,000,000 % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110403
MAX-3



Main OEM: City Technology
OEM Sensor Part No.: MOX3
Maxtec REF: R109P11
Output Connector: Phone socket, 4 way
Sensor Output: 9.0 - 13.0 mV
Sensor Life: ≥ 500,000 % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 12 months



0110460
MAX-7



Main OEM: Maxtec
Maxtec REF: R109P09
Output Connector: Phone jack, 3.5 mm
Sensor Output: 8.0 - 12.0 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110461
MAX-7L



Main OEM: Maxtec
Maxtec REF: R109P13
Output Connector: Phone jack, 3.5 mm
Sensor Output: 3.5 - 7.5 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110409
MAX-9



Main OEM: Teledyne
OEM Sensor Part No.: B39636-R13
Maxtec REF: R114P80
Output Connector: 1 mm pin, x 4
Sensor Output: 26.4 - 44.0 mV
Sensor Life: 6 months
Response Time: ≤ 20 seconds
Warranty: 14 months



0110410
MAX-10



Main OEM: GE Healthcare
OEM Sensor Part No.: 6050-0004-110
Maxtec REF: R112P10
Output Connector: Phone jack, 0.141"
Sensor Output: 8.0 - 13.5 mV
Sensor Life: > 900,000 % oxygen hours
Response Time: < 15 seconds
Warranty: 12 months

0110411
MAX-11



Main OEM: Dräger
Application: Fabius, Evita, Babylog, Cato
Maxtec REF: R113P10
Output Connector: Slip rings, 3
Sensor Output: 14.0 - 20.0 mV
Sensor Life: ≥ 500,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months

0110441
MAX-11i



Main OEM: Dräger
Application: Dräger Incubators
Maxtec REF: R113P06
Output Connector: Slip rings, 3
Sensor Output: 14.0 - 20.0 mV
Sensor Life: ≥ 750,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



**Compatible lead-free
sensors are now available.
See page 20 for more
information.**

0110412
MAX-12



Main OEM: Siemens
OEM Sensor Part No.: 9004979-E347E
Maxtec REF: R109P45
Output Connector: Molex, 3 pin plug
Sensor Output: 12.5 - 16.5 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months

0110462
MAX-12A



Main OEM: Philips (Respironics)
Application: NeoPAP
Maxtec REF: R109P48
Output Connector: Molex, 3 pin plug
Sensor Output: 8.0 - 13.0 mV
Sensor Life: ≥ 500,000 % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 14 months

0110424
MAX-12C



Main OEM: Viasys
Application: Avea Ventilator
Maxtec REF: R109P53
Output Connector: Molex, 3 pin plug
Sensor Output: 8.0 - 13.0 mV
Sensor Life: ≥ 1,000,000 % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 14 months



0110413
MAX-13



Main OEM: Philips (Respironics)
Application: Criterion Vent
Maxtec REF: R115P10
Output Connector: Phone jack, 3.5 mm
Sensor Output: 13.0 - 16.5 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 14 months



0110463
MAX-13C



Main OEM: BioMed Devices
OEM Sensor Part No.: 4433
Maxtec REF: R115P01
Output Connector: Phone jack, 2.5 mm
Sensor Output: 13.0 - 17.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 13 seconds
Warranty: 14 months



0110469
MAX-13CS



Main OEM: BioMed Devices
OEM Sensor Part No.: Crossvent 2+, 2i+, 3+, 4+
Maxtec REF: R115P01-001
Output Connector: Phone jack, 2.5mm
Sensor Output: 10.5 - 15.0 mV
Sensor Life: 3 years
Response Time: ≤ 15 seconds
Warranty: 12 months



0110474
MAX-13J



Main OEM: Maxtec
Maxtec REF: R115P03-002
Output Connector: Phone jack, 2.5 mm
Sensor Output: 8.0 - 12.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 17 seconds
Warranty: 12 months



0110444
MAX-13-250



Main OEM: Maxtec
Maxtec REF: R125P07
Output Connector: Phone jack, 3.5 mm
Sensor Output: 12.0 - 17.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110414
MAX-14



Main OEM: MSA
OEM Sensor Part No.: 806572
Maxtec REF: R116P80
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 13 seconds
Warranty: 14 months



0110420
MAX-14 (Fluke)



Main OEM: Fluke
Maxtec REF: R116P82-001
Output Connector: Molex SL, 2 pin
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 12 months



0110475
MAX-15M



Main OEM: Maxtec
Maxtec REF: R115P63
Output Connector: Phone jack, 3.5 mm
Sensor Output: 5.0 - 15.0 mV
Sensor Life: $\geq 750,000$ % oxygen hours
Response Time: < 12 seconds
Warranty: 14 months



0110416
MAX-16



Main OEM: Nellcor Puritan Bennett
OEM Sensor Part No.: 4-072214-00
Maxtec REF: R114P70
Output Connector: Molex, 3 pin plug
Sensor Output: 8.5 - 15.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 16 months



0110421
MAX-16HT



Main OEM: Versamed
Application: Vent
Maxtec REF: R114P73
Output Connector: Molex, 3 pin plug
Sensor Output: 9.5 - 16.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 18 months



0110417
MAX-17



Main OEM: Teledyne
OEM Sensor Part No.: T-7
Maxtec REF: R116P10
Output Connector: Phone socket, 4 way
Sensor Output: 7.5 - 12.5 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 8 seconds
Warranty: 12 months



0110418
MAX-18



Main OEM: Teledyne
OEM Sensor Part No.: C-1R
Maxtec REF: R116P40
Output Connector: Slip rings, 2
Sensor Output: 200 ± 40 μ A
Sensor Life: $\geq 250,000$ % oxygen hours
Response Time: ≤ 13 seconds
Warranty: 12 months



0110419
MAX-19



Main OEM: Teledyne
OEM Sensor Part No.: T-1
Maxtec REF: R116P06
Output Connector: Slip rings, 2
Sensor Output: 170 - 230 μ A
Sensor Life: $\geq$ 250,000 % oxygen hours
Response Time: $\leq$ 20 seconds
Warranty: 12 months



0110464
MAX-23



Main OEM: Teledyne
OEM Sensor Part No.: R-22MED
Maxtec REF: R116P06
Output Connector: Molex, 3 pin plug
Sensor Output: 8.0 - 13.0 mV
Sensor Life: $\geq$ 500,000 % oxygen hours
Response Time: 1.5 - 3.5 seconds
Warranty: 12 months



0110449
MAX-43
Pack of 2



Main OEM: GE (Ohmeda)
Application: Giraffe
Maxtec REF: R109P07
Output Connector: Slip rings, 2
Sensor Output: 25.0 - 35.0 mV
Sensor Life: $\geq$ 500,000 % oxygen hours
Response Time: $\leq$ 17 seconds
Warranty: 12 months



**Free oxygen sensor
disposal service**
for the safe disposal of
any of your depleted
oxygen sensors



0110439
MAX-48



Main OEM: Analytical Industries
OEM Sensor Part No.: All-11-60
Maxtec REF: R112P18
Output Connector: Phone socket, 4 way
Sensor Output: 3.8 - 4.8 mV
Sensor Life: $\geq$ 500,000 % oxygen hours
Response Time: $\leq$ 12 seconds
Warranty: 12 months



0110470
MAX-108A



Main OEM: Maxtec
Maxtec REF: R109P21
Output Connector: Phone socket, 4 way
Sensor Output: 8.0 - 15.0 mV
Response Time: $<$ 10 seconds
Warranty: 12 months



0110468
MAX-125M



Main OEM: Covidien
OEM Sensor Part No.: 4-072214-00
Maxtec REF: R140P07-001
Output Connector: Molex, 3 pin plug
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 12 months



0110473
MAX-125WF



Main OEM: Fluke
OEM Sensor Part No.: R116P82-001
Maxtec REF: R140P07-002
Output Connector: Molex SL, 2 pin
Sensor Output: 10.5 - 15.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 12 months

Awaiting
Image



Main OEM: City Technology
OEM Sensor Part No.: MOX2
Maxtec REF: R140-P07-003
Output Connector: Unterminated
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 12 months



0110428
MAX-250



without 'O' Ring

Main OEM: Maxtec
Maxtec REF: R125P01-002
Output Connector: 2 pin socket
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months




0110425
MAX-250



with 'O' Ring

Main OEM: Maxtec
Maxtec REF: R125P01-007
Output Connector: 2 pin socket
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months

0110427
MAX-250+



Main OEM: Maxtec
Maxtec REF: R125P02-011
Output Connector: Molex SL, 2 pin
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110431
MAX-250A



Main OEM: Blease
OEM Sensor Part No.: 70300001
Maxtec REF: R125P04-001
Output Connector: Phone socket, 4 way
Sensor Output: 11.0 ± 2.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110432
MAX-250(B)



Main OEM: Maxtec
Maxtec REF: R125P02-003
Output Connector: Unterminated
Sensor Output: $10.0 - 15.5$ mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110429
MAX-250E



Main OEM: Maxtec
Maxtec REF: R125P03-002
Output Connector: Mini power socket
Sensor Output: $10.0 - 15.5$ mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110430
MAX-250ESF



Main OEM: Maxtec
Maxtec REF: R115P85
Output Connector: Mini power socket
Sensor Output: 12.0 ± 2.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 5 seconds
Warranty: 12 months



0110433
MAX-250K
with DC



Main OEM: Viasys
OEM Sensor Part No.: 16101
Maxtec REF: R125P11-001
Output Connector: Mini power plug
Sensor Output: $10.0 - 15.5$ mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months

Awaiting
Image

0110453
MAX-250MS



Main OEM: Maxtec
Maxtec REF: R125P97
Output Connector: Molex, 3 pin plug (female)
Sensor Output: $10.5 - 15.5$ mV
Response Time: < 15 seconds
Warranty: 24 months

Awaiting
Image



0110479
MAX-250MST

Main OEM: Maxtec
Maxtec REF: R140P12
Output Connector: Molex, 3 pin plug
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 24 months



0110471
MAX-250TEL

Main OEM: Maxtec
Maxtec REF: R125P18-012
Output Connector: Mini phone socket
Sensor Output: 10.0 - 15.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110435
MAX-250TM



Main OEM: Maxtec
Maxtec REF: R125P18-012
Output Connector:
 Molex, 3 pin plug, 3P2C
Sensor Output: 11.0 ± 2.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months

Awaiting
Image



0110472
MAX-250PCB

Main OEM: Maxtec
Maxtec REF: R125P10
Sensor Output: 10.5 - 15.5 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110452
MAX-550E



Main OEM: Maxtec
Maxtec REF: R140P02
Application: MaxO2 ME Monitor
Output Connector: Stereo phone jack, 3.5 mm
Sensor Output: 10.5 - 15.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months



0110454
MAX-550E



**Flow Diverter also
available separately**
 Part Number: 0120086

Main OEM: Maxtec
Maxtec REF: R140P02-001
Application: MaxBlend Devices
Output Connector: Stereo phone jack, 3.5 mm
Sensor Output: 10.5 - 15.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: ≤ 15 seconds
Warranty: 24 months

0110570
OOM101

Honeywell



Output Connector: Slip rings, 2
Sensor Output: 14.0 - 20.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: < 12 seconds
Warranty: 15 months

0110565
OOM109

Honeywell



Main OEM: Cortex
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 200,000$ % oxygen hours
Response Time: ≤ 360 milliseconds
Warranty: 9 months

0110566
OOM109-LF2

Honeywell



Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 200,000$ % oxygen hours
Response Time: ≤ 360 milliseconds
Warranty: 9 months

0110560
OOM111

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 01-00-0114
Output Connector:
Stereo phone jack, 3.5 mm
Sensor Output: 11.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months

0110590
OOM111-M

Honeywell



Main OEM: Maquet
OEM Sensor Part No.: 66 40 044
Output Connector: Molex, 6 pin
Sensor Output: 10.0 - 20.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 15 months

0110579
OOM113

Honeywell



Main OEM: City Technology
OEM Sensor Part No.: MOX-3
Output Connector: Phone socket, 4 way
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110660
OOI103

Honeywell

Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 01-00-0095
Output Connector: Slip rings, 4
Sensor Output: 9.0 - 15.0 mV
Sensor Life: $\geq 500,000$ % oxygen hours
Response Time: ≤ 13 seconds
Warranty: 15 months



0110501
MOX1



REF: AA829-210
Output Connector: 3-pin Molex
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 13 months

Viamed's online short-form cross reference can be used to check compatibility, as well as for details of additional oxygen sensors:

www.viamed.co.uk/xref

Alternatively, if your oxygen sensor or equipment is not listed, please contact us and we will check our comprehensive database.



0110502
MOX2



REF: AA829-220
Output Connector: 3.5mm Mini Phone Jack
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 13 months



0110503
MOX3



REF: AA829-M10
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 13 months



0110504
MOX4



REF: AA829-M20
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 1,500,000$ % oxygen hours
Response Time: < 15 seconds
Warranty: 13 months



0110510
INQOX



REF: AA844-210

Output Connector: 3-pin Molex

Sensor Output: 7.0 - 14.0 mV

Sensor Life: ≥ 940,000 % oxygen hours

Response Time: < 15 seconds

Warranty: 13 months



0110511
MOX20



REF: AAE29-210

Output Connector: 3-pin Molex

Sensor Output: 0.80 - 1.25 V in 210 mBar O₂

Sensor Life: ≥ 276,000 % oxygen hours

Response Time: < 750 milliseconds at 0.5 lpm

Warranty: 13 months



**Compatible lead-free
sensors are
now available**

www.viamed.co.uk/xref



0110800
OOMLF102

Honeywell



Main OEM: Honeywell (Envitec)

OEM Sensor Part No.: 1002523

Output Connector: Molex, 3 pin plug

Sensor Output: 9.0 - 14.0 mV

Sensor Life: < 700,000 hours

Response Time: ≤ 12 seconds

Warranty: 15 months



0110801
OOMLF102-1

Honeywell



Main OEM: Honeywell (Envitec)

OEM Sensor Part No.: 1002532

Output Connector: Phone jack, 3.5 mm

Sensor Output: 9.0 - 14.0 mV

Sensor Life: < 700,000 hours

Response Time: ≤ 12 seconds

Warranty: 15 months



0110809
OOMLF103

Honeywell



Main OEM: Honeywell (Envitec)

OEM Sensor Part No.: 1002533

Output Connector: Molex, 3 pin plug

Sensor Output: 9.0 - 13.0 mV

Sensor Life: < 2 years

Response Time: ≤ 7 seconds

Warranty: 15 months



Lead-free Oxygen Sensors



RoHS COMPLIANT



The Restriction of the Use of Certain Hazardous Substances (RoHS) in Electrical and Electronic Equipment (EEE) Directive (2011/65/EU) 8th June 2011 was transposed into UK law on the 2nd January 2013. Under the recast RoHS, lead anodes in electrochemical oxygen sensors had been granted exemption status until 22nd July 2021.

However, the European Commission received two exemption requests during the period November-January 2019/2020. Therefore, whilst the review process is carried out, the exemption status has in effect been extended, until the Commission's decision is finalised.

In the meantime, Viamed continues to introduce and phase in a range of RoHS Compliant lead-free alternatives. Should you be unable to find the lead-free alternative you require, please contact us or visit our website... www.viamed.co.uk/xref



0110803
OOMLF110

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 1002536
Output Connector: Phone socket, 6P4C
Sensor Output: 9.0 - 13.0 mV
Sensor Life: < 700,000 hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110804
OOMLF111

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 1002537
Output Connector: Phone jack, 3.5 mm
Sensor Output: 11.0 - 13.0 mV
Sensor Life: < 700,000 hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110805
OOMLF202

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 1002539
Output Connector: Molex, 3 pin plug
Sensor Output: 10.0 - 14.0 mV
Sensor Life: < 700,000 hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110806
OOMLF202-1

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 1002540
Output Connector: Phone jack, 3.5 mm
Sensor Output: 10.0 - 14.0 mV
Sensor Life: < 700,000 hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110802
OOMLF106

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: 1002582
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: < 700,000 hours
Response Time: ≤ 12 seconds
Warranty: 15 months



0110814
OOMLF204-D

Honeywell



Main OEM: Honeywell (Envitec)
OEM Sensor Part No.: E1002573
Output Connector: Molex, 3 pin
Sensor Output: 9.0 - 13.5 mV
Response Time: < 30 seconds
Warranty: 15 months



0110700
MLF-03



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410303
Output Connector: Phone jack, 3.5 mm
Sensor Output: 13.0 - 16.5 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110701
MLF-04



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410606
Output Connector: Molex, 3 pin plug
Sensor Output: 13.0 - 16.5 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110702
MLF-12A



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410417
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110703
MLF-15



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410523
Output Connector: Phone jack, 3.5 mm
Sensor Output: 8.0 - 13.0 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110704
MLF-16



Main OEM: I.T. Gambert
OEM Sensor Part No.: 470316
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110705
MLF-19



Main OEM: I.T. Gambert
OEM Sensor Part No.: 470042
Output Connector: Phone socket, 4 way
Sensor Output: 9.0 - 13.0 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110706
MLF-43

itg



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410032
Output Connector: Slip rings, 2
Sensor Output: 11.0 - 15.0 mV
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110707
MLF-60HC

itg



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410040
Output Connector: Molex, 3 pin plug
Sensor Output: 0.8 - 1.25 V
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110708
MLF-650

itg



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410033
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 14.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 650 milliseconds
Warranty: 15 months



0110709
MLF-350

itg



Main OEM: I.T. Gambert
OEM Sensor Part No.: 410035
Output Connector: Molex, 3 pin plug
Sensor Output: 9.0 - 14.0 mV
Sensor Life: $\geq 1,000,000$ % oxygen hours
Response Time: ≤ 350 milliseconds
Warranty: 15 months



0110710
MLF-16D

itg



Main OEM: I.T. Gambert
OEM Sensor Part No.: 471116
Output Connector: Molex, 4 pin plug
 (digital sensor output signal, I²C interface)
Sensor Output: 2546 - 4455 bytes
Sensor Life: $\geq 2,000,000$ % oxygen hours
Response Time: ≤ 7 seconds
Warranty: 15 months



0110547
KE-25F3LFM



Output Connector: Unterminated
Inlet Connector: Threaded
Range: 0 - 100% oxygen
Sensor Output: 5.0 - 8.0 mV
Sensor Life: 6 years
Response Time: 15 seconds
Warranty: 12 months



Honeywell

- RoHS compliant (lead-free)
- One-to-one direct replacement for standard legacy 'leaded' sensors

Viamed Part No.	Original Sensor Description	Viamed Part No.	Honeywell Lead-Free Alternative
0110019	Viamed R-17Vi	0110801	OOMLF102-1 / 1002532
0110572	Honeywell OOM102-1 / 01-00-0020	0110801	OOMLF102-1 / 1002532
0110020	Viamed R-22Vi	0110800	OOMLF102 / 1002523
0110571	Honeywell OOM102 / 01-00-0019	0110800	OOMLF102 / 1002523
0110021	Viamed R-22MEDV	0110809	OOMLF103 / 1002533
0110574	Honeywell OOM103 / 01-00-0015	0110809	OOMLF103 / 1002533
0110040	Viamed R-30V	0110803	OOMLF110 / 1002536
0110577	Honeywell OOM110 / 01-00-0098	0110803	OOMLF110 / 1002536
0110041	Viamed R-41V	0110806	OOMLF202-1 / 1002540
0110585	Honeywell OOM202-1 / 01-00-0021	0110806	OOMLF202-1 / 1002540
0110044	Viamed R-44V	0110807	OOMLF202-2 / 1002606
0110586	Honeywell OOM202-2 / 01-00-0068	0110807	OOMLF202-2 / 1002606
0110045	Viamed R-45V	0110802	OOMLF106 / 1002582
0110049	Viamed R-49V	0110805	OOMLF202 / 1002539
0110560	Honeywell OOM111 / 01-00-0114	0110804	OOMLF111 / 1002537



Gas Sensors

- Capable of continuous measurement
- 4th electrode for additional temperature stability



Nitric Oxide

Nitrogen Dioxide

Carbon Monoxide

0110990
A3MEF

Awaiting
Image



Gas: Carbon Monoxide
Maximum Range: 4000 ppm CO
REF: MBU90-014
Output Connector: UK Data Socket AMP
Response Time: < 40 seconds
Warranty: 12 months

0110490
MN01



Gas: Nitric Oxide
Application: Inhaled Nitric Oxide Therapy
REF: AF0F4-H00 std.
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Expected Life: 12 months
Response Time: < 15 seconds
Warranty: 12 months

0110491
MN01B



Gas: Nitric Oxide
Application: Inhaled Nitric Oxide Therapy
REF: AF0F7-H00 w/bias
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Expected Life: 12 months
Response Time: < 15 seconds
Warranty: 12 months

0110492
MN02



Gas: Nitric Oxide
Application: Inhaled Nitric Oxide Therapy
REF: AF7F4-400 std.
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Expected Life: 12 months
Response Time: < 15 seconds
Warranty: 12 months

0110493
MN02B



Gas: Nitric Oxide
Application: Inhaled Nitric Oxide Therapy
REF: AF7F7-400 w/bias
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Expected Life: 12 months
Response Time: < 15 seconds
Warranty: 12 months

0110495
MND1S



Gas: Nitrogen Dioxide
Application: Inhaled Nitric Oxide Therapy
REF: AG010-H00
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Expected Life: 12 months
Response Time: < 15 seconds
Warranty: 12 months

0110496
MND2




Gas: Nitrogen Dioxide
Application: Inhaled Nitric Oxide Therapy
REF: AG7F4-400
Output Connector: UK Data Socket AMP
Sensor Output: 9.0 - 13.0 mV
Expected Life: 12 months
Response Time: < 15 seconds
Warranty: 12 months

UltraMaxO₂

0111265

The UltraMaxO₂ offers a fast and easy verification of oxygen concentration, flow and outlet pressure of oxygen concentrators

- Accurately measures oxygen, flow & pressure
- No oxygen sensor required
- No in-field calibration
- Self-diagnostics
- Shielded, reinforced sample gas inlet port
- Measurement range: 20.9 - 96%
- Warranty: 36 months



Smart Check


Ultrasonic Oxygen Analyser

Designed for accurate testing of oxygen concentrators and therapy devices



0111266

- Accurately measures oxygen, flow, pressure & pulse volume
- No oxygen sensor required
- No in-field calibration
- Backlit display with integrated torch
- Suitable for continuous flow & pulse dose concentrators
- Low-pressure mode for CPAP, BiPAP & nebulisers
- Warranty: 36 months



OxiQuant S

Oxygen Analyser

Honeywell

Used to determine oxygen concentrations in gas mixtures, delivered by oxygen concentrators, blenders...



Low battery indicator



0111275

- Flexible manual calibration
- Auto-off (after 3 minutes)
- Response time:
< 13 seconds to 90% of value
- Sensor (with integrated battery)
can be replaced
- Warranty: Analyser 24 months,
sensor 15 months

Note: Not approved for monitoring medical breathing air whilst in direct contact with patients.

Includes operator manual and the following standard accessories:



* Also available in pack quantity 0120093 - pack of 10

** Also available in pack quantity 0120174 - pack of 50

Handi+



Oxygen Analyser

This analyser is great for spot-checking oxygen percentage in hospitals, clinics and in homecare environments. Includes integrated sensor and battery.



0111250

- One-touch calibration (room air 20.9% oxygen, or 100% oxygen)
- Auto-off (after 80 seconds)
- Response time: < 15 seconds to 90% of value
- Disposable at end of sensor life
- Warranty: 24 months

CE0123

Includes operator manual and the following standard accessories:

0120399 Pk of 5




'T' Adapter 22mm I.D. - 22mm O.D., T = 15mm I.D.
Single Unit Supplied

0120095



Flow Diverter
15 mm O.D.

0120120




Oxygen Concentrator Adapter Cap

MaxO₂+A

The MaxO₂+A analyser is ideal for checking oxygen percent accuracy in oxygen concentrators.

0111260

- Integral sensor
- Long battery life (approximately 5,000 hours on 2 x AA batteries)
- Ergonomic hand-held design
- Impact resistant and drip proof
- Large LCD with 3.5 digit display
- One-touch calibration
- Warranty: 24 months



maxtec
A SALAERA COMPANY



CE 0123

Includes the following standard accessories:



0110427

MAX-250+ Oxygen Sensor



0120399 Pk of 5

'T' Adapter 22mm I.D. - 22mm O.D., T = 15mm I.D.
Single Unit Supplied



0120095

Flow Diverter
15 mm O.D.



0120120

Oxygen Concentrator Adapter Cap


See page 35 for optional extra accessories...

MaxO₂+AE

The MaxO₂+AE is best used anywhere an inline analyser is needed, when alarms are not deemed important. It is especially useful in conjunction with older ventilators or oscillators.


Standard cable version - 0111261
Short cable version - 0111262

- External sensor
- Long battery life (approximately 5,000 hours on 2 x AA batteries)
- Ergonomical hand-held design
- Impact resistant and drip proof
- Large LCD with 3.5 digit display
- One-touch calibration
- Warranty: 24 months




CE 0123

Includes the following standard accessories:




MaxO₂ ME Oxygen Monitor

The MaxO₂ ME oxygen monitor with backlit LCD display, smart alarms, built-in kickstand and protective overmould



CE 0123

Includes the following standard accessories:



See page 35 for optional extra accessories...

Oxygen Monitoring Accessories

Supplied as Standard Optional Accessories								
Part No.	Description	OxiQuant S	Handi+	MaxO ₂ +A	MaxO ₂ +AE	MaxO ₂ ME	MySign O Monitor Only	MySign O Kit
0120099	Teledyne Flow Diverter 15 mm O.D.							
0120092	Viamed Flow Diverter 15 mm O.D.							
0120095	Maxtec Flow Diverter 15 mm O.D.							
0120097	Maxtec Flow Diverter 18 mm O.D.							
0120399	T' Adapter 22 mm I.D. - 22 mm O.D.							
0120103	T' Adapter 15 mm I.D. - 15 mm O.D., T = 15 mm I.D. for paediatric circuits							
0121205	Calibration Assembly							
0120101	Adapter Cap 22 mm I.D.							
0120102	Adapter Cap 22 mm O.D.							
0120120	Oxygen Concentrator Adapter Cap							
0120125	Oxygen Connector 22 mm I.D. - 22 mm I.D.							
0120126	Oxygen Connector 22 mm O.D. - 22 mm O.D.							
0120127	Oxygen Connector 15 mm I.D./22 mm O.D. - 6.5 mm (tapered)							
0131150	Sensor Cable - Straight 3 m, right angled connectors							
0131201	Sensor Cable - Coiled 1 m, extendable, straight connectors							
0131202	Sensor Cable - Coiled 0.9 m, extendable, right angled connectors							
0121350	Sensor Cable - Coiled 0.5 m, extendable, right angled connectors							
0131700	Sensor Cable - Coiled 10ft fully extended, straight connectors							
0121302	V' Mount Assembly							
0121180	V' Wall Mount							
0121181	V' Mount Pole Clamp: Small							
0121182	V' Mount Pole Clamp: Large							
0121184	V' Mount Rail Clamp							
0121197	V' Mount Pole Clamp: Horizontal							
0121200	Universal Mounting Clamp							

Part No.	Description	OxiQuant S	Handi+	MaxO ₂ +A	MaxO ₂ +AE	MAXO ₂ ME	MySign O Monitor Only	MySign O Kit
0121351	MySign O Universal Mounting Clamp						•	•
0121301	Belt Clip & Pin Assembly			•	•	•		
0121305	Rubber Overmould for Handi+, Blue		■					
0121300	Lanyard		■	■	■			
0110427	MAX-250+ Oxygen Sensor			■				
0110429	MAX-250E Oxygen Sensor				■			
0110430	MAX-250ESF Oxygen Sensor				•			
0110452	MAX-550E Oxygen Sensor					■		
0110560	OOM111 Oxygen Sensor						■	■
0110660	OOI103 Oxygen Sensor	■						
0120121	Flowcheck	•	•	•	•	•	•	•
0121318	Remote Power Supply including UK/USA/EU adapters					•		
0121352	Power Supply including UK/EU/USA/JPN adapters						•	■
0120124	Connector 22 mm oxygen stem	■	•	•	•	•	•	•

Flow Diverters for use with oxygen sensors with an M16 x 1 mm input thread

0120099
TELEDYNE
ANALYTICAL
INSTRUMENTS



15 mm O.D.

0120092 Single
0120093 Pk of 10
Honeywell



15mm O.D.

0120095
R110P10-001
maxtec
A SALADA COMPANY



15 mm O.D.


0120097
RP33P42-002
maxtec
A SALADA COMPANY



18 mm O.D., Available with
or without 'O' Rings

T Adapters for use with 15 mm O.D. flow diverters

0120399
Box of 5



22 mm I.D. - 22 mm O.D.
T = 15 mm I.D.

0120113
Box of 40
②



15 mm I.D. - 15 mm O.D.
T = 15 mm I.D. for paediatric circuits

0121205



Calibration Assembly

Adapter Caps

Connects to oxygen sensors/analysers/monitors that have M16 x 1 mm input thread

Connectors

0120101



22 mm I.D.

0120102




22 mm O.D.

0120120



Oxygen Concentrator
Adapter Cap


0120174
Pack of 50



Connector
22 mm O.D. - 6 mm
oxygen stem

Connectors

0120175
Box of 35



②

22 mm I.D. - 22 mm I.D.

0120126 Single
0120176 Box of 40



②

15 mm I.D./22 mm O.D. -
22 mm O.D.

0120177
Box of 45



②

15 mm I.D. /22 mm O.D. -
6.5 mm (tapered)

0120178
Box of 50



②

15 mm I.D. - 22 mm I.D.

Flow Check Available Whilst Stock Lasts

0120179
Pack of 35



②

22 mm O.D. - 30 mm O.D.

0120121



- Simple to use and easy to read
- Convenient pocket-size
- For sensors/analysers with threaded input M16 x 1 mm
- Check flow and O₂% all-in-one
- Range 0 - 8 LPM
- Accuracy ± 0.4 LPM

Whilst stocks last



Maxtec FlowCheck

Working in conjunction with oxygen analysers, providing users with the ability to check oxygen concentration and flow all at once. This flowmeter will indicate the flow from 0 - 8 litres per minute and is useful in multiple applications.

Cables with screw lock connectors

for use with oxygen sensors that have a 3.5 mm/0.141" jack output connector

0131150



(Straight 3m)
Right angled connectors

0131201



(Coiled 1m, extendable)
Straight connectors

0131202



(Coiled 0.9m, extendable) Right
angled connectors

Monitor Mounting Options

for use with Teledyne AX300/MX300 and Maxtec monitors

0121180



'V' Wall Mount

0121181



'V' Mount Pole Clamp
Small:
14 - 25 mm clamping width

0121182



'V' Mount Pole Clamp
Large:
16 - 40 mm clamping width

0121184



'V' Mount Rail Clamp
Attaches to most types of medirail 30 mm (H) x 10 mm (D)

0121197



'V' Mount Pole Clamp
Horizontal
10 - 44 mm clamping width

0121200



Universal Mounting Clamp
Attaches to the threaded socket on the rear of the units



Maxtec Specific Accessories



0121302



'V' Mount Assembly
for use with Maxtec MaxO₂ To
attach to V mount clamps

0121301



**Belt Clip &
Pin Assembly**

0121305



**Rubber Overmould,
Blue** for use with Handi+

0121300
RP76P06


Lanyard

0110427



**MAX-250+
Oxygen Sensor**

0110429



**MAX-250E
Oxygen Sensor**

0110430



**MAX-250ESF
Oxygen Sensor**

0110452



**MAX-550E
Oxygen Sensor** for use
with MaxO₂ ME Oxygen Monitors

0131700



Sensor Cable
Coiled, 10ft fully extended,
straight connectors.
For use with MaxO₂ ME

0121318



Remote Power Supply
Supplied for use with MaxO₂ ME
includes UK, EU, USA/AUS adapters



0110560

OOM111
Oxygen Sensor



0110660

OOI103
Oxygen Sensor



0121353

Data Cable
USB 2.0 Type A/Mini-B



0121352

Power Supply Mini USB
5V/min, 1A including UK /
EU / USA / JPN adapter



0121350

(Coiled 0.5m, extendable)
Right angled connector



0121351

MySign O Universal Mounting Clamp

The convenient robust aluminium one-piece universal mounting clamp from Honeywell (Envitec) fits any shape of rail, can be adjusted and fastened in any position.



Disposable EEG Sensors

for monitoring the depth of anaesthesia as well as acquisition and transmission of biological EEG signals

- BIS EEG Compatible with a large range of BIS™ monitors and modules
- GE Entropy Compatible
- Clinically tested, high-measurement accuracy
- Soft and bio-compatible material
- Latex-free
- Adapter cables also available





Viamed Limited · 15 Station Road · Cross Hills
Keighley · West Yorkshire · BD20 7DT · United Kingdom
Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582
Email: info@viamed.co.uk Website: www.viamed.co.uk

All trademarks and trade names referenced in this material are the property of their respective owners.

OEM application details are provided in good faith without responsibility.

Images are for illustrative purposes only. Cover image supplied by Vecteezy.com

Specification subject to change



Part Number: 9990100

UK

Date: 06/26