

VM3COP50.14 Tom Thumb Calibration / QA Sheet

Description.	Tom Thumb.	Time & Date of Calibration / Test.	
Model.		Time & Date of QA.	
Serial No.		Serial no. : O ₂ flowmeter.	
		Serial no. : Air flowmeter.	

Do not start QA check within 1 hour of the calibration / test. Labelling is to be attached after calibration / test. Record the manometer reading in millibars below, ensuring the Tom Thumb meets the limits specified.

Test Equipment	Test	Specification	Reading		P/F
			Cal	Q.A.	
Snoop liquid.	Check all ports / connections for leaks.	No bubbling.			
CE ____	Adjustable Valve: @ 10 lpm	Minimum: <8 cmH ₂ O.			
CE ____	Adjustable Valve: @ 10 lpm.	Maximum: 42.1 ± 1 mbar			
CE ____	Precision Valve: @ 10 lpm.	Maximum: 44.1 ± 1 mbar			
CE ____	Pressure Gauge Test. @30cmH ₂ O	Pressure: 29.4mbar			
Visual check.	Gauge cannot be removed without tools.				
Visual check.	Gauge appears straight.				
Visual check.	All adjustable settings are set to a minimum.				
Visual check.	Labels are attached.	CE label.			
		Serial No. label.			
		Tom Thumb label			

Calibration:

Q.A check:

Signed:

Signed: