

Head Office - UK	USA Branch	Europe Branch	Middle East Branch	India Branch	Asia Branch
+44 (0)1869 - 324 144	+1 713 660 1427	+32 486 46 62 93	+971 (0)50 680 3107	+91 20 6573 4333	+86 139 2001 5417
sales@tag-pipe.com	sales-usa@tag-pipe.com	sales-europe@tag-pipe.com	sales-me@tag-pipe.com	sales-india@tag-pipe.com	sales-asia@tag-pipe.com



PIPE EQUIPMENT SPECIALISTS LTD

[VIEW RANGES](#)

[SEND ENQUIRY](#)

[HOME](#) | [ABOUT](#)

[NEWS](#)

Pipe Purging Equipment

>>> [Why Purge](#)

>>> [Purge Bag System](#)

>>> [Rapid Purge System](#)

>>> [Heat Resistant](#)

>>> [Purging System](#)

>>> [Gas Cylinders](#)

>>> [E-Z Zone Tape](#)

Zoom



**TAG
Handy
Purge 100
Plus Weld
Purge
Monitor**
Portable,
self-
calibrating,
self
pumping
digital
oxygen
monitor.
Measures
oxygen
levels down
to 0.01%
(100ppm)

>>> E-Z Purge

>>> Water Soluble Paper

>>> Handy Purge 100

Self Calibrating Weld

Purge Monitor Monitor

Weld Purge Monitor

Purge Blank Tape

>>> Solugap

>>> Liquifilm

>>> EZ Wipes

>>> Trailing Shields

Featured In

OUT NOW!

THE NEW 'E-Z' FIT RED PIP

The latest addition to TAG I
- rapid fit up, pipe-welding
clamps, is the latest versior
Fit Red. Boasting a range o

High Purity Welding

Oxygen
contamination is one
of the most common
reasons for
substandard welds.
Constant monitoring
is necessary
to ascertain oxygen
has been evacuated to
prevent
oxidation, discolouration
and coking. The
enhanced 100
ppm resolution makes
the Handy Purge 100
Plus perfectly suited
for high purity
welding.

Overview

Specificat

Download

Gallery

TAG Handy Purge 100 Plus Weld Purge Monitor Features and Advantages

- 0.01% Oxygen Resolution
- Automatic Self Calibration
- Internal Pump
- Data Logging Capability: Accumulates Up to 50 Data Points
- Data Output to Computer for Recording History
- Audiovisual Alarm
- Rechargeable 9V Battery
- One Year Warranty on Unit and Sensor
- Illuminated Display
- Designed for Universal Voltage
- Programmable in Multiple Gas Compositions



- Programmable in Multiple Languages

Audiovisual Alarm

Oxygen contamination is one of the most common reasons for substandard welds.

Eliminate guesswork by setting the audiovisual alarm to desired O2 PPM value.

The unit will produce an intermittent beep sound simultaneously as a green light flashes. The operator is alerted and can continue evacuating oxygen, reset the alarm or commence welding.

CONTACT US

Why not contact one of our team today and find out how TAG Pipe Equipment Specialists Ltd can be of assistance to you and your business.

Telephone: +44 (0)1869 324144

Email: sales@tag-pipe.com

Units 15 & 16
Grendon Industrial Estate
Grendon Underwood
Buckinghamshire
HP18 0QX
United Kingdom

RESOURCES & LINKS

- Home
- About
- Pipe Beveling Machine
- Pipe Cold Cutting Machines
- Pipe Flame Cutting Machines
- Pipe Alignment Clamps
- Pipe Stands & Rollers
- Pipe Purging Equipment
- Pipe Stoppers
- Layout and Marking Tools
- Tungsten Grinders
- Plate Beveling Machines
- Tube Tools
- Manipulation Equipment

JOIN OUR NEWSLETTER

Your Name

name@email.com

Join