



Infant Resuscitation Cabinet



Provides essential equipment for safe and easy infant resuscitation

- Wall mounted cabinet with antibacterial coating
- Wall mounted radiant warmer on articulated arm
- Tom Thumb Infant Resuscitation Unit
- Low suction controller
- Vacsax suction receiving system, utilising disposable liners
- Resuscitation platform manufactured from waterproof construction board
- Wide bed (35cm), designed to prevent mattress movement
- Sealed mattress, manufactured to BS5852 (Crib5) standards
- Digital Apgar Timer, audible indication at 1, 5 and 10-minutes
- Storage bins
- Air/Oxygen Blender (optional)



The Viamed Infant Resuscitation Cabinet offers an economical, convenient solution for the delivery room.

Compact and discreet, the cabinet is unobtrusive when not in use, yet facilitates the essential equipment for safe and easy resuscitation.

The cabinet is available in several configurations matched to your particular needs. An overhead radiant warmer mounted on an articulated boom arm conveniently and safely folds away when not in use.

The whole installation has a low profile and is ideally suited to even the smallest delivery rooms.



Infant Resuscitation Cabinet

Features

- Low profile, discreet: cabinet can be closed when not in use
- Economical; several delivery rooms can be equipped for the cost of a traditional mobile unit
- Provides a permanent, always ready solution for each individual delivery room
- Easy to operate, safe and fatigue-free resuscitation
- Optional air/oxygen blender for delivery of mixed gases
- Bacteria resistant, waterproof resuscitation platform and antibacterial coating on cabinet

Cabinet

Dimensions	660mm (Height), 650mm (Width), 280mm (Depth)
Weight	19kg (empty), 25kg (with standard accessories)
Medirails	3 (1 x 300mm, 2 x 400mm)
Shelving	Integral shelf and 3 bin rails
Storage	3 storage bins (blue, size 3 Lin bin)
Bed	Flat, 35cm (14") wide
Mattress	Sealed design, manufactured to BS5852 (Crib5) standards
Digital Apgar Timer	Preset audible indicators at 1, 5 and 10-minute intervals

Tom Thumb Infant Resuscitation Unit

Connection	3m hose to wall oxygen outlet
Flowmeter	Integral, 0 - 15 litres/min (option without flowmeter also available)
Pressure	Adjustable, provides complete control
Emergency blow-off valve	Factory set to a fixed, predefined pressure level
Patient circuit	One NeoPEEP variable PEEP resuscitation circuit included
Tom Thumb	TT480 for connection to an existing flowmeter or air/oxygen blender

Low Suction Controller

Suction	Variable, 0 - 150 mmHg (relief valve at -180 mmHg)
Scaling	Dual, -kPa and -mmHg
Connection to wall suction	3m hose with BS probe
Receiving jar	1 litre reusable Vacsax with disposable liner

Choice of Low Suction Controller:

Oxylitre S7 series

Therapy Equipment 7725 Diamond series

Ceratherm 600-3 Radiant Warmer

Power requirements	
Power rating	230V $\pm$ 10%, 50 - 60Hz
Element	620VA
Output	Ceramic, 600W. Efficient with fast warm up
Lighting	LED, 3W/700mA/4.5V, dazzle-free illumination of work area
Alarms	Audible and visual, 15 minutes with reset function
Mounting	Wall mounted articulated arm, folds away when not in use. Mobile radiant warmers also available
Certifications	IEC 601-2, CE0123

Optional Air/Oxygen Blender (Low flow)

Flowmeter	0 - 15 litres/min
Oxygen % Range	21 - 100%


Specifications subject to change

Cabinets are available in a variety of configurations suited to individual requirements

Installation of cabinets and warmers is the responsibility of the customer



Infant Resuscitation Cabinet system shown mounted on wall strengthening pattress board



TT480 Tom Thumb with NeoPEEP resuscitation circuit and mask



Air/Oxygen Blender (Optional)

Distributed by:



VIAMED

Viamed Limited · 15 Station Road · Cross Hills
 Keighley · West Yorkshire · BD20 7DT · United Kingdom
 Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582
 Email: info@viamed.co.uk Website: www.viamed.co.uk



Part Number: 0390100
 Date: 01/18