Automotive O₂ Sensors

Range includes:

R-17A-LVG R-17AVG R-22AVG

For use with most automotive emissions testing equipment



Viamed Automotive Oxygen Sensors are engineered to provide greater reliability and consistency.















Sensor models	R-17A-LVG, R-17AVG, R-22AVG
Output range R-17A-LVG: R-17AVG R-22AVG	7.0 - 11.5 mV 9.0 - 13.0 mV 9.0 - 13.0 mV Outputs in dry ambient air at 25°C, 1013 mbar
Measurement range	0 to 100% O ₂
Repeatability	< 1% volume oxygen at constant temperature and pressure
Pressure range	0.6 to 2.0 bar
Linearity error	< 3% relative
Accuracy	0% to 3.3% oxygen: ± 0.1% absolute 3.4% to 100% oxygen: ± 3.0% relative
Warm-up time	< 30 minutes after sensor installed
Zero offset voltage	< 40µV in 100% nitrogen
Nominal sensor life	≥ 500,000 % oxygen hours
Response time	< 5 seconds for 90% of final value. < 40 seconds fall time from 20.95% to 0.1% oxygen, when 100% nitrogen applied
Operating humidity	0 - 99% RH (non-condensing)
Operating temperature range	0°C to +50°C
Temperature compensation error	+25 to +40 °C: 3% relative 0 to +50 °C: 8% relative
Cross interference	< 0.1% volume oxygen to: 15% $\rm CO_2$ balance $\rm N_2$, 10% CO balance $\rm N_2$, 3000 ppm NO balance $\rm N_2$, 3000 ppm $\rm C_3H_8$ balance $\rm N_2$, 500 ppm $\rm H_2S$ balance $\rm N_2$, 500 ppm $\rm SO_2$ balance $\rm N_2$, 1000 ppm benzene balance $\rm N_2$
Connectors	3.5 mm mono phone jack (R-17A-LVG, R-17AVG) 3 pin Molex (R-22AVG)
Connecting thread	M16 x 1 (5/8-24 UNEF) Intermediate thread, metric/unified extra fine
Flow diverter	Yes
Packaging	Gas barrier bag - transparent
Warranty	12 months from date of sales invoice

All specifications are applicable at standard conditions: 1013 mbar, 25°C dry ambient air

Specification Subject to Change





W VIAMED

Viamed Limited · 15 Station Road · Cross Hills Keighley · West Yorkshire · BD20 7DT · United Kingdom Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582 Email: info@viamed.co.uk Website: www.viamed.co.uk

