



BlenderBuddy 2

A compact and clean addition to your blender

- DFB Dual scale flow meter
- Built-in oxygen port
- DISS outlet connection



The BlenderBuddy 2 equips your blender with the Maxtec DFB (designed for blenders) dual scale flow meter and has a built-in oxygen port, which allows gas to be analyzed safely and away from the patient to avoid cross-contamination. It securely attaches to your blender using the blender's DISS outlet connection.

The BlenderBuddy 2 also has a micro bleed, which reduces the amount of wasted gas.

BlenderBuddy 2

Specifications

Flow Meter Accuracy	± 10% of indicated value or 0.5 lpm, whichever is greater with 50 psig input pressure
Total System Response Time	≤ 30 seconds
Sensor Bleed Flow	≤ 0.2 lpm
Device Weight	0.4 kg (0.88 lbs)
Device Dimensions	9 cm (L) x 9 cm (W) x 18 cm (H) (3.5" (L) x 3.5" (W) x 7" (H))
Part Numbers	
BlenderBuddy 2, DFB, Low Flow 0 - 15 lpm	0310211
BlenderBuddy 2, DFB with MaxO2+A Oxygen Analyser, Low Flow 0 - 15 lpm	0310216

Specifications subject to change



BlenderBuddy 2, DFB with MaxO2+A Oxygen Analyser, Low Flow 0 - 15 lpm



Distributed by:



Viamed Limited · 15 Station Road · Cross Hills
Keighley · West Yorkshire · BD20 7DT · United Kingdom
Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582
Email: info@viamed.co.uk Website: www.viamed.co.uk

