

Blu-Ox Power Consumption.

Author: Peter Anderson
Date: 3rd November 2004

Assumptions:

- 1 The Blu-Ox will never be turned OFF – there will always be some LCD activity.
- 2 The A/D will sample 3 times a second with 3 conversions per sample.
- 3 The LCD will be updated every A/D sample.
- 4 The battery will be monitored once every hour with 5 ADC cycles per sample.

Power Consumption Calculation:

ST7LITE15

CPU (Estimated):			
Active Halt mode	200uA		
Run (Slow) mode	200uA		
Consumption:		200 uAh	(1)
LVD/AVD	245uA	245 uAh	(2)
RC Oscillator (Not used)		0 mAh	
PLL (Not used)		0 mAh	
12-bit Timer AT2	50uA	50 uAh	(3)
SPI (Not used)		0 mAh	

ADC	1.2mA	1.2 mAh	(4)
Flash Memory			
No Read/Write	100uA	100 uAh	(5)
Read	2.6mA		
	2.6mA x (256 / 32768)(Instructions)	20 uAh	(6)
Ports (Leakage)	1uA		
	1uA x 15(Pins)	15 uAh	(7)
<u>CV9018A LCD</u>			
Supply	300uA		
	20uA x 8760	300 uAh	(8)
<u>Battery Potential Divider</u>	10uA	10 uAh	(9)
<u>LTC3459 Regulator (1.2mA Load)</u>	100uA	100 <u>uAh</u>	(10)
Total (1 – 10):		1.2 mAh	

“AA” Battery capacities by manufacturer:

Varta 4106	2600 mAh
Duracell MN1500	2700 mAh
Energizer Ultra Alkaline	2850 mAh

<u>Battery life:</u>	$((2 \times 2600) / 1.2) / 24$	181 days
----------------------	--------------------------------	----------