

oxygen monitoring



Handheld Oxygen Analysers

Designed with simplicity and portability in mind



CE 0123


Maxtec oxygen analysers feature exceptional battery life. The patented MaxO₂⁺ analysers offer a unique one-touch calibration with no maintenance required, providing fast and easy operation.





MaxO₂+A

The MaxO₂+A analyser is ideal for checking oxygen percent accuracy in concentrators.




0111260

- Long battery life (approximately 5,000 hours on 2 x AA batteries)
- Ergonomical handheld design
- Impact resistant and drip proof
- Large LCD with 3.5 digit display
- Warranty: 24 months



MaxO₂+AE

The MaxO₂+AE is best used anywhere an inline analyser is needed, when alarms are not deemed important. It is especially useful in conjunction with older ventilators or oscillators.



Standard Cable - 0111261
Short Cable - 0111262

- Long battery life (approximately 5,000 hours on 2 x AA batteries)
- Ergonomical handheld design
- Impact resistant and drip proof
- Large LCD with 3.5 digit display
- Warranty: 24 months



Handi+

This analyser is great for spot-checking oxygen percentage in hospitals, clinics and in homecare environments. Includes integrated sensor and battery.



0111250


- One-touch calibration
- Overmould for extra protection
- Small, convenient and portable
- Auto-off
- Disposable at end of sensor life
- 3 digit LCD display
- Warranty: 24 months

MaxO₂ ME

The MaxO₂ ME low-maintenance oxygen monitor with smart alarms auto-set at 3% ± current reading

0111263

- **Long battery life** (approximately 5,000 hours on 2 x AA batteries)
- **Adjustable alarms** from 15 - 99%
- **Smart alarms**
Sets alarms 3% ± current reading
- **Back lit LCD display**
- **DC power port** (power supply sold separately)
- **Protective overmould**
- **Built-in kickstand and dove tail**
- **Warranty: 24 months**



UltraMaxO₂

The UltraMaxO₂ offers a fast and easy verification of oxygen concentration, flow and outlet pressure of oxygen concentrators

0111265

- **Accurately measure oxygen, flow & pressure**
- **No oxygen sensor required**
- **No in-field calibration**
- **Self-diagnostics**
- **Shielded, reinforced sample gas inlet port**
- **Measurement range: 20.9 - 96%**
- **Warranty: 36 months**



Part No.	Description	<div> <div>■ Supplied as Standard</div> <div>● Optional Accessories</div> </div>			
		MaxO ₂ +A	MaxO ₂ +AE	MaxO ₂ ME	Handi+
0110427	MAX-250+ Oxygen Sensor	■			
0110429	MAX-250E Oxygen Sensor		■		
0110430	MAX-250ESF Oxygen Sensor		●		
0110452	MAX-550E Oxygen Sensor			■	
0120095	Flow Diverter	■	■	■	■
0120399	'T' Adapter	■	■	■	■
0120120	Oxygen Concentrator Adapter Cap	■	●		■
0121302	'V' Mount Assembly	●	■	●	
0121180	'V' Wall Mount	●	●	●	
0121181	'V' Mount Pole Clamp: Small	●	●	●	
0121182	'V' Mount Pole Clamp: Large	●	●	●	
0121197	'V' Mount Pole Clamp: Horizontal	●	●	●	
0121184	'V' Mount Rail Clamp	●	●	●	
0121200	Universal Mounting Clamp	●	●		
0121301	Belt Clip & Pin Assembly	●	●	●	
0121305	Rubber Overmould for Handi+, Blue				■
0121303	Case Soft 'Tight Fit' for MaxO ₂	●	●		
0121300	Lanyard	■	■		■
0120121	Flowcheck	●	●		●

Additional Optional Accessories

<p>0120101</p>  <p>Sensor Adapter Cap 22 mm I.D.</p>	<p>0120102</p>  <p>Sensor Adapter Cap 22 mm O.D.</p>	<p>0120120</p>  <p>Oxygen Concentrator Adapter Cap</p>	<p>0121205</p>  <p>Calibration Assembly</p>	<p>0120399</p>  <p>'T' Adapter 22 mm I.D. - 22 mm O.D. Pack of 5</p>	<p>0120103</p>  <p>'T' Adapter 15mm I.D. - 15 mm O.D., T = 15 mm I.D. for paediatric circuits</p>
<p>0120095 R110P10-001</p>  <p>Flow Diverter</p>	<p>0120121</p> <ul style="list-style-type: none"> • Simple to use and easy to read • Convenient pocket-size • For Handi and MaxO₂+A analysers • Check flow and O₂% all-in-one • Range 0 - 8 LPM • Accuracy ± 0.3 LPM  <p>FlowCheck Working in conjunction with the Handi and MaxO₂+A oxygen analysers, providing users with the ability to check oxygen concentration and flow all at once. This flowmeter will indicate the flow from 0 - 8 litres per minute and is useful in multiple applications.</p>				
<p>0121302</p>  <p>'V' Mount Assembly</p>	<p>0121180</p>  <p>'V' Wall Mount</p>	<p>0121181</p>  <p>'V' Mount Pole Clamp Small: 14 - 25 mm clamping width</p>	<p>0121182</p>  <p>'V' Mount Pole Clamp Large: 16 - 40 mm clamping width</p>	<p>0121197</p>  <p>'V' Mount Pole Clamp Horizontal 10 - 40 mm clamping width</p>	<p>0121184</p>  <p>'V' Mount Rail Clamp Attaches to most types of medirail 30 mm (H) x 10 mm (D)</p>
<p>0121200</p>  <p>Universal Mounting Clamp</p>	<p>0121301</p>  <p>Belt Clip & Pin Assembly</p>	<p>0121305</p>  <p>Rubber Overmould, Blue for use with Handi+</p>	<p>0121300 RP76P06</p>  <p>Lanyard</p>	<p>0121318 R230P10</p>  <p>Remote Power Supply with UK, Europe, USA and Australia Adapters</p>	

Please note: These images are not to scale

Distributed by:



Viamed Limited · 15 Station Road · Cross Hills
Keighley · West Yorkshire · BD20 7DT · United Kingdom
Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582
Email: info@viamed.co.uk Website: www.viamed.co.uk

Part Number: 0191204

Specifications Subject to Change

Date: 02/20



All trademarks and trade names referenced in this material are the property of their respective owners.