

Viamed Limited - 15 Station Road - Cross Hills Keighley - West Yorkshire BD20 7DT - United Kingdom Tel: +44 1535 634542 Fax: +44 1535 635582 Email: info@viamed.co.uk Website: www.viamed.co.uk

Specification Datasheet – 0110364Prosol GOC5230 Oxygen Sensor



Specifications


Part number	0110364
Model	GOC5230
Output in ambient air	9 mV – 13 mV
Output connector/connection	3.5 mm mono phone jack
Input connector/connection	M16 x 1 (5/8-24 UNEF) Intermediate thread, metric/unified extra fine
Input O ring	Yes
Measurement range	0 – 100% oxygen (at atmospheric pressure)
Repeatability	< 1% volume oxygen at constant temperature and pressure
Influence of pressure	Output proportional to change in oxygen partial pressure
Pressure range	0.6 to 2.0 bar
Linearity error	< 3% relative
Accuracy	0 % to 3.3 % oxygen: +/- 0.1 % absolute
	3.4 % to 100 % oxygen: +/- 3.0 % relative
Warm up time	< 30 minutes after sensor installed
Zero offset voltage	< 40μV in 100% nitrogen
Cross interference	< 0.1% volume oxygen response to:
	15% CO ₂ balance N ₂ , 10% CO balance N ₂ , 3000 ppm NO balance N ₂ ,
	3000 ppm C ₃ H ₈ balance N ₂ , 500 ppm H ₂ S balance N ₂ ,
	500 ppm SO ₂ balance N ₂ , 1000 ppm benzene balance N ₂
Response time (t90)	< 5 s for 90% of final value.
	< 40 s fall time from 20.95% to 0.1% oxygen, when 100% nitrogen applied.
Operating humidity	0 – 99% R.H. (non-condensing).
Influence of humidity	- 0.03% relative per % R.H. at 25 °C.
Influence of mechanical shock	< 1% relative after fall from 1m
Operating temperature range	0 to +50 °C
Storage temperature	-20 to +50 °C
Recommended storage temperature	+5 to +15 °C
Temperature compensation	Integrated NTC thermistor
Temperature compensation error	+25 to +40 °C: 3% relative
(steady state)	0 to +50 °C: 8% relative
Nominal sensor life	≥ 500,000 % oxygen hours
Long term output drift	< 1% volume oxygen per month, typically < -15% over sensor lifetime.
Recommended load	≥ 10 KΩ
Weight (approximate)	28 g
Flow diverter	Not included
Packaging	Gas barrier bag – transparent.
Warranty period	12 months from date of sales invoice

All specifications are applicable at standard conditions: 1013 mbar, 25°C dry ambient air.

Specifications subject to change.

Viamed Limited - 15 Station Road - Cross Hills Keighley - West Yorkshire BD20 7DT - United Kingdom Tel: +44 1535 634542 Fax: +44 1535 635582 Email: info@viamed.co.uk Website: www.viamed.co.uk

Drawings



Measurements are in mm



Viamed Limited - 15 Station Road - Cross Hills Keighley - West Yorkshire BD20 7DT - United Kingdom Tel: +44 1535 634542 Fax: +44 1535 635582 Email: info@viamed.co.uk Website: www.viamed.co.uk

Images









Viamed Limited - 15 Station Road - Cross Hills Keighley - West Yorkshire BD20 7DT - United Kingdom Tel: +44 1535 634542 Fax: +44 1535 635582 Email: info@viamed.co.uk Website: www.viamed.co.uk

Labelling

Oxygen sensor label 90.0mm x 15.0mm

White vinyl label, text & graphics - black



GOC5230 Oxygen Sensor





2018-11



Gas barrier bag label 63.5mm x 46.6mm

White label, text & graphics - black



www.prosol.co.uk

Compatible to:

R-17A, R-17AV, R-17AH, AO3, OOA101-1

GOC5230 Oxygen Sensor



2018-11













Depending on the ambient conditions the sensor may require up to 30 minutes to reach signal stability after installation. The sensor contains caustic liquid. In case of leakage avoid contact with eyes and skin! Recommended storage temperature: 5°C - 15°C!