

2:1 Shrink Ratio

- Assorted colour range
- **UL224** recognised, **CSA, LR54949** irradiated polyolefin
- 2:1 heat shrink ratio when heated to 100
- **VW-1** flame retardant (except clear)
- Fuel, oils, hydraulic fuel resistant
- Dielectric strength=20kv/mm min
- Operating temp. -55 to +135

Black							
Dia.		Reel Length		Price Per Reel			
Nom.	Shrunk	(m)	Order Code	+	+	+	+
1.6	0.8	150	107-451				
2.4	1.2	150	107-452				
3.2	1.6	150	107-453				
4.8	2.4	150	107-454				
6.4	3.2	75	107-455				
9.5	4.7	75	107-456				
12.7	6.3	75	107-457				
19	9.5	60	107-458				
25.4	12.7	60	235-787				
38.1	19	30	107-460				
50.8	25.4	30	107-461				

Black - 1.2m Lengths							
Dia.		Order	Price Per Length				
Nom.	Shrunk	Code	+	+	+	+	+
1.6	0.8	143-717					
2.4	1.2	143-718					
3.2	1.6	143-719					
4.8	2.4	143-720					
6.4	3.2	143-721					
9.5	4.7	143-722					
12.7	6.3	143-723					
19	9.5	143-724					
25.4	12.7	143-725					
38.1	19	143-726					
50.8	25.4	143-727					

Black - 5m Coils							
Nom.	Shrunk	Order	Price Per Coil				
		Code	+	+	+	+	+
1.6	0.8	107-440					
2.4	1.2	107-441					
3.2	1.6	107-442					
4.8	2.4	107-443					
6.4	3.2	107-444					
9.5	4.7	107-445					
12.7	6.3	107-446					
19	9.5	107-447					
25.4	12.7	107-448					
38.1	19	107-449					
50.8	25.4	107-450					

CLOSE WINDOW