

infant resuscitation



Infant Resuscitation Cabinet

Provides essential equipment for safe and easy infant resuscitation.

- Wall mounted radiant warmer
- Tom Thumb infant resuscitation unit
- Low suction controller
- Bed with mattress
- Apgar timer
- Storage bins



The Viamed Infant Resuscitation Cabinet offers an economical convenient solution for the delivery room. Compact and discreet, the cabinet is unobtrusive when not in use, yet facilitates the essential equipment for safe and easy resuscitation.

The cabinet is available in several configurations matched to your particular needs. An overhead radiant warmer mounted on an articulated boom arm conveniently and safely folds away when not in use.

The whole installation has a low profile and is ideally suited to even the smallest delivery rooms.



Infant Resuscitation Cabinet

Features

- Low profile, discreet.
- Economical, several delivery rooms can be equipped for the cost of a traditional mobile unit.
- Provides a permanent, always ready solution for each individual delivery room.
- Easy to operate, safe and fatigue free resuscitation.

Cabinet

Dimensions:	Height 660 mm, length 650 mm, depth 280 mm
Weight:	19 kg (empty), 25 kg (with standard accessories)
Medirails:	3 (standard 30 mm x 10 mm), length 240 mm
Shelving:	Integral drugs shelf and 3 bin rails or no shelf and 4 bin rails
Storage:	3 storage bins (blue, size 3 Lin bin)
Bed:	Option of flat or angled bed (includes mattress), custom beds available on request
Apgar timer:	Start/stop timer function

Tom Thumb infant resuscitation unit

Connection:	3 m hose to wall oxygen outlet
Flow meter:	Integral, 0-15 lpm (option without flow meter is also available)
Pressure:	Adjustable, provides complete control
Emergency blow-off valve:	Factory set to a fixed, predefined pressure level
Patient circuit:	One standard occlusion circuit included

Low Suction Controller

Suction:	Variable, 0-150 mmHg (relief valve at 180 mmHg)
Scaling:	Dual, -kPa and -mmHg
Connection to wall suction:	3 m hose with BS probe
Receiving jar:	1/2 litre polycarbonate, autoclavable

Ceratherm 600-2 radiant warmer

Power requirements:	230 VAC, 50-60 Hz
Power rating:	620 VA
Element:	Ceramic, 600 W. Efficient with fast warm up
Output:	4 programmable levels, 0-99%
Lighting:	20 W halogen lamp, dazzle free illumination of work area
Alarms:	Audible and visual, 15 minutes with reset function
Mounting:	Wall mounted articulated boom arm, folds flat to the wall when not in use. Mobile radiant warmers also available
Certifications:	IEC 601-2, CE 0123

Specifications subject to change.

Cabinets are available in a variety of configurations suited to individual requirements. The pictures to the right depict a cabinet configuration which has a Tom Thumb unit without an integral flow meter, so as to be used with an existing external flow meter.

The cabinet is also a custom design whereby extended Medirails were chosen in preference to bin rails and storage bins. The outlet holes for the hoses were also moved from the default position in the bottom of the cabinet to the top.

Installation of cabinets and warmers are the responsibility of the customer. Pictures shown illustrate the low profile of the equipment, they are not intended to imply that Viamed is able to furnish rooms in such a manner.



Photographs reproduced with kind permission of Sunderland Royal Hospital.
Special thank you to the parents of Holly Colbeck

Distributed by:



Viamed Limited · 15 Station Road · Cross Hills
Keighley · West Yorkshire · BD20 7DT · United Kingdom
Tel: +44 (0)1535 634542/636757 Fax: +44 (0)1535 635582
Email: info@viamed.co.uk Website: www.viamed.co.uk



BS EN ISO 9001
BS EN 46001