

infant resuscitation



Infant Resuscitation Cabinet

Provides essential equipment for safe and easy infant resuscitation.
Featuring a number of recent improvements.

- Wall mounted radiant warmer
- Tom Thumb infant resuscitation unit
- Low suction controller
- Vacsax suction receiving system, utilising disposable liners
- Wide bed (35cm), designed to prevent mattress movement
- Sealed mattress, manufactured to BS5852 (Crib5) standards
- Digital Apgar timer, audible indication at 1, 5 and 10-minutes
- Storage bins



The Viamed Infant Resuscitation Cabinet offers an economical, convenient solution for the delivery room. Compact and discreet, the cabinet is unobtrusive when not in use, yet facilitates the essential equipment for safe and easy resuscitation.

The cabinet is available in several configurations matched to your particular needs. An overhead radiant warmer mounted on an articulated boom arm conveniently and safely folds away when not in use.

The whole installation has a low profile and is ideally suited to even the smallest delivery rooms.

 **VIAMED**

Infant Resuscitation Cabinet

Features

- Low profile, discreet.
- Economical: several delivery rooms can be equipped for the cost of a traditional mobile unit.
- Provides a permanent, always ready solution for each individual delivery room.
- Easy to operate, safe and fatigue-free resuscitation.

Cabinet

Dimensions: Height 660mm, length 650mm, depth 280mm
Weight: 19Kg (empty), 25Kg (with standard accessories)
Medirails: 3 (standard 30mm x 10mm), length 240mm
Shelving: Integral drugs shelf and 3 bin rails
Storage: 3 storage bins (blue, size 3 Lin bin)
Bed: Flat, 35cm (14") wide
Mattress: Sealed design, manufactured to BS5852 (Crib5) standards
Digital Apgar Timer: Preset audible indicators at 1, 5 and 10-minute intervals

Tom Thumb infant resuscitation unit

Connection: 3m hose to wall oxygen outlet
Flow meter: Integral, 0-15Lpm
(option without flow meter is also available)
Pressure: Adjustable, provides complete control
Emergency blow-off valve: Factory set to a fixed, predefined pressure level
Patient circuit: One standard occlusion circuit included

Low suction controller

Suction: Variable, 0-150mmHg (relief valve at -180mmHg)
Scaling: Dual, -kPa and -mmHg
Connection to wall suction: 3m hose with BS probe
Receiving jar: 1 litre reusable Vacsax cannister with disposable liner

Ceratherm 600-2 radiant warmer

Power requirements: 230VAC, 50-60Hz
Power rating: 620VA
Element: Ceramic, 600W. Efficient with fast warm up
Output: 4 programmable levels, 0-99%
Lighting: 20W halogen lamp, dazzle-free illumination of work area
Alarms: Audible and visual, 15 minutes with reset function
Mounting: Wall mounted articulated boom arm, folds flat to the wall when not in use. Mobile radiant warmers also available
Certifications: IEC 601-2, CE0123

Specifications subject to change.

Cabinets are available in a variety of configurations suited to individual requirements. The pictures to the right depict a cabinet configuration which has a Tom Thumb unit without an integral flow meter, so as to be used with an existing external flow meter.

The cabinet is also a custom design whereby extended Medirails were chosen in preference to bin rails and storage bins. The outlet holes for the hoses were also moved from the default position in the bottom of the cabinet to the top.

Installation of cabinets and warmers are the responsibility of the customer. Pictures shown illustrate the low profile of the equipment, they are not intended to imply that Viamed is able to furnish rooms in such a manner.



Photographs reproduced with kind permission of Sunderland Royal Hospital.
Special thank you to the parents of Holly Colbeck

Distributed by:



VIAMED

Viamed Limited • 15 Station Road • Cross Hills
Keighley • West Yorkshire • BD20 7DT • United Kingdom
Tel: +44 (0)1535 634542/636757 Fax: +44 (0)1535 635582
Email: info@viamed.co.uk Website: www.viamed.co.uk



BS EN ISO 9001-2000
ISO 13485-2003
CMDCAS

FS 28344 MD 78787