


Miniature radial electrolytic · type SMEVB ±20%

ECC

A range of subminiature, general purpose, aluminium electrolytic capacitors with low leakage currents and extremely small case sizes.

- ▶ Miniaturised standard series.
- ▶ Solvent-proof type.
- ▶ Wide range of values.



Case Code	Diameter	Length	Pitch	Wire Diameter
A	5	11	2	0,5
B	6,3	11	2,5	0,6
C	8	11,5	3,5	0,6
D	10	12,5	5	0,6
E	10	16	5	0,6
F	10	20	5	0,6
G	12,5	20	5	0,6
H	12,5	25	5	0,6
I	16	25	7,5	0,8
J	16	31,5	7,5	0,8

Tolerance: ±20%

Operating temperature range: -40°C to +85°C

Leakage current: ≤100V

0.03CV or 4µA after 1 minute; 0.01CV or 3µA after 2 minutes

ECC Part No.	Value µF	Case Code	Order Code	Price Per Pack of 5		
				1-4	5-9	10-19
10 Volt						
SMEVB47/10	47	A	92-907768D	0.43	0.42	0.41
SMEVB100/10	100	A	92-907769A	0.45	0.44	0.43
SMEVB220/10	220	B	92-907770B	0.55	0.54	0.52
SMEVB1000/10	1000	E	92-907771K	1.57	1.53	1.49
16 Volt						
SMEVB470/16	470	D	92-907772G	1.56	1.52	1.48
SMEVB1000/16	1000	F	92-907773D	1.89	1.84	1.80
SMEVB2200/16	2200	H	92-907774A	3.15	3.07	2.99
SMEVB3300/16	3300	I	92-907775J	3.71	3.62	3.52
SMEVB4700/16	4700	J	92-907776F	4.53	4.42	4.30
25 Volt						
SMEVB22/25	22	A	92-907777C	0.43	0.42	0.41
SMEVB47/25	47	A	92-907778L	0.45	0.44	0.43
SMEVB100/25	100	B	92-907779H	0.55	0.54	0.52
SMEVB220/25	220	C	92-907780J	1.28	1.25	1.22
SMEVB330/25	330	D	92-907781F	1.41	1.37	1.34
SMEVB470/25	470	E	92-907782C	1.63	1.59	1.55
SMEVB1000/25	1000	G	92-907783L	2.60	2.54	2.47
SMEVB2200/25	2200	I	92-907784H	3.77	3.68	3.58
SMEVB3300/25	3300	J	92-907785E	4.98	4.86	4.73
35 Volt						
SMEVB33/35	33	A	92-907786B	0.45	0.44	0.43
SMEVB220/35	220	D	92-907787K	1.13	1.10	1.07
SMEVB470/35	470	F	92-907788G	1.96	1.91	1.86
SMEVB1000/35	1000	H	92-907789D	3.28	3.20	3.12
SMEVB2200/35	2200	J	92-907790E	4.86	4.74	4.62
50 Volt						
SMEVB4.7/50	4.7	A	92-907791B	0.40	0.39	0.38
SMEVB47/50	47	B	92-907792K	0.55	0.54	0.52

Continued overleaf