

SPECIFICATION SHEET

TC400R Wall mounted radiant heater with resuscitation cabinet

Wall mounted Ceratherm 600-2 radiant heater with double jointed arm

Part number: 52160022

Dimensions:

Radiator:	Height 90 mm	Length 550 mm	Width 210 mm
Weight:	4.9 Kg		
Power:	220/240V, AC, 50Hz 630 watts		
Heating:	Long life Ceramic, 600 watts (infra red radiation approximately 3n/M)		
Lighting:	20 watt halogen lamp (dazzle free)		
Radiator performance:	4 steps: 25 %, 50 %, 75 % & 99 % of full power		
Alarm:	15 minutes, automatically switches to 25% power if alarm is not reset within 8 seconds (as per EC regulations)		
Certification:	IEC 601-2 TUV / CE		
Colour:	White RAL 9010		
Wall fixing:	800 mm to 1000 mm between mattress and lower edge of heater		
Wall plate:	4 x M8 holes 80 mm centres 130 mm between top & bottom set		
Foot print:	Swing from wall 600 mm - 1100 mm		

Cabinet and accessories

Dimensions:

Cabinet:	Height 660 mm	Width 650 mm	Depth 280 mm
Cabinet weight:	Empty - 19 Kg, with standard accessories - approximately 25 Kg		
Bed:	White folded perspex with a head down slope		
Mattress:	Height 25 mm	Length 540 mm	Width 230 mm
Tom Thumb:	Weight: 1.32 Kg, Pressure: 0 - 45 cm H ₂ O, Flow rate 0 - 5 Ltr/Min		
Suction controller:	0-150 mm Hg (relief valve at 180mm Hg) 1/2ltr. polycarbonate jar		
Clock:	Smiths model NS 22G Seconds Timer supplied with medirail clamp		
Storage bins:	Three size 3 blue lin bin		
Medirail:	Standard 30 mm x 10 mm	Length 240 mm	
Open shelf:	Height 190 mm	Depth 150 mm	Width 280 mm
Wall fixing:	To be completed by the hospital to customer specified height		
Wall plate:	4 x M6 holes 555 mm centres, 456 mm between top & bottom set		

*A larger bed can be supplied upon request Dimension: Customer specified

A mobile stand with heater and swivel arm is available as a stand alone product

Ceratherm 600-2 radiant heater with mobile stand

Part number: 52160030SM

Dimensions:

Ceratherm 600-2 radiant heater:	same as above		
Mobile stand:	Height 1700 mm	Length 640 mm	Width 580 mm
Mobile stand weight:	41 Kg		
Height adjustment:	200 mm		
Tilt range:	45 degrees		

* These parts are not included in the standard TC400R and must be specified

All information supplied is for reference only and may be altered without notification measurements are approximate