



VIAMED



TC400R Specifications Wall mounted Overhead heater with Resuscitation

Overhead Heater is our standard TC400 Heater unit mounted onto a wall plate approximately 300 mm square. It can swivel in either direction to lie against the wall when not in use. In use it is locked with a pin in a position 90 degrees to the wall. Size of Heater unit 850mm from wall 100mm x 100mm. Output is manually adjustable to 400 watts maximum.

The wall plate is fixed by 6 screws or wall bolts. The weight of heater 7.6Kg, is evenly distributed along the heater unit and not concentrated at one end.

The height of the heater should be a minimum 660mm above the bed. Although it is preferable to have it higher to avoid conflict with the users head a height of more than 760mm will start to substantially reduce the heat at the bed surface. The output is 400watts and is calculated to be safe at maximum output generating a temperature approximately 10 degrees above ambient in the vicinity of the bed/mattress. This will be effected by ambient conditions.

The TC400 can be used with standard mobile cots.

Resuscitation Cabinet is of metal construction, fixed to the wall with 4 screws or wall bolts. Size 620 x 280 x 665. weight 16 Kg.

The inner rear wall has fixed to it a rack to hold plastic bins for disposables etc. A small open shelf at the top is designed to accommodate a standard box for emergency supplies.

The inner rear wall also has three medical rails (adjustable heights) to accommodate Clock, suction, and resuscitation block.

The bed is white acrylic with retainers on both sides and a removable mattress. Size 250 x 500.

The door which doubles as a level working surface is a composite material to which the bed and hinges are screwed. This material has no cracks or joins so is easily cleaned. The mattress is removable.

Time Elapsed Clock is rail mounted on a hinge to facilitate quick access for winding. It is the normal three button, Start.Stop. Reset.

Tom Thumb Resuscitation Block is manufactured in metal where possible, is a modular system and designed to have a long life with low service costs.

Low Suction Controller which accepts disposable jars is available if required.

Standard Hospital Inspection Lamps can be fitted to the exterior of the cabinet or to the wall.

TC400R June 1994

Viamed Ltd. 15 Station Road, Cross Hills, Keighley, West Yorkshire BD20 7DT

Telephone: 0535 634542 / 636757 Fax: 0535 635582

Registration No. 1291765 in England



VIAMED



PRICE GUIDE - THERMACOT

<u>Product No</u>	<u>Description</u>	<u>Price</u> £
TC400	Thermacot Baby Warmer	900
TC400/W	Wall mounted Thermacot	660
TC400/F	Free standing Thermacot	850
TC400/R	Wall mounted Thermacot with resuscitation cabinet resuscitation unit and clock	1,830
TC400/RF	Free standing Thermacot with resuscitation cabinet resuscitation unit TC490 and clock	2,030
TC405	Stand for use with wall mounted TC400/W	295
TC430	Medical Light and fixing clamp Isolated low voltage:Quartz Halogen light.	300
TC451	Cupboard for use with TC400	130
TC452	Perspex Crib for use with TC400	65
TC453	Mattress for above	24
TC470	Neonatal Resuscitation Cabinet To be used with TC400/W Includes internal Rail and Storage bins.	380
TC460	Time elapsed Clock rail mounted and hinged.	70
TC465	Low suction controller and jar Accepts disposable jars.	205
TC466	Injector Suction unit with Flowmeter regulator and schraeder valve.	305
TC480	Resuscitation unit without Flowmeter	265
TC490	Resuscitation unit with Flow meter	380

N.B. Crib and Mattress are standard items as used in
most Baby Units

Above prices do not include V.A.T.

Carriage extra.

Feb1994
(PGAPP2)



Viamed Limited, 15 Station Road, Cross Hills,
Keighley, West Yorkshire BD20 7DT
Tel: 01535 634542 / 636757 Fax: 01535 635582
Registration No. 1291765 in England