SPECIFICATION SHEET

TC400R Wall mounted radiant heater with resuscitation cabinet

Wall mounted Ceratherm 600-2 radiant heater with double jointed arm

Part number: 52160022

Dimensions:

Radiator: Height 90 mm Length 550 mm Width 210 mm

Weight: 4.9 Kg

Power: 220/240V,AC,50Hz 630 watts

Heating: Long life Ceramic, 600 watts (infra red radiation approximately 3n/M)

Lighting: 20 watt halogen lamp (dazzle free)

Radiator performance: 4 steps: 25 %, 50 %, 75 % & 99 % of full power

Alarm: 15 minutes, automatically switches to 25% power if alarm is not reset

within 8 seconds (as per EC regulations)

Certification: IEC 601-2 TUV / CE

Colour: White RAL 9010

Wall fixing: 800 mm to 1000 mm between mattress and lower edge of heater Wall plate: 4 x M8 holes 80 mm centres 130 mm between top & bottom set

Foot print: Swing from wall 600 mm - 1100 mm

Cabinet and accessories

Dimensions:

Cabinet: Height 660 mm Width 650 mm Depth 280 mm

Cabinet weight: Empty - 19 Kg, with standard accessories - approximately 25 Kg

Bed: White folded perspex with a head down slope

Mattress: Height 25 mm Length 540 mm Width 230 mm

Tom Thumb: Weight: 1.32 Kg, Pressure: 0 - 45 cm H2O, Flow rate 0 - 5 Ltr/Min Suction controller: 0-150 mm Hg (relief valve at 180mm Hg) 1/2ltr. polycarbonate jar Smiths model NS 22G Seconds Timer supplied with medirail clamp

Storage bins: Three size 3 blue lin bin

Medirail: Standard 30 mm x 10 mm Length 240 mm

Open shelf: Height 190 mm Depth 150 mm Width 280 mm

Wall fixing: To be completed by the hospital to customer specified height

Wall plate: 4 x M6 holes 555 mm centres, 456 mm between top & bottom set

*A larger bed can be supplied upon request

Dimension: Customer specified

A mobile stand with heater and swivel arm is available as a stand alone product

Ceratherm 600-2 radiant heater with mobile stand

Part number: 52160030SM

Dimensions:

Ceratherm 600-2 radiant heater: same as above

Mobile stand: Height 1700 mm Length 640 mm Width 580 mm

Mobile stand weight: 41 Kg
Height adjustment: 200 mm
Tilt range: 45 degrees

SPECIFICATION SHEET

TC400R Wall mounted radiant heater with resuscitation cabinet

* These parts are not included in the standard TC400R and must be specified

All information supplied is for reference only and may be altered without notification measurements are approximate



SPECIFICATION SHEET

TC400R Wall mounted radiant heater with resuscitation cabinet

Wall mounted Ceratherm 600-2 radiant heater with double jointed arm

Part number: 52160022

Dimensions:

Radiator: Height 90 mm Length 550 mm Width 210 mm

Weight: 4.9 Kg

Power: 220/240V,AC,50Hz 630 watts

Heating: Long life Ceramic, 600 watts (infra red radiation approximately 3n/M)

Lighting:20 watt halogen lamp (dazzle free)

Radiator performance: 4 steps: 25 %, 50 %, 75 % & 99 % of full power

Alarm: 15 minutes, automatically switches to 25% power if alarm is not reset

within 8 seconds (as per EC regulations)

Certification: IEC 601-2 TUV / CE Colour: White RAL 9010

Wall fixing: 800 mm to 1000 mm between mattress and lower edge of heater Wall plate: 4 x M8 holes 80 mm centres 130 mm between top & bottom set

Foot print: Swing from wall 600 mm - 1100 mm

Cabinet and accessories

Dimensions:

Cabinet: Height 660 mm Width 650 mm Depth 280 mm

Cabinet weight: Empty - 19 Kg, with standard accessories - approximately 25 Kg

Bed: White folded perspex with a head down slope

Mattress: Height 25 mm Length 540 mm Width 230 mm

Tom Thumb: Weight: 1.32 Kg, Pressure: 0 - 45 cm H2O, Flow rate 0 - 5 Ltr/Min
Suction controller: 0-150 mm Hg (relief valve at 180mm Hg) 1/2ltr. polycarbonate jar
Clock: Smiths model NS 22G Seconds Timer supplied with medirail clamp

Storage bins: Three size 3 blue lin bin

Medirail:Standard 30 mm x 10 mmLength 240 mmOpen shelf:Height 190 mmDepth 150 mmWidth 280 mmWall fixing:To be completed by the hospital to customer specified heightWall plate:4 x M6 holes 555 mm centres, 456 mmbetween top & bottom set

*A larger bed can be supplied upon request

Dimension: Customer specified

A mobile stand with heater and swivel arm is available as a stand alone product

Ceratherm 600-2 radiant heater with mobile stand

Part number: 52160030SM

Dimensions:

Ceratherm 600-2 radiant heater: same as above

Mobile stand: Height 1700 mm Length 640 mm Width 580 mm

Mobile stand weight: 41 Kg
Height adjustment: 200 mm
Tilt range: 45 degrees

All information supplied is for reference only and may be altered without notification measurements are approximate

^{*} These parts are not included in the standard TC400R and must be specified