Certificate of Calibration

Certificate number:				
Model Number: Part Number: Serial number:				
This certificate reports recorded values for the instrument specified above.				
The output values were measured in accordance with procedure: VM3COP44.03.				
Equipment used: Time Electronics LTD Microcal 1030 – Calibrated Voltage source (CE076) - calibration traceable to UKAS calibration standards.				
Microcal	MySign (D expected reading	MySign O actual	Pass/Fail
			, , ,	
output	 (≤	2% relative)	reading	
output 50.0 mV		2% relative) (98.0% - 102.0%)	reading	
		•	reading	
50.0 mV	100%	(98.0% - 102.0%)	reading	
50.0 mV 45.0 mV	100% 90%	(98.0% - 102.0%) (88.2% - 91.8%)	reading	
50.0 mV 45.0 mV 40.0 mV	100% 90% 80%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%)	reading	
50.0 mV 45.0 mV 40.0 mV 35.0 mV	100% 90% 80% 70%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%) (68.6% - 71.4%)	reading	
50.0 mV 45.0 mV 40.0 mV 35.0 mV	100% 90% 80% 70% 60%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%) (68.6% - 71.4%) (58.8% - 61.2%)	reading	
50.0 mV 45.0 mV 40.0 mV 35.0 mV 30.0 mV 25.0 mV	100% 90% 80% 70% 60% 50%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%) (68.6% - 71.4%) (58.8% - 61.2%) (49.0% - 51.0%)	reading	
50.0 mV 45.0 mV 40.0 mV 35.0 mV 30.0 mV 25.0 mV	100% 90% 80% 70% 60% 50% 40% 30%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%) (68.6% - 71.4%) (58.8% - 61.2%) (49.0% - 51.0%) (39.2% - 40.8%)	reading	
50.0 mV 45.0 mV 40.0 mV 35.0 mV 30.0 mV 25.0 mV 20.0 mV	100% 90% 80% 70% 60% 50% 40% 30%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%) (68.6% - 71.4%) (58.8% - 61.2%) (49.0% - 51.0%) (39.2% - 40.8%) (29.4% - 30.6%)	reading	
50.0 mV 45.0 mV 40.0 mV 35.0 mV 30.0 mV 25.0 mV 20.0 mV 15.0 mV	100% 90% 80% 70% 60% 50% 40% 30% 20.9%	(98.0% - 102.0%) (88.2% - 91.8%) (78.4% - 81.6%) (68.6% - 71.4%) (58.8% - 61.2%) (49.0% - 51.0%) (39.2% - 40.8%) (29.4% - 30.6%)	reading	

Signed: