

<u>Device Essential Requirements Checklist</u> (in compliance with the 93/42/EEC Medical Device Directive).

Product:	Oxygen Hoods	New product:	No
Part number:	8000 Series	Existing Product:	Yes
Description:	Tent-house / Hood	Introduced:	1984
Class:	Class IIa	Main Standard:	N/A

No	Essential Requirement	A/NA	Standard.	Report.
I	General Requirements		H/box	
1.	The devices must be designed and manufactured in such a way that, when used under the conditions and for the purposes intended, they will not compromise the clinical condition or the safety of patients, or the safety and health of users or, where applicable, other persons, provided that any risks which may be associated with their use constitute acceptable risks when weighed against the benefits to the patient and are compatible with a high level of protection of health and safety.	A	ISO 9001. EN 46001. EN ISO 14971:2001.	(E) Risk management. (J,K) Production plan / procedures. (YZ) Design file. Based on existing products in use since late 1960's.
2.	The solutions adopted by the manufacturer for the design and construction of the devices must conform to safety principles, taking account of the generally acknowledged state of the art. - Eliminate or reduce risks as far as possible (inherently safe design and construction),	A	ISO 9001. EN 46001. EN ISO 14971:2001. EN ISO 14971:2001.	(YZ) Design file.(J,K) Production plan / procedures.(E) Risk management
	- Where appropriate take adequate protection measures including alarms if necessary, in relation to risks that cannot be eliminated,	A	EN ISO 14971:2001.	(E) Risk management
	- Inform users of the residual risks due to any shortcomings of the protection measures adopted	A	BSEN980 EN1041 EN ISO 14971:2001.	(F) User manual /Inserts / labels.(E) Risk management
3.	The devices must achieve the performances intended by the manufacturer and be designed, manufactured and packaged in such a way that they are suitable for one or more of the functions referred to in Article 1 (2) (a), as specified by the manufacturer.	A	ISO 9001. EN 46001.	(YZ) Design file. (J,K) Production plan / procedures. (M) Packaging T & V. Items custom made and uniquely packed.
4.	The characteristics and performances referred to in Sections 1, 2 and 3 must not be adversely affected to such a degree that the clinical conditions and safety of the patients and, where applicable, of other persons are compromised during the lifetime of the device as indicated by the manufacturer, when the device is subjected to the stresses which can occur during normal	A	EN ISO 14971:2001.	(E) Risk management(F) User manual.(G) Product life



	conditions of use		I	
5.	The devices must be designed, manufactured and packed in such a way that their characteristics and performances during their intended use will not be adversely affected during transport and storage taking account of the instructions and information provided by the manufacturer.	A	ISO 9001. EN 46001. EN1041.	(YZ) Design file. (J,K) Production plan / procedures. (F) User manual / Inserts / Labels. (M) Packaging T & V. Items often made specifically to order and uniquely packed.
6.	Any undesirable side effect must constitute an acceptable risk when weighed against the performances intended.	A	BS EN ISO 14971:2001	(E) Risk management. No known side effects.
II	Requirements Regarding Construction & Design			
7.	Chemical, physical and biological properties.			
7.1	The devices must be designed and manufactured in such a way as to guarantee the characteristics and performances referred to in Section I on the 'General requirements'. Particular attention must be paid to:	A	ISO 9001. EN 46001.	(J,K) Production plan / procedures. (T) Specification of materials. (YZ) Design file.
	-The choice of materials used, particularly as regards toxicity and, where appropriate, flammability,	A		(T) Specification of materials. Non flammable. Non Toxic.
	- The compatibility between the materials used and biological tissues, cells and body fluids, taking account of the intended purpose of the device.	A		(YZ) Biocompatibility. (T) Specification of materials.
7.2	The devices must be designed, manufactured and packed in such a way as to minimize the risk posed by contaminants and residues to the persons involved in the transport, storage and use of the devices and to the patients, taking account of the intended purpose of the product. Particular attention must be paid to the tissues exposed and to the duration and frequency of exposure.	A	ISO 9001. EN 46001.	Items often made specifically to order and uniquely packed. Material inert. (J,K) Production plan / procedures. (T) Specification of materials. (YZ) Design file.
7.4	The devices must be designed and manufactured in such a way that they can be used safely with the materials, substances and gases with which they enter into contact during their normal use or during routine procedures; if the devices are intended to administer medicinal products they must be designed and manufactured in such a way as to be compatible with the medicinal products concerned according to the provisions and restrictions governing these products and that their performance is maintained in accordance with the intended use. Where a device incorporates, as an integral part, a	A N/A	ISO 9001. EN 46001.	(JK) Production plan / procedures. (YZ) Design file. Used only with oxygen (T) Material specifications



	substance which, if used separately, may he considered to be a medicinal product as defined in Article 1 of Directive 65/65/EEC and which is liable to act upon the body with action ancillary to that of the device, the safety, quality and usefulness of the substance must be verified, taking account of the intended purpose of the device, by analogy with the appropriate methods specified in Directive 75/318/EEC.			medicinal products.
7.5	The devices must be designed and manufactured in such a way as to reduce to a minimum the risks posed by substances leaking from the device.	N/A	ISO 9001. EN 46001.	No fluids inside the device.
7.6	Devices must be designed and manufactured in such a way as to reduce, as much as possible, risks posed by the unintentional ingress of substances into the device taking into account the device and the nature of the environment in which it is intended to be used.	N/A	ISO 9001. EN 46001. BS EN ISO 14971: 2001.	(E) Risk management. (JK) Production plan / procedures. (YZ) Design file. Not sealed enclosure. No risk posed by unintentional ingress of substances.
8	Infection and microbial contamination			
8.1	The devices and manufacturing processes must be designed in such a way as to eliminate or reduce as far as possible the risk of infection to the patient, user and third parties. The design must allow easy handling and, where necessary, minimize contamination of the device by the patient or vice versa during use.	A	ISO 9001. EN 46001. BS EN ISO 14971: 2001.	Cracks can harbour bacteria. Sharp edges must be removed during final stages of manufacture.
8.2	Tissues of animal origin must originate from animals that have been subjected to veterinary controls and surveillance adapted to the intended use of the tissues. Notified bodies shall retain information on the geographical origin of the animals. Processing, preservation, testing and handling of tissues, cells and substances of animal origin must be carried out so as to provide optimal security. In particular safety with regard to viruses and other transferable agents must be addressed by implementation of validated methods of elimination or viral inactivation in the course of the manufacturing process.	N/A		No tissues of animal origin.
8.3	Devices delivered in a sterile state must be designed, manufactured and packed in a non-reusable pack and/or according to appropriate procedures to ensure that they are sterile when placed on the market and remain sterile, under the storage and transport conditions laid down,	N/A	ISO 9001. EN 46001.	Not intended to be delivered in a sterile state.



			I	1
	until the protective packaging is damaged or opened.			
8.4	Devices delivered in a sterile state must have been manufactured and sterilized by an appropriate, validated method.	N/A	ISO 9001. EN 46001.	Not intended to be delivered in a sterile state.
8.5	Devices intended to be sterilized must be	N/A	ISO 9001.	Not intended to be
0.5	manufactured in appropriately controlled (e. g. environmental) conditions.	IV/A	EN 46001.	delivered in a sterile state.
8.6	Packaging systems for non-sterile devices must	Α		(M). Packaging trial &
	keep the product without deterioration at the level			validation.
	of cleanliness stipulated and, if the devices are to			Not intended to be
	be sterilized prior to use, minimize the risk of			sterilized prior to use.
	microbial contamination; the packaging system			Items often made
	must be suitable taking account of the method of			specifically to order
	sterilization indicated by the manufacturer.			and uniquely packed.
8.7	The packaging and/or label of the device must	Α		Only non sterile
	distinguish between identical or similar products			components
	sold in both sterile and non-sterile condition.			
9.1	Construction and environmental properties If the device is intended for use in combination	A	ISO 0001	Intended for access
9.1	with other devices or equipment, the whole	A	ISO 9001. EN 46001.	Intended for oxygen
	combination, including the connection system		EN 40001.	delivery via pressure outlet / cylinder.
	must be safe and must not impair the specified			Regulator & flow tube.
	performances of the devices. Any restrictions on			Minimum of 6 litres /
	use must be indicated on the label or in the			min flow rate.
	instructions for use.			(F). Instructions for use
				/ inserts / labels.
9.2	Devices must be designed and manufactured in	Α	ISO 9001.	
	such a way as to remove or minimize as far as is		EN 46001.	
	possible:			
	- The risk of injury, in connection with their		BS EN ISO	(E). Risk management.
	physical features, including the volume/pressure		14971:2001	No volume / pressure.
	ratio, dimensional and where appropriate			Lightweight device. No
	ergonomic features,			sharp edges unless
				damaged by user.
	- Risks connected with reasonably foreseeable	Α	BS EN ISO	(E). Risk management.
	environmental conditions, such as magnetic		14971:2001.	No risks are foreseen
	fields, external electrical influences, electrostatic			regarding specific
	discharge, pressure, temperature or variations in pressure and acceleration,			environmental conditions.
	- The risks of reciprocal interference with other	N/A	BS EN ISO	
	devices normally used in the investigations or for	1 N /A	14971:2001.	(E). Risk management. No reciprocal
	the treatment given,		149/1.2001.	interference.
	- risks arising where maintenance or calibration	A	BS EN ISO	(E). Risk management.
	are not possible (as with implants), from ageing	11	14971:2001	No calibration or
	of materials used or loss of accuracy of any		1.5/1.2001	maintenance required.
	measuring or control mechanism.			
9.3	Devices must be designed and manufactured in	A	ISO 9001.	Used with levels of
	such a way as to minimize the risks of fire or		EN 46001.	oxygen up to 100%.



10	explosion during normal use and in single fault condition. Particular attention must be paid to devices whose intended use includes exposure to flammable substances or to substances, which could cause combustion. Devices with a measuring function		BS EN ISO 14971:2001	(E). Risk management. No flammable or combustible materials used.
10.1	Devices with a measuring function must be designed and manufactured in such a way as to provide sufficient accuracy and stability within appropriate limits of accuracy and taking account of the intended purpose of the device. The manufacturer must indicate the limits of accuracy.	N/A	ISO 9001. EN 46001.	No measuring function.
10.2	The measurement, monitoring and display scale must be designed in line with ergonomic principles, taking account of the intended purpose of the device.	N/A	ISO 9001. EN 46001.	No measuring function.
10.3	The measurements made by devices with a measuring function must be expressed in legal units conforming to the provisions of Council Directive 80/181/EEC (1).	N/A	ISO 9001. EN 46001.	No measuring function.
11	Protection against radiation			
11.1	General			
11.1	Devices shall be designed and manufactured in such a way that exposure of patients, users and other persons to radiation shall be reduced as far as possible compatible with the intended purpose, whilst not restricting the application of appropriate specified levels for therapeutic and diagnostic purposes.	N/A	ISO 9001. EN 46001.	No emitted radiation.
11.2	Intended radiation			
11.2.1	Where devices are designed to emit hazardous levels of radiation necessary for a specific medical purpose the benefit of which is considered to outweigh the risks inherent in the emission, it must be possible for the user to control the emissions. Such devices shall be designed and manufactured to ensure reproducibility and tolerance of relevant parameters.	N/A	BS EN ISO 14971:2001	No emitted radiation.
11.2.2	Where devices are intended to emit potentially hazardous, visible and/or invisible radiation, they must be fitted, where practicable, with visual displays and/or audible warnings of such emissions.	N/A		No emitted radiation.
11.3	Unintended radiation	NT / 4	ICO 0001	No omitted and '
11.3.1	Devices shall be designed and manufactured in such a way that exposure of patients, users and other persons to the emission of unintended, stray	N/A	ISO 9001. EN 46001.	No emitted radiation



	or scattered radiation is reduced as far as			
	possible.			
11.4	Instructions.			
	The operating instructions for devices emitting	N/A	EN1041	No emitted radiation
11.4.1	radiation must give detailed information as to the	1 \ / /A	LINIU41	ino cilitted radiation
	nature of the emitted radiation, means of			
	protecting the patient and the user and on ways of			
	avoiding misuse and of eliminating the risks			
	inherent in installation.			
11.5	Ionizing radiation			No radiation
	Devices intended to emit ionizing radiation must	N/A	ISO 9001.	No Ionizing radiation
11.5.1	be designed and manufactured in such a way as	11/71	EN 46001.	140 Iomzing radiation
	to ensure that, where practicable, the quantity,		LIV 40001.	
	geometry and quality of radiation emitted can be			
	varied and controlled taking into account the			
	intended use.			
11.5.2	Devices emitting ionizing radiation intended for	N/A	ISO 9001.	No Ionizing radiation
11.3.2	diagnostic radiology shall be designed and	11/11	EN 46001.	Tomain Francisco
	manufactured in such a way as to achieve			
	appropriate image and/or output quality for the			
	intended medical purpose whilst minimizing			
	radiation exposure of the patient and user.			
11.5.3	Devices emitting ionizing radiation, intended for	N/A	ISO 9001.	No Ionizing radiation
	therapeutic radiology shall be designed and		EN 46001.	
	manufactured in such a way as to enable reliable			
	monitoring and control of the delivered dose, the			
	beam type and energy and where appropriate the			
	quality of radiation.			
12	Requirements for medical devices connected to			
	or equipped with an energy source			
12.1	Devices incorporating electronic programmable	N/A	ISO 9001.	Not electronic or
	systems must be designed to ensure the		EN 46001.	programmable.
	repeatability, reliability and performance of these			
	systems according to the intended use. In the			
	event of a single fault condition (in the system)			
	appropriate means should be adopted to eliminate			
	or reduce as far as possible consequent risks.			
12.2	Devices where the safety of the patients depends	N/A		No internal energy
	on an internal power supply must be equipped			source
	with a means of determining the state of the			
	power supply.			
12.3	Devices where the safety of the patients depends	N/A		No external energy
	on an external power supply must include an			source
L	alarm system to signal any power failure.			
12.4	Devices intended to monitor one or more clinical	N/A		Not monitoring device
	parameters of a patient must be equipped with			
	appropriate alarm systems to alert the user of			
	situations which could lead to death or severe			
1.5 -	deterioration of the patient's state of health.		1.000000	
12.5	Devices must he designed and manufactured in	N/A	ISO 9001.	No energy source



	such a way as to minimize the risks of creating		EN 46001.	
	electromagnetic fields which could impair the			
	operation of other devices or equipment in the			
	usual environment.			
12.6	Protection against electrical risks			
12.6.1	Devices must be designed and manufactured in	N/A	ISO 9001.	No energy source
	such a way as to avoid, as far as possible, the risk		EN 46001.	
	of accidental electric shocks during normal use			
	and in single fault condition, provided the			
	devices are installed correctly.			
12.7	Protection against mechanical and thermal risks			
12.7.1	Devices must be designed and manufactured in	N/A	ISO 9001.	No moving parts.
	such a way as to protect the patient and user		EN 46001.	Non-electrical device.
	against mechanical risks connected with, for			
10.7.0	example, resistance, stability and moving parts.	37/4	100 0001	77 9
12.7.2	Devices must be designed and manufactured in	N/A	ISO 9001.	No vibration.
	such a way as to reduce to the lowest possible		EN 46001.	
	level the risks arising from vibration generated by			
	the devices, taking account of technical progress			
	and of the means available for limiting			
	vibrations, particularly at source, unless the			
12.7.3	vibrations are part of the specified performance.	N/A	ISO 9001.	No emitted noise.
12.7.3	Devices must be designed and manufactured in	N/A	EN 46001.	No emitted noise.
	such a way as to reduce to the lowest possible level the risks arising from the noise emitted		EN 46001.	
	taking account of technical progress and of the			
	means available to reduce noise, particularly at			
	source, unless the noise emitted is part of the			
	specified performance.			
12.7.4	Terminals and connectors to the electricity, gas	N/A	ISO 9001.	No pressure inlet.
	or hydraulic and pneumatic energy supplies		EN 46001.	Plastic push-to-fit
	which the user has to handle must be designed			connectors used.
	and constructed in such a way as to minimize all			
	possible risks.			
12.7.5	Accessible parts of the devices (excluding the	N/A		No heat generated.
	parts or areas intended to supply or reach given			
	temperatures) and their surroundings must not			
	attain potentially danger temperatures under			
	normal use.			
12.8	Protection against the risks posed to the patient			
	by energy supplies or substances			
12.8.1	Devices for supplying the patient with energy or	N/A	ISO 9001.	Does not supply energy
	substances must be designed and constructed in		EN 46001.	
	such a way that the flow-rate can be set and			
	maintained accurately enough to guarantee the			
1	safety of the patient and of the user.			
12.8.2	Devices must be fitted with the means of	N/A		No controls
	preventing and/or indicating any inadequacies in			
	the flow-rate, which could pose a danger.			
	Devices must incorporate suitable means to			



				1
	prevent, as far as possible, the accidental release			
	of dangerous levels of energy from an energy			
	and/or substance source.			
12.9	The function of the controls and indicators must	N/A		No controls
	be clearly specified on the devices.			
	Where a device bears instructions required for its			
	operation or indicates operating or adjustment			
	parameters by means of a visual system, such			
	information must be understandable to the user			
	and, as appropriate, the patient.			
13	Information supplied by the manufacturer			
13.1	Each device must be accompanied by the		EN1041	(F). User manual /
	information needed to use it safely and to identify			insert / label.
	the manufacturer, taking account of the training			
	and knowledge of the potential users.			
1	This information comprises the details on the			
	label and the data in the instructions for use.			
1	As far as practicable and appropriate, the			
	information needed to use the device safely must			
1	be set out on the device itself and/or on the			
	packaging for each unit or, where appropriate, on			
	the sales packaging. If individual packaging of			
	each unit is not practicable, the information must			
	be set out in the leaflet supplied with one or more			
	devices.			
	Instructions for use must be included in the			
	packaging for every device. By way of exception,			
	no such instructions for use are needed for			
	devices in Class I or II(a) if they can be used			
	safely without any such instructions.			
13.2	Where appropriate, this information should take	A	BSEN980.	(F). User manual /
13.2	the form of symbols. Any symbol or	7 1	BSEI 1700.	insert / label.
	identification color used must conform to the			illisert / laber.
	harmonized standards. In areas for which no			
	standards exist, the symbols and colors must be			
	described in the documentation supplied with the			
	device.			
13.3	The label must bear the following particulars			
(a)	The name or trade name and address of the	Α	BSEN980.	(F) Labels
1	manufacturer. For devices imported into the			
1	Community, in view of their distribution in the			
	Community, the label, or the outer packaging, or			
	instructions for use, shall contain in addition the			
1	name and address of either the person responsible			
	referred to in Article 14 (2) or of the authorized			
	representative of the manufacturer established			
	within the Community or of the importer			
	established within the Community, as			
	appropriate;			
L			1	<u> </u>



NOVA TENT – CE FILE

(b)	The details strictly necessary for the user to	A	BSEN980	(F) Labels
	identify the device and the contents of the packaging;			
(c)	Where appropriate, the word 'STERILE';	N/A	BSEN980	Non sterile device
(d)	Where appropriate, the batch code, preceded by the word 'LOT', or the serial number;	A	BSEN980.	(F) Labels
(e)	Where appropriate, an indication of the date by which the device should be used, in safety, expressed as the year and month;	N/A	BSEN980.	No shelf life or use by date
(f)	Where appropriate, an indication that the device is for single use;	N/A	BSEN980	Multiple use.
(g)	If the device is custom-made, the words 'custom-made device';	N/A	BSEN980	(F) Label
(h)	If the device is intended for clinical investigations, the words 'exclusively for clinical investigation';	N/A	BSEN980	(F) Label. Device not intended for clinical investigations.
(i)	Any special storage and/or handling conditions;	N/A	BSEN980	(F) Label No special instructions.
(j)	Any special operating instructions;	N/A	BSEN980	No special operating instructions
(k)	Any warnings and/or precautions to take;	N/A	BSEN980	(F) Label Minimum 6 litres / min flow rate.
(1)	Year of manufacture for active devices other than those covered by (c). This indication may be included in the batch or serial number;	N/A	BSEN980	Not active device
(m)	Where applicable, method of sterilization.	N/A	BSEN980	Not intended for sterilization.
13.4	If the intended purpose of the device is not obvious to the user, the manufacturer must clearly state it on the label and in the instructions for use.	N/A	BSEN980 EN1041	(F). User manual.
13.5	Wherever reasonable and practicable, the devices and detachable components must be identified, where appropriate in terms of batches, to allow all appropriate action to detect any potential risk posed by the devices and detachable components	N/A	BSEN980 EN1041	(F). User manual. (F). Insert.
13.6	Where appropriate, the instructions for use must contain the following particulars:			
a	The details referred to in Section 13.3, with the exception of (d)&(c);		EN1041	(F) Instructions for use.
b	The performances referred to in Section 3 and any undesirable side-effects;		EN1041	(F) Instructions for use. No side effects.



С	If the device must be installed with or connected to other medical devices or equipment in order to operate as required for its intended purpose, sufficient details of its characteristics to identify the correct devices or equipment to use in order to obtain a safe combination;	N/A	EN1041	Connection to O ₂ outlet and / or humidity.
d	All the information needed to verify whether the device is properly installed and can operate correctly and safely, plus details of the nature and frequency of the maintenance and calibration needed to ensure that the devices operate properly and safely at all times;	N/A	EN1041	Not required.
e	Where appropriate information to avoid certain risks in connection with implantation of the device;	N/A	EN1041	Not implantable device.
f	Information regarding the risks of reciprocal interference posed by the presence of the device during specific investigations or treatment;	N/A	EN1041	No reciprocal interference.
g	The necessary instructions in the event of damage of the sterile packaging and, where appropriate, details of appropriate methods of re-sterilization;	N/A	EN1041	Not delivered sterile or intended to be sterilized.
h	If the device is reusable, information on the appropriate processes to allow reuse, including cleaning, disinfection, packaging and, where appropriate, the method of sterilization of the device to be re-sterilized, and any restriction on the number of reuses.	A	EN1041	(F) Instructions for Use
	Where devices are supplied with the intention that they be sterilized before use, the instructions for cleaning and sterilization must be such that, if correctly followed, the device will still comply with the requirements in Section I;			
i	Details of any further treatment or handling needed before the device can be used (for example, sterilization, final assembly, etc.);	N/A	EN1041	Not delivered sterile or intended to be sterilized. No final assembly etc.
j	In the case of devices emitting radiation for medical purposes, details of the nature, type, intensity and distribution of this radiation. The instructions for use must also include details allowing the medical staff to brief the patient on any contra-indications and any precautions to be taken. These details should cover in particular:	N/A	EN1041	No emitted radiation.



NOVA TENT – CE FILE

k	Precautions to be taken in the event of changes in the performance of the device;	N/A	EN1041	Not this type of device.
1	Precautions to be taken as regards exposure, in reasonably foreseeable environmental conditions, to magnetic fields, external electrical influence, electrostatic discharge, pressure or variations in pressure, acceleration, thermal ignition sources, etc.;	N/A	EN1041	No precautions need to be taken.
m	Adequate information regarding the medicinal product or products which the device in question is designed to administer, including any limitations in the choice of substances to be delivered;	N/A	EN1041	No medicinal products used.
n	Precautions to be taken against any special, unusual risks related to the disposal of the device;	N/A	EN1041	No risk in disposing of this device
0	Medicinal substances incorporated into the device as an integral part in accordance with section 7.4;	N/A	EN1041	No medicinal products used.
p	Degree of accuracy claimed for devices with a measuring function.	N/A	EN1041	No measurement function
14	Where conformity with the essential requirements must be based on clinical data, as in Section I (6), such data must be established in accordance with Annex X.	N/A		Not required.