

Design & Development Compliance

<u>DESCRIPTION</u>	JOB NUMBER
MICROSTIM DBS Mk3	

1. General	Report
(a) The solutions adopted for the design and construction of the devices must conform to safety principals to eliminate or reduce risks as far as possible (inherently safe design and construction). The device must be designed in such a way that, when used under the conditions and for the purpose intended, it will not compromise the safety of patients, or the safety and health of users or, where applicable, other persons.	The unit has been designed within the parameters allowed within IEC 601
The device must be designed with particular attention to: • Electrical Safety	Electrical Safety Tests
	No moving parts
Moving Parts	No enclosures
Enclosures	Stable Unit
Stability	No expelled parts
Expelled Parts	No vibration or noise
Vibration & Noise (b) Where modification of other manufactured devices is required, written approval will be sought from the manufacturer, otherwise concessionary status will be sought.	
2. Environment	Report
(a) If the device is intended for use in combination with other devices or equipment, the whole combination, including connection system, must be made safe and must not impair the specified performance of the device.	N/A
(b) The devices must be designed in such a way that they can be used safely with the materials, substances and gases with which they enter contact with during their normal use or during routine procedures.	N/A
(c) Accessible parts of the device (excluding parts or areas intended for supply or reach given temperatures) and their surroundings must not attain potentially dangerous temperatures under normal use.	N/A
(d) Devices must be designed and manufactured in such a way as to minimise the risks of fire or explosion during normal use. Particular attention must be paid to devices whose intended use includes exposure to flammable substances or to substances that could cause combustion.	N/A
(e) Devices must be designed and manufactured in such a way as to minimise the risks connected with environmental conditions, such as magnetic fields, external electrical influences, electrostatic discharge, pressure, temperature or variations in pressure and acceleration.	EMC Tests carried out to IEC601
3. Biological Hazards	Report
T:\Michael Lamb\intrastat docs\3 3229\3407.doc	18/04/2011

MICROSTIM DBS_Mk3 - CE File

Mickor	STIM DDS_MK3 - CE FIIE
(a) The device must be designed with particular attention to the choice of materials used, particularly as regards toxicity and where appropriate, flammability.	N/A
(b) The device must be designed with particular attention to the compatibility between materials used and biological tissues, cells and fluids, taking account of the intended purpose of the device.	N/A
(c) The device must be designed in such a way as to minimise the risks posed by the unintentional ingress of substances into the device taking into account the device and the environment in which it is intended to be used.	N/A
(d) The device must be designed with particular attention to reducing to a minimum the risks posed by substances leaking from the device.	N/A
4. Material Physical Properties	Report
(a) The materials used shall be appropriate for the intended purpose, taking account of strength, elasticity, melting point, porosity, conductance etc.	Plastic casing
(b) The surface finishes shall be suitable for the intended purpose of the device.	
(c) The materials selected shall be appropriate for any sterilisation / disinfection / cleaning requirements.	Plastic casing
(d) The characteristics and performance must not be adversely affected to such a degree that the clinical conditions and safety of the patients and, where applicable, of other persons are compromised when the device is subjected to the stresses which can occur during the normal conditions of use i.e. ageing and corrosion.	N/A
5. User Information	Report
(a) Each device must be accompanied by the information needed to use it safely, taking account of the training and knowledge of the potential users. This information comprises details on the label and the data in the instructions for use.	Instruction leaflet supplied
(b) Where appropriate, this information should take the form of symbols. Any symbol or identification colour used must conform to the harmonised standards.	Labelled – BS EN 980 & IEC 601
The label must bear the following particulars:	
Identification of Viamed as the Manufacturer. If the device is custom made, the words "Custom-made Device"	Yes
The label or instructions must contain the following instructions where applicable:	
Any special storage or handling precautions	N/A
Any special operating instructions	Yes – see insert
Any warnings and / or precautions to be taken	Yes – see insert
Where appropriate, the method of sterilisation	Not sterile
6. Contamination	Report
(a) The device must be designed in such a way as to eliminate, or	N/A
(a) The device must be designed in such a way as to climinate, or	

$MICROSTIM\ DBS_Mk3\ -\ CE\ File$

	Tillettes	STIM DDS_MK5 - CE FILE
reduce as far as possible, the risk of infect parties. The design must allow easy himinimise contamination of the device by use.	nandling and, where necessary,	
(b) Devices delivered in a sterile stareusable pack and remain sterile unde conditions, until the protective packaging	er normal transport and storage	Not Sterile
(c) Devices delivered in a sterile sta an appropriate method.	ate must have been sterilised by	Not Sterile
(d) Devices that require sterilisation the user in a non-sterile state, will		Not Sterile
(e) The packaging for non-sterile de cleanliness without deterioration, and contamination. The packaging system account the method of sterilisation recom	minimise the risk of microbial must be suitable, taking into	Not Sterile
7. Radiation		Report
(a) Devices must be designed and r exposure of patients, users and be reduced as far as possible purpose, whilst not restricting specified levels for therapeutic an	other persons, to radiation shall , compatible with the intended the application of appropriate	N/A
(b) Where devices are designed to emit hazardous levels of radiation necessary for a specific medical purpose the benefit of which is considered to outweigh the risks inherent in the emissions. It must be possible for the user to control the emissions. Such devices shall be designed and manufactured to ensure reproducibility and tolerance of relevant parameters.		N/A
(c) Where devices are intended to e and / or invisible radiation, they n with visual diplayed and / or audib	must be fitted, where practicable,	N/A
 (d) Devices shall be designed and new posure of patients, users and continued of the continued	other persons to the emissions of	N/A
(e) The operating instructions for devidetailed information as to the means of protecting the patient avoiding misuse and of eliminating	nature of the emitted radiation, and the user, and on ways of	N/A
Standards and Statutory Requirements		
appropriate at this stage Requirement		

MVIAMED	MICROSTIM DBS_Mk3 - CE File
Final Design Tests Dranged	Accordance Cuitavia for Toota
Final Design Tests Proposed Tested to Viamed Specifications	Acceptance Criteria for Tests Viamed
·	
All test equipment subject to:	
All test equipment subject to: "NAMAS" Calibration Trace ability	
Quotation Authorised by: Name:	Date:
Name.	Date.

Drawings Enclosed: Yes () No () Not Applicable ()