Device Essential Requirements Checklist (in compliance with the 93/42/EEC Medical Device Directive).

Product:	Thermistor	New product:	No
Part number:	0210 Series	Existing Produc	et: Yes
Description:	Temperature Probes	Introduced:	1980
Class:	I & IIa	Main Standard:	BS EN 60539

No.	Essential Requirement.	A/NA.	Standard.	Report.
I	General Requirements			
1.	The devices must be designed and manufactured in such a way that, when used under the conditions and for the purposes intended, they will not compromise the clinical condition or the safety of patients, or the safety and health of users or, where applicable, other persons, provided that any risks which may be associated with their use constitute acceptable risks when weighed against the benefits to the patient and are compatible with a high level of protection of health and safety.	A	IEC 601/1	Manufactured to ISO 9000 quality standards. (E) Risk analysis. (YZ) Design File
2.	The solutions adopted by the manufacturer for the design and construction of the devices must conform to safety principles, taking account of the generally acknowledged state of the art. - Eliminate or reduce risks as far as possible	A	BS EN ISO 14971:2001	Compatibility with OEM Product (E) Risk analysis. Known risks reduced for hazards identified (E) Risk analysis
	(inherently safe design and construction),			
	- Where appropriate take adequate protection measures including alarms if necessary, in relation to risks that cannot be eliminated,	A	BS EN 980	(E) Risk analysis
	- Inform users of the residual risks due to any shortcomings of the protection measures adopted	A	EN1041	(E) Risk analysis (F) User manual
3.	The devices must achieve the performances intended by the manufacturer and be designed, manufactured and packaged in such a way that they are suitable for one or more of the functions referred to in Article 1 (2) (a), as specified by the manufacturer.	A		(YZ) Design File (M) Packaging trials & Validation.
4.	The characteristics and performances referred to in Sections 1, 2 and 3 must not be adversely affected to such a degree that the clinical conditions and safety of the patients and, where applicable, of other persons are compromised during the lifetime of the device as indicated by	A	BS EN ISO 14971:2001.	(E) Risk analysis



				_
	the manufacturer, when the device is subjected			
	to the stresses which can occur during normal			
	conditions of use.			
5.	The devices must be designed, manufactured	A		(M) Packaging trials
] 3.	and packed in such a way that their	71		& validation
	characteristics and performances during their			(T) Manufacturers
	intended use will not be adversely affected			data & Materials
	during transport and storage taking account of			Specifications
	the instructions and information provided by			
	the manufacturer.			
6.	Any undesirable side effect must constitute an	N/A	BS EN ISO	No known side
	acceptable risk when weighed against the		14971:2001	effects
	performances intended.			(E) Risk analysis
II	Requirements Regarding Construction &			(_)
11	Design Constitution			
7				
7.	Chemical, physical and biological properties			Madiant 1
7.1	The devices must be designed and	Α		Medical grade
	manufactured in such a way as to guarantee the			materials used
	characteristics and performances referred to in			Manufacturers data
	Section I on the 'General requirements'.			(T) Material
	Particular attention must be paid to:			specifications
	-The choice of materials used, particularly as	Α		Non-inflammable
	regards toxicity and, where appropriate,			(YZ) Design
	flammability,			Reviews
	The state of the s			(T) Material
				specifications
	- The compatibility between the materials used	A		Medical grade
		A		materials used
	and biological tissues, cells and body fluids,			
	taking account of the intended purpose of the			(T) Material
	device.			specifications
7.2	The devices must be designed, manufactured	Α		Manufactured to
	and packed in such a way as to minimize the			ISO 9000 quality
	risk posed by contaminants and residues to the			standards.
	persons involved in the transport, storage and			(E) Risk analysis
	use of the devices and to the patients, taking			(M) Packaging trials
	account of the intended purpose of the product.			& validation
	Particular attention must be paid to the tissues			
	exposed and to the duration and frequency of			
	exposure.			
7.2	•	Α.	1	(V7) Degian Eile
7.3	\mathcal{E}	A		(YZ) Design File
	manufactured in such a way that they can be			(T) Material
	used safely with the materials, substances and			specifications –
	gases with which they enter into contact during			materials
	their normal use or during routine procedures; if			comparable to OEM
	the devices are intended to administer			
	medicinal products they must be designed and			
	manufactured in such a way as to be compatible			
	with the medicinal products concerned			
	according to the provisions and restrictions			
	governing these products and that their			
	150 verming these products and that then			I



	performance is maintained in accordance with			
	the intended use.			
7.4	Where a device incorporates, as an integral part,	N/A		No Medicinal
	a substance which, if used separately, may be			Products
	considered to be a medicinal product as defined			
	in Article 1 of Directive 65/65/EEC and which			
	is liable to act upon the body with action			
	ancillary to that of the device, the safety,			
	quality and usefulness of the substance must be			
	verified, taking account of the intended purpose			
	of the device, by analogy with the appropriate			
	methods specified in Directive 75/318/EEC.			
7.5	The devices must be designed and			Nothing to Leak
	manufactured in such a way as to reduce to a			
	minimum the risks posed by substances leaking			
	from the device.			
7.6	Devices must be designed and manufactured in	A	BS EN ISO	Device sealed
	such a way as to reduce, as much as possible,		14971:2001	against moisture
	risks posed by the unintentional ingress of			ingress
	substances into the device taking into account			(YZ) Design File
	the device and the nature of the environment in			
	which it is intended to be used.			
8	Infection and microbial contamination			
8.1	The devices and manufacturing processes must	A	ISO900:2000	Manufacturing
	be designed in such a way as to eliminate or			procedures.
	reduce as far as possible the risk of infection to			Cleaning
	the patient, user and third parties. The design			Instructions
	must allow easy handling and, where necessary,			Manufacturers Data
	minimize contamination of the device by the			(T) Material
	patient or vice versa during use.			specifications
8.2	Tissues of animal origin must originate from	N/A		No animal origin
"-	animals that have been subjected to veterinary			components
	controls and surveillance adapted to the			T T T
	intended use of the tissues.			
	Notified bodies shall retain information on the			
	geographical origin of the animals.			
	Processing, preservation, testing and handling			
	of tissues, cells and substances of animal origin			
	must be carried out so as to provide optimal			
	security. In particular safety with regard to			
	viruses and other transferable agents must be			
	addressed by implementation of validated			
	methods of elimination or viral inactivation in			
	the course of the manufacturing process.			
8.3	Devices delivered in a sterile state must be	N/A		Non Sterile
3.5	designed, manufactured and packed in a non-			
	reusable pack and/or according to appropriate			
	procedures to ensure that they are sterile when			
	placed on the market and remain sterile, under			
	the storage and transport conditions laid down,			
	until the protective packaging is damaged or			
	partition protective packaging is damaged of		l .	1



	opened.			
8.4	Devices delivered in a sterile state must have been manufactured and sterilized by an	N/A		Not supplied Sterile
	appropriate, validated method.			
8.5	Devices intended to be sterilized must be manufactured in appropriately controlled (e. g. environmental) conditions.	N/A		Not intended to be Sterilised
8.6	Packaging systems for non-sterile devices must keep the product without deterioration at the level of cleanliness stipulated and, if the devices are to be sterilized prior to use, minimize the risk of microbial contamination; the packaging system must be suitable taking account of the method of sterilization indicated by the manufacturer.	A		(F) Cleaning instructions (M) Packaging
8.7	The packaging and/or label of the device must distinguish between identical or similar products sold in both sterile and non-sterile condition.	N/A		Non Sterile
9	Construction and environmental properties			
9.1	If the device is intended for use in combination with other devices or equipment, the whole combination, including the connection system must be safe and must not impair the specified performances of the devices. Any restrictions on use must be indicated on the label or in the instructions for use.	A	BS EN 980 ISO 9001:2000 BS EN ISO 14971:2001	Device fully tested for compatibillity (F) User manual (E) Risk analysis
9.2	Devices must be designed and manufactured in such a way as to remove or minimize as far as is possible: - The risk of injury, in connection with their physical features, including the volume/pressure ratio, dimensional and where appropriate ergonomic features,	N/A		No Sharp edges or areas
	- Risks connected with reasonably foreseeable environmental conditions, such as magnetic fields, external electrical influences, electrostatic discharge, pressure, temperature or variations in pressure and acceleration,	A		EMC rationale
	- The risks of reciprocal interference with other devices normally used in the investigations or for the treatment given,	A		EMC rationale
	- risks arising where maintenance or calibration are not possible (as with implants), from ageing of materials used or loss of accuracy of any measuring or control mechanism.	N/A		No calibration required
9.3	Devices must be designed and manufactured in such a way as to minimize the risks of fire or explosion during normal use and in single fault	N/A		Protection built into Monitors



10	condition. Particular attention must be paid to devices whose intended use includes exposure to flammable substances or to substances, which could cause combustion.			
10	Devices with a measuring function		700 0001 2000	(7.70) 5 1 511
10.1	Devices with a measuring function must be designed and manufactured in such a way as to provide sufficient accuracy and stability within appropriate limits of accuracy and taking account of the intended purpose of the device. The manufacturer must indicate the limits of accuracy.	A	ISO 9001:2000 BS EN 60539-1	(YZ) Design File Specification for Thermistors
10.2	The measurement, monitoring and display scale must be designed in line with ergonomic principles, taking account of the intended purpose of the device.	N/A		Accessory
10.3	The measurements made by devices with a measuring function must be expressed in legal units conforming to the provisions of Council Directive 80/181/EEC (1).	N/A		Accessory
11	Protection against radiation			
11.1	General			
11.1	Devices shall be designed and manufactured in such a way that exposure of patients; users and other persons to radiation shall be reduced as far as possible compatible with the intended purpose, whilst not restricting the application of appropriate specified levels for therapeutic and diagnostic purposes. Intended radiation	N/A		No radiation
11.2.1	Where devices are designed to emit hazardous levels of radiation necessary for a specific medical purpose the benefit of which is considered to outweigh the risks inherent in the emission, it must be possible for the user to control the emissions. Such devices shall be designed and manufactured to ensure reproducibility and tolerance of relevant parameters.	N/A		No radiation
11.2.2	Where devices are intended to emit potentially hazardous, visible and/or invisible radiation, they must be fitted, where practicable, with visual displays and/or audible warnings of such emissions. Unintended radiation	N/A		No radiation
11.3.1	Devices shall be designed and manufactured in such a way that exposure of patients, users and other persons to the emission of unintended, stray or scattered radiation is reduced as far as possible.	N/A		No radiation



11.4	Instructions.			
11.4.1	The operating instructions for devices emitting	N/A	No radiation	
	radiation must give detailed information as to			
	the nature of the emitted radiation, means of			
	protecting the patient and the user and on ways			
	of avoiding misuse and of eliminating the risks			
	inherent in installation.			
11.5	Ionizing radiation			
11.5.1	Devices intended to emit ionizing radiation	N/A	No Ionizing	
	must be designed and manufactured in such a		radiation	
	way as to ensure that, where practicable, the			
	quantity, geometry and quality of radiation			
	emitted can be varied and controlled taking into			
11.5.2	account the intended use.	NT/A	N. I	
11.5.2	Devices emitting ionizing radiation intended for	N/A	No Ionizing	
	diagnostic radiology shall be designed and		radiation	
	manufactured in such a way as to achieve			
	appropriate image and/or output quality for the intended medical purpose whilst minimizing			
	radiation exposure of the patient and user.			
11.5.3	Devices emitting ionizing radiation, intended	N/A	No Ionizing	
11.5.5	for therapeutic radiology shall be designed and	1 1/ / 1	radiation	
	manufactured in such a way as to enable		Tudiation	
	reliable monitoring and control of the delivered			
	dose, the beam type and energy and where			
	appropriate the quality of radiation.			
12	Requirements for medical devices connected to			
	or equipped with an energy source			
12.1	Devices incorporating electronic programmable	N/A	No software	
	systems must be designed to ensure the			
	repeatability, reliability and performance of			
	these systems according to the intended use. In			
	the event of a single fault condition (in the			
	system) appropriate means should be adopted to			
	eliminate or reduce as far as possible			
12.2	consequent risks.	NT/A	A 22	
12.2	Devices where the safety of the patients	N/A	Accessory	
	depends on an internal power supply must be equipped with a means of determining the state			
	of the power supply.			
12.3	Devices where the safety of the patients	N/A	Accessory	
12.5	depends on an external power supply must	1 1/ 1 1	Treecosory	
	include an alarm system to signal any power			
	failure.			
12.4	Devices intended to monitor one or more	N/A	Accessory	
	clinical parameters of a patient must be			
	equipped with appropriate alarm systems to			
	alert the user of situations which could lead to			
	death or severe deterioration of the patient's			
	state of health.			



12.5	D: (1 1 : 1 1 C (1:)		DC (0(01 1 2	C1: 11 1 11
12.5	Devices must be designed and manufactured in	Α	BS 60601-1-2	Shielded cable
	such a way as to minimize the risks of creating			
	electromagnetic fields, which could impair the			
	operation of other devices or equipment in the			
	usual environment.			
12.6	Protection against electrical risks			
12.6.1	Devices must be designed and manufactured in	Α		Protection in
	such a way as to avoid, as far as possible, the			Monitors
	risk of accidental electric shocks during normal			
	use and in single fault condition, provided the			
	devices are installed correctly.			
12.7	Protection against mechanical and thermal risks			
12.7.1	Devices must be designed and manufactured in	A		No moving parts
	such a way as to protect the patient and user			
	against mechanical risks connected with, for			
	example, resistance, stability and moving parts.			
12.7.2	Devices must be designed and manufactured in	N/A		No vibration
	such a way as to reduce to the lowest possible			
	level the risks arising from vibration generated			
	by the devices, taking account of technical			
	progress and of the means available for limiting			
	vibrations, particularly at source, unless the			
	1			
12.7.3	vibrations are part of the specified performance.	NT/A		No noise emitted
12.7.3	Devices must be designed and manufactured in	N/A		No noise emitted
	such a way as to reduce to the lowest possible			
	level the risks arising from the noise emitted			
	taking account of technical progress and of the			
	means available to reduce noise, particularly at			
	source, unless the noise emitted is part of the			
12 - 1	specified performance.			
12.7.4	Terminals and connectors to the electricity, gas	Α		Insulated Jack-Plug
	or hydraulic and pneumatic energy supplies			(E) Risk analysis
	which the user has to handle must be designed			
	and constructed in such a way as to minimize			
	all possible risks.			
12.7.5	Accessible parts of the devices (excluding the	N/A		Low temperature
	parts or areas intended to supply or reach given			only
	temperatures) and their surroundings must not			
	attain potentially danger temperatures under			
	normal use.			
12.8	Protection against the risks posed to the patient			
	by energy supplies or substances			
12.8.1	Devices for supplying the patient with energy	N/A		No flow rates
	or substances must be designed and constructed			involved
	in such a way that the flow-rate can be set and			
	maintained accurately enough to guarantee the			
	safety of the patient and of the user.			
12.8.2	Devices must be fitted with the means of	N/A		No flow rates
	preventing and/or indicating any inadequacies	- 1/		involved
	in the flow-rate, which could pose a danger.			
	in the field, which could pose a dailget.		1	-



	,		ı	1
	Devices must incorporate suitable means to			
	prevent, as far as possible, the accidental			
	release of dangerous levels of energy from an			
	energy and/or substance source.			
12.9	The function of the controls and indicators must	N/A		
	be clearly specified on the devices.			
	Where a device bears instructions required for			
	its operation or indicates operating or			
	adjustment parameters by means of a visual			
	system, such information must be			
	understandable to the user and, as appropriate,			
	1			
1.2	the patient.			
13	Information supplied by the manufacturer		D.C. 23.1.000	
13.1	Each device must be accompanied by the	A	BS EN 980.	Information supplied
	information needed to use it safely and to		EN1041	by the manufacturer
	identify the manufacturer, taking account of the			with medical devices
	training and knowledge of the potential users.			(F) User manual,
	This information comprises the details on the			
	label and the data in the instructions for use.			
	As far as practicable and appropriate, the			
	information needed to use the device safely			
	must be set out on the device itself and/or on			
	the packaging for each unit or, where			
	appropriate, on the sales packaging. If			
	individual packaging of each unit is not			
	practicable, the information must be set out in			
	the leaflet supplied with one or more devices.			
	Instructions for use must be included in the			
	packaging for every device. By way of			
	exception, no such instructions for use are			
	needed for devices in Class I or II(a) if they can			
	be used safely without any such instructions.			
13.2	Where appropriate, this information should take	Α	BS EN 980.	Graphic symbols for
	the form of symbols. Any symbol or		EN1041	use in the labeling of
	identification color used must conform to the			medical devices
	harmonized standards. In areas for which no			(F) Labels
	standards exist, the symbols and colors must be			
	described in the documentation supplied with			
	the device.			
13.3	The label must bear the following particulars	A	BS EN 980	Graphic symbols for
13.3	The facet must bear the following particulars	11	EN1041	use in the labeling of
			LATOT1	medical devices
				All controls are
				marked
			D 0 D 2	(F) labels
(a)	The name or trade name and address of the	A	BS EN 980	(F) Label
	manufacturer. For devices imported into the		EN1041	
	Community, in view of their distribution in the			(F) User manual
	Community, the label, or the outer packaging,			
	or instructions for use, shall contain in addition			
	the name and address of either the person			
	1		1	1



	responsible referred to in Article 14 (2) or of			
	the authorized representative of the			
	manufacturer established within the			
	Community or of the importer established			
	within the Community, as appropriate;			
(b)	The details strictly necessary for the user to	A	BS EN 980	(F) Label
	identify the device and the contents of the	7.1	EN1041	(1) Edoci
	packaging;		LIVIOTI	(F) User manual
(0)	Where appropriate, the word 'STERILE';	N/A		Not Sterile
(c)		A	BS EN 980	(F) Label
(d)	Where appropriate, the batch code, preceded by	А		` /
	the word 'LOT', or the serial number;		EN1041	(F) User manual
				(F) Serial number
				label
(e)	Where appropriate, an indication of the date by	N/A		Not required – No
	which the device should be used, in safety,			end of life set
	expressed as the year and month;			
(f)	Where appropriate, an indication that the device	N/A		Multiple use device
	is for single use;			
(g)	If the device is custom-made, the words	N/A		Not Custom-made
	'custom-made device';			
(h)	If the device is intended for clinical	N/A		Not exclusively for
	investigations, the words 'exclusively for			clinical use
	clinical investigation';			
(i)	Any special storage and/or handling conditions;	N/A		None required
(j)	Any special operating instructions;	A	BS EN 980	(F) User manual
(k)	Any warnings and/or precautions to take;	A	BS EN 980	(F) User manual
(1)	Year of manufacture for active devices other	N/A	BS EI () 00	On Cable Label
(1)	than those covered by (c). This indication may	1 1/ /1		On Cable Laber
	be included in the batch or serial number;			
(122)	i i	NT/A		Not to be Sterilised
(m)	Where applicable, method of sterilization.	N/A	DC EN 000	
13.4	If the intended purpose of the device is not	A	BS EN 980	Intended purpose is
	obvious to the user, the manufacturer must		EN1041	obvious
	clearly state it on the label and in the			(F) User manual
	instructions for use.			
13.5	Wherever reasonable and practicable, the	N/A		No detachable
	devices and detachable components must be			components
	identified, where appropriate in terms of			
	batches, to allow all appropriate action to detect			
	any potential risk posed by the devices and			
	detachable components			
13.6	Where appropriate, the instructions for			
	use must contain the following particulars:			
(a)	The details referred to in Section 13.3, with the	A	BS EN 980	Full Instruction
	exception of (d)&(c);		EN1041	leaflet supplied
				(F) User manual
(b)	The performances referred to in Section 3 and	N/A		No side effects
	any undesirable side-effects;	1 1/ / 1		110 5140 5110065
(c)	If the device must be installed with or	A	BS EN 980	Full Instruction
	connected to other medical devices or	11	EN1041	leaflet supplied
	equipment in order to operate as required for its		LINIUTI	(F) User manual
	requipment in order to operate as required for its			(1) Oser manuar



	T			
	intended purpose, sufficient details of its characteristics to identify the correct devices or equipment to use in order to obtain a safe			
(d)	combination; All the information needed to verify whether	N/A		No Calibration
	the device is properly installed and can operate correctly and safely, plus details of the nature and frequency of the maintenance and calibration needed to ensure that the devices operate properly and safely at all times;	- " -		
(e)	Where appropriate information to avoid certain risks in connection with implantation of the device;	N/A		Not implantable
(f)	Information regarding the risks of reciprocal interference posed by the presence of the device during specific investigations or treatment;	N/A		
(g)	The necessary instructions in the event of damage of the sterile packaging and, where appropriate, details of appropriate methods of re-sterilization;	N/A		Not sterile
(h)	If the device is reusable, information on the appropriate processes to allow reuse, including cleaning, disinfection, packaging and, where appropriate, the method of sterilization of the device to be re-sterilized, and any restriction on the number of reuses.	A	BS EN 980 EN1041	Full Instruction leaflet supplied (F) User manual
	Where devices are supplied with the intention that they be sterilized before use, the instructions for cleaning and sterilization must be such that, if correctly followed, the device will still comply with the requirements in Section I;	N/A		Not Sterile
(i)	Details of any further treatment or handling needed before the device can be used (for example, sterilization, final assembly, etc.);	N/A		No treatment required
(j)	In the case of devices emitting radiation for medical purposes, details of the nature, type, intensity and distribution of this radiation. The instructions for use must also include details allowing the medical staff to brief the patient on any contra-indications and any precautions to be taken. These details should cover in particular:	N/A		No radiation
(k)	Precautions to be taken in the event of changes in the performance of the device;	N/A		
(1)	Precautions to be taken as regards exposure, in reasonably foreseeable environmental conditions, to magnetic fields, external electrical influence, electrostatic discharge, pressure or variations in pressure, acceleration,	A	BS EN 980 EN1041	MRI Advice in Leaflet Full Instruction leaflet supplied (F) User manual



	thermal ignition sources, etc.;		
(m)	Adequate information regarding the medicinal product or products which the device in question is designed to administer, including any limitations in the choice of substances to be delivered;		Does not administer substances
(n)	Precautions to be taken against any special, unusual risks related to the disposal of the device;	N/A	No risks in disposable of the device
(0)	Medicinal substances incorporated into the device as an integral part in accordance with section 7.4;	N/A	No medicinal products used
(p)	Degree of accuracy claimed for devices with a measuring function.	A	(YZ) Specification (F) User Manual
14.	Where conformity with the essential requirements must be based on clinical data, as in Section I (6), such data must be established in accordance with Annex X.	A	Compatibility tests only required