



QQHM2.E143128 Power Supplies, Medical and Dental - Component

Page Bottom

Power Supplies, Medical and Dental - Component

See General Information for Power Supplies, Medical and Dental - Component

FRIWO GERAETEBAU GMBH

E143128

VON-LIEBIG-STR 11

48346 OSTBEVERN, GERMANY

Model No.	Rated Input		SC	Output			OC	SP	EP	FC	GC
	V	Hz		Max V	Max A	Max VA					
FW7555M/XX (a)(b)	120	50-60	0	5-24	2.4-0.625	15	4	2601-1	—	0	0
FW7555MP/XX (a)(b)	120	50-60	0	5-24	2.4-0.625	15	4	2601-1	—	0	0
FW7362M/xx (a)(b)	120	50-60	0	5-24	4-1.25	30	4	2601-1	—	0	0
FW7333M/XX (a)(c), FW7333SM/XX (a)(c)	120	60	0	3-24	1.7-0.33	10	4	2601-1	—	0	0
Open Frame Power Supply FW7333S/PCBA (a)(c)	120	60	0	3-24	1.7-0.33	10	4	2601-1	—	0	0
FW7405M/XX (b)	120	50-60	0	5-24	5.0-2.2	53	4	60601-1	—	0	0
15.2394	120	50-60	0	12 Vdc	1.4	—	9	60601-1	—	0	0
T14-50 I 1131	100-240	50-60	0	19Vdc	2.1	—	4	60601-1	—	0	2
FW3299M	120	60	0	12	400	—	4	2601	20B	0	0
FW7401M/(A) (a) (d)	100-240	50-60	0	5-24	2.0-0.5	—	4	60601-1	—	0	0
FW7660M/XX (b)	120	50-60	0	5-24Vdc	1.6 - 0.42	12	4	60601-1	—	0	2
FW7333/152332	120	50-60	0	5 Vdc	0.35	—	4	60601-1	—	0	0
FW7219/NI 4-10	120	50-60	0	4.8-12 Vdc	0.8	—	9	60601-1	—	0	0
FW7219/LION 2 may be followed by NTC	120	50-60	0	7.4 Vdc	0.8	—	9	60601-1	—	0	0
FW7219/LION 3 may be followed by NTC	120	50-60	0	11.1 Vdc	0.8	—	9	60601-1	—	0	0
FW7219/LION 4 may be followed by NTC	120	50-60	0	14.8 Vdc	0.8	—	9	60601-1	—	0	0

(a) Values given for Max V, Max A and Max VA are rated values.

(b) XX can be any number from 5-24 denoting the output voltage.

(c) XX can be any number from 3-24 denoting the output voltage.

(d) (A) can be the following number 5, 6, 8, 9, 12, 15, 18 and 24 denoting the output voltage.



Marking: Company name or trademarks "FRIWO", "FWGB", "FWHK", "FWHC", "FWMX" or trademark and model designation.

Last Updated on 2008-03-26

[Questions?](#)[Notice of Disclaimer](#)[Page Top](#)

[Copyright © 2008 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





QQHM8.E143128

Power Supplies, Medical and Dental Certified for Canada - Component

Page Bottom

Power Supplies, Medical and Dental Certified for Canada - Component

See General Information for Power Supplies, Medical and Dental Certified for Canada - Component

FRIWO GERAETEBAU GMBH

E143128

VON-LIEBIG-STR 11

48346 OSTBEVERN, GERMANY



Model No.	Rated Input		SC	Output			OC	SP	EP	FC	GC
	V	Hz		Max V	Max A	Max VA					
FW7555M/XX (a)(b)	120	50-60	0	5-24	2.4-0.625	15	4	2601-1	—	0	0
FW7555MP/XX (a)(b)	120	50-60	0	5-24	2.4-0.625	15	4	2601-1	—	0	0
FW7362M/xx (a)(b)	120	50-60	0	5-24	4-1.25	30	4	2601-1	—	0	0
FW7333M/XX (a)(c), FW7333SM/XX (a)(c)	120	60	0	3-24	1.7-0.33	10	4	2601-1	—	0	0
Open Frame Power Supply FW7333S/PCBA (a)(c)	120	60	0	3-24	1.7-0.33	10	4	2601-1	—	0	0
FW7405M/XX (b)	120	50-60	0	5-24	5.0-2.2	53	4	60601-1	—	0	0
15.2394	120	50-60	0	12 Vdc	1.4	—	9	60601-1	—	0	0
T14-50 I 1131	100-240	50-60	0	19Vdc	2.1	—	4	60601-1	—	0	2
FW3299M	120	60	0	12	400	—	4	2601	20B	0	0
FW7401M/(A) (a) (d)	100-240	50-60	0	5-24	2.0-0.5	—	4	60601-1	—	0	0
FW7660M/XX (b)	120	50-60	0	5-24Vdc	1.6 - 0.42	12	4	60601-1	—	0	2
FW7333/152332	120	50-60	0	5 Vdc	0.35	—	4	60601-1	—	0	0
FW7219/NI 4-10	120	50-60	0	4.8-12 Vdc	0.8	—	9	60601-1	—	0	0
FW7219/LION 2 may be followed by NTC	120	50-60	0	7.4 Vdc	0.8	—	9	60601-1	—	0	0
FW7219/LION 3 may be followed by NTC	120	50-60	0	11.1 Vdc	0.8	—	9	60601-1	—	0	0
FW7219/LION 4 may be followed by NTC	120	50-60	0	14.8 Vdc	0.8	—	9	60601-1	—	0	0

(a) Values given for Max V, Max A and Max VA are rated values.

(b) XX can be any number from 5-24 denoting the output voltage.

(c) XX can be any number from 3-24 denoting the output voltage.

(d) (A) can be the following number 5, 6, 8, 9, 12, 15, 18 and 24 denoting the output voltage.

Marking: Company name or trademarks "FRIWO", "FWGB", "FWHK", "FWHC", "FWMX" or , model designation and Recognized Component Mark for



[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2008 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

