









Part		CapnoTrue® AMP / ASP / MG – compatibility of component versions	
Front housing	Photo		
	REF:	3090512025	5090512006 (incl. Window - AMP REF: 4090512019 , ASP REF: 4090512020 , MG REF: 4090512021)
	Info	Initial version	Shaft shorter and with metal nut
Housing screws (long)	Photo		
Screws short with no change	Info	Long screws are Tin, 10 mm	Long screws are metal with fine thread, 20 mm
V-holder	Photo		
	REF:	3090122008	4090122001
	Info	Initial version	ID screw is larger. Use metal fine thread screws to connect to device
V-holder screws	Photo		
	Info	Tin, 18mm	Metal, fine thread, 26mm

Part		CapnoTrue® AMP / ASP / MG – compatibility of component versions				
Silicone Cover	Rev.					
	REF:	3090122006		6090122004		
	Info	Initial version		V-holder can be connected while silicone cover is attached		
Back housing includes Battery contacts + cables, Battery cover, power supply connector rear label, USB port cover	Photo					 10090512007 (blue); 10090512008 (yellow)
	REF:	3090512013 (blue); 3090512012 (yellow)		4090512022 (blue); 4090512023 (yellow)	6090512007 (blue); 6090512008 (yellow)	
	Info	Initial version		Shaft screw longer, bigger ID	Fits UL power connector	
Power connector	Photo					  Housing with connector REF: 8090500001 to fit power supply REF: 10090122001 + power PCB and battery contacts
	REF:	3090512001			6090512010	
	Info	Black female connector – initial version (NO UL)			Fits metal male connector (UL)	
Power supply	Photo	 			 	 
	REF:	3090122002			6090122003	10090122001
	Info	Output: 6V; NOT UL connector (black)			UL approved, connector (orange)	UL approved, bluepoint connector (black)