

blenders



# MaxBlend 2

An all-in-one blender, O<sub>2</sub> monitor and flow meter



- Backlit LCD display
- Easy-to-use Smart Alarms
- Dual Scale Acrylic DFB Flow Meter with back light

The MaxBlend 2 has been designed by Maxtec with years of customer feedback in mind.

This easy-to-use, low maintenance blender has a range of new features and improvements, including a backlit LCD display and acrylic flow meter, smart alarms, DC power port, extended battery life plus a 2 year manufacturers warranty.

 VIAMED

# MaxBlend 2

## Specifications

Model Weight	Approximately 2404 g (5.3 lbs)
Power Source	4 x AA alkaline batteries
Battery Life	5,000 hours (continuous operation; no alarms, no lights)
Oxygen Concentration Measurement Range	0 - 100% oxygen
Display Resolution	0.1% oxygen
Oxygen Concentration Adjustment Range	21% to 100% oxygen
Gas Supply Pressure	The gas supplies must provide clean, dry, medical-grade air and oxygen at a pressure of 30 to 75 psig (2.1 to 5.2 bar). Optimal performance is achieved at 50 psig inlet pressures
Pressure Drop	Less than 6 psi (0.4 bar) @ 50 psig (3.4 bar) sensor supply pressure and 10 lpm flow rate
Sensor Bleed Flow	0.1 lpm @ 50 psig (3.4 bar)
Bleed Flow (toggle ON)	3 lpm for low-flow blender and 13 lpm for high-flow blender
Outlet Flow Range	0 - 30 lpm for low-flow blender 2 - 100 lpm for high-flow blender with input pressure at 50 psig (3.4 bar)
Operating Temperature Range ??	15°C to 50°C (59°F to 104°F)
Relative Humidity Range ??	0 - 95%, non-condensing
Flow Meter Accuracy ??	± 10% of indicated value or 0.5 lpm, whichever is greater with 50 psig inlet pressure
<b>Part Numbers</b>	
MaxBlend 2 - Low Flow 0 - 15 lpm	0310291

**Specifications subject to change**

Distributed by:



**Viamed Limited** · 15 Station Road · Cross Hills  
Keighley · West Yorkshire · BD20 7DT · United Kingdom  
Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582  
Email: [info@viamed.co.uk](mailto:info@viamed.co.uk) Website: [www.viamed.co.uk](http://www.viamed.co.uk)

