

# DVM Calibration record

|    |   |             |
|----|---|-------------|
| 1  | DVM Calibration Index Number            | CE112       |
| 2  | DVM Bar code                            | 102096      |
| 3  | Equipment Used                          | MICROCAL    |
| 4  | Serial number Test Equipment            | 6939K6      |
| 5  | Calibration Certificate Number          | 1580162     |
| 6  | Test Equipment Calibration Index Number | CE076       |
|    |   |             |
|    | Micro Cal @                             | DVM Reading |
| 7  | 0mV +/- 0.1                             | 0           |
| 8  | 5mV +/- 0.1                             | 5.0         |
| 9  | 10mV +/- 0.1                            | 10.0        |
| 10 | 15mV +/- 0.1                            | 15.0        |
| 11 | 20mV +/- 0.1                            | 20.0        |
| 12 | 25mV +/- 0.1                            | 25.0        |
| 13 | 30mV +/- 0.1                            | 30.0        |
| 14 | 35mV +/- 0.1                            | 35.0        |
| 15 | 40mv +/- 0.1                            | 40.0        |
| 16 | Pass / Fail                             | PASS        |
| 17 | Tested By                               | P CROSSLEY  |
| 18 | Tested On                               | 8.8.19      |
| 19 | Signed                                  | PC Crossley |

1. Enter the details of the unit being tested in boxes 1 – 2

2. Enter the details of the calibrated Micro Cal unit being used to test against the equipment. In to boxes 3 -6

Ensure the calibrated unit is still inside its calibration period before you begin.

3. set the micro cal to the required settings (7 – 15) and enter the readings on the DVM in the Boxes

4. Assuming the units passes the tests, date and sign the form (17 – 19). Scan the form and upload to the issue requesting calibration and complete the Issue.

If the unit fails the test return the Unit to RS for calibration