

VIAMED

Suppliers of
Electromedical
Equipment

2011



Skipton Castle, North Yorkshire

January

M	30	3	10	17	23
T	31	4	11	18	24
W	5	12	19	25	
T	6	13	20	26	
F	7	14	21	27	
S	1	8	15	22	28
S	2	9	16	22	29

February

M	7	14	21	28
T	1	8	15	22
W	2	9	16	23
T	3	10	17	24
F	4	11	18	25
S	5	12	19	26
S	6	13	20	27

March

M	7	14	21	28
T	1	8	15	22
W	2	9	16	23
T	3	10	17	24
F	4	11	18	25
S	5	12	19	26
S	6	13	20	27

April

M	4	11	18	25
T	5	12	19	26
W	6	13	20	27
T	7	14	21	28
F	1	8	15	22
S	2	9	16	23
S	3	10	17	24

May

M	30	2	9	16	23
T	31	3	10	17	24
W	4	11	18	25	
T	5	12	19	26	
F	6	13	20	27	
S	7	14	21	28	
S	1	8	15	22	29

June

M	6	13	20	27
T	7	14	21	28
W	1	8	15	22
T	2	9	16	23
F	3	10	17	24
S	4	11	18	25
S	5	12	19	26

July

M	4	11	18	25
T	5	12	19	26
W	6	13	20	27
T	7	14	21	28
F	1	8	15	22
S	2	9	16	23
S	3	10	17	24

August

M	1	8	15	22	29
T	2	9	16	23	30
W	3	10	17	24	31
T	4	11	18	25	
F	5	12	19	26	
S	6	13	20	27	
S	7	14	21	28	

September

M	5	12	19	26
T	6	13	20	27
W	7	14	21	28
T	1	8	15	22
F	2	9	16	23
S	3	10	17	24
S	4	11	18	25

October

M	31	3	10	17	24
T	4	11	18	25	
W	5	12	19	26	
T	6	13	20	27	
F	7	14	21	28	
S	1	8	15	22	29
S	2	9	16	23	30

November

M	7	14	21	28
T	1	8	15	22
W	2	9	16	23
T	3	10	17	24
F	4	11	18	25
S	5	12	19	26
S	6	13	20	27

December

M	5	12	19	26
T	6	13	20	27
W	7	14	21	28
T	1	8	15	22
F	2	9	16	23
S	3	10	17	24
S	4	11	18	25



VIAMED

15 Station Road • Cross Hills • Keighley • West Yorkshire • BD20 7DT • UK
Tel: +44 (0)1535 634 542/ 636 757 • Fax: +44 (0)1535 635 582
www.viamed-online.com • info@viamed.co.uk



VM-2500-M / VM-2500-S

High performance capnography with either mainstream or sidestream measurement



**Fastest
warm-up
time on the
market**

- Robust and ergonomic design.
- Fastest warm-up time in the industry.
- Rapid response time.
- Extremely accurate and reliable measurement
- CO_2 and SpO_2 combined.
- Displays EtCO_2 , FiCO_2 , SpO_2 , respiration and pulse rate, capnogram and plethysmogram.
- Maintenance and calibration FREE technology.
- Clear and bright, colour OLED display offers superior clarity at any angle.
- For intubated or non-intubated patients.
- Stores up to 400 hours of trending information.
- Adjustable high and low level alarms.
- Wide range of accessories and SpO_2 sensors are available

The ultra-compact, ergonomic design of the VM-2500 combines outstanding performance and reliability in either mainstream or sidestream CO_2 and SpO_2 monitoring.

VM-2500-M Mainstream CO_2 & SpO_2 Monitor



VM-2500-S Sidestream CO_2 & SpO_2 Monitor



Key Features of the VM-2500-M

- Mainstream CO_2 measurement with the **IRMA™ CO_2 Analyser**.
- Fast warm-up time of LESS than 10 seconds to full specification.
- 'PLUG-IN and MEASURE...'™ technology - **no integration procedures** or associated expenses required.
- **No occlusion by water or mucus possible**.
- **IRMA airway adapter with XTP™ non-condensing light transmission window**.
- Small, lightweight and shock-resistant; the **IRMA™ CO_2 Analyser** weighs less than 30g.
- Direct measurement without time delay.
- Predominately for intubated patients.
- Maintenance and calibration FREE technology.

Key Features of VM-2500-S

- Sidestream CO_2 measurement with the **ISA™ CO_2 Analyser** and Nomo technology.
- Fast warm-up time of LESS than 10 seconds to full specification.
- The Nomo technology contained in the **Nomo Adapter removes water and vapour** from the sampled gas.
- The Nomo Adapter includes a hydrophobic bacterial filter to **protect against water intrusion and cross contamination**.
- Specifically designed for **low flow applications**; 50 ml/min sampling flow for all applications, from adults to neonates.
- Predominately used on non-intubated patients.
- Maintenance and calibration FREE technology.

Tel: +44 (0)1535 634542

Fax: +44 (0)1535 635582

info@viamed.co.uk

www.viamed-online.com



BS EN ISO 9001:2000
ISO 13485:2003
ISO 13485:2003 CMDCAS Recognised

FS 28344 MD 78787



VIAMED