

infant resuscitation



Infant Resuscitation Cabinet

Provides essential equipment for safe and easy infant resuscitation.
Featuring a number of recent improvements.



- Wall mounted radiant warmer.
- Tom Thumb Infant Resuscitation Unit.
- Low suction controller.
- Vacsax suction receiving system, utilising disposable liners.
- Wide bed (35 cm), designed to prevent mattress movement.
- Sealed mattress, manufactured to BS5852 (Crib5) standards.
- Digital Apgar Timer, audible indication at 1, 5 and 10 minutes.
- Storage bins.

New
and
Improved

The Viamed Infant Resuscitation Cabinet offers an economical, convenient solution for the delivery room. Compact and discreet, the cabinet is unobtrusive when not in use, yet facilitates the essential equipment for safe and easy resuscitation.

The whole installation has a low profile and is ideally suited to even the smallest delivery rooms.

VIAMED

Infant Resuscitation Cabinet

Features

- Low profile, discreet.
- Economical: several delivery rooms can be equipped for the cost of a traditional mobile unit.
- Provides a permanent, always ready solution for each individual delivery room.
- Easy to operate, safe and fatigue-free resuscitation.

Cabinet

Dimensions	660 mm (H) x 650 mm (W) x 280 mm (D)
Weight	19kg (Empty), 25kg (with standard accessories)
Medirails	3 (standard 30 mm x 10 mm), length 240 mm
Shelving	Integral drugs shelf and 3 bin rails
Storage	3 storage bins (blue, size 3 Lin bin)
Bed	Flat, 35 cm, (14") wide
Mattress	Sealed design, manufactured to BD5852 (Crib5) standards
Digital Apgar Timer	Preset audible indicators at 1, 5 and 10 minute intervals



Tom Thumb Infant Resuscitation Unit

Connection	3m hose to wall oxygen outlet
Flow meter	Integral, 0-15 Lpm (option without flow meter is also available)
Pressure	Adjustable, provides complete control
Emergency blow-off valve	Factory set to a fixed, predefined pressure level
Patient circuit	One standard occlusion circuit included

Low Suction Controller

Suction	Variable, 0-150 mmHg (relief valve at -180 mmHg)
Scaling	Dual, -kPa and -mmHg
Connection to wall suction	3m hose with BS probe
Receiving jar	1 litre reusable Vacsax cannister with disposable liner

Ceratherm 600-2 Radiant Warmer

Power requirements	230VAC, 50-60Hz
Power rating	620VA
Element	Ceramic, 600W. Efficient with fast warm up
Output	4 programmable levels, 0 - 99 %
Lighting	20W halogen lamp, dazzle-free illumination of work area
Alarms	Audible and visual, 15 minutes with reset function
Mounting	Wall mounted articulated boom arm, folds flat to the wall when not in use. Mobile radiant warmers also available
Certifications	IEC 601-2, CE0123



Cabinets are available in a variety of configurations suited to individual requirements. The pictures to the right depict a cabinet configuration which has a Tom Thumb unit without an integral flow meter, so as to be used with an existing external flow meter.

The cabinet is also a custom design whereby extended Medirails were chosen in preference to bin rails and storage bins. The outlet holes for the hoses were also moved from the default position in the bottom of the cabinet to the top.

Installation of cabinets and warmers are the responsibility of the customer. Pictures shown illustrate the low profile of the equipment, they are not intended to imply that Viamed is able to furnish rooms in such a manner.



Photographs reproduced with kind permission of Sunderland Royal Hospital. Special thank you to the parents of Holly Colbeck.

CE0123

Specifications subject to change

Distributed by:



Viamed Limited · 15 Station Road · Cross Hills
Keighley · West Yorkshire · BD20 7DT · United Kingdom
Tel: +44 (0)1535 634 542 / 636 757
Fax: +44 (0)1535 635 582
Email: info@viamed.co.uk Website: www.viamed.co.uk



Part Number: ???????
Date: 11/10



BS EN ISO 9001:2008
ISO 13485:2003

FS 28344

MD 78767