

automotive products



VIAMED



Contact Us



01535 634 542



01535 635 582



15 Station Road
Cross Hills
Keighley
West Yorkshire
BD20 7DT



info@viamed.co.uk



www.viamed.co.uk



VIAMED

‘R’ Series Oxygen Sensors

see page 4...

AN-300 Nitrogen Analyser

see page 12...

Automotive Accessories

see page 18...



Range includes:
R-17A-LV
R-17A, R-21A, R-22A
R-17AV, R-21AV, R-22AV
R-17AH, R-22AH

'R' Series Oxygen Sensors

As used by most automotive emissions testing equipment manufacturers.

- PTB, BAR90, BAR97 and CE product approval
- Accurate measurement performance
- Exceeds industry requirements
- Long life in the field
- Fast response time
- Consistent linear response
- Stable zero
- Choice of connector and thread options

The 'R' series of Oxygen Sensors from Viamed feature special Rhodium plating on the cathode resulting in greater resistance to the effects of CO₂, increasing the life of the sensor when used in exhaust emissions testing.

**No minimum order value
&
no order processing charge**

Viamed's online short-form cross reference can be used to check compatibility, as well as for details of additional oxygen sensors:

www.viamed.co.uk/xref

Alternatively, or if your oxygen sensor or equipment is not listed, please contact us and we will check our comprehensive database.



Free oxygen sensor disposal service
for the safe disposal of
any of your depleted
oxygen sensors



0110107
R-17A-LV

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: Bosch

OEM Sensor Part No.: ???

Output Connector: Phone jack, 0.141"

Sensor Output: 7 - 11.5 mV

Response Time: < 30 seconds

Warranty: 12 months



0110117
R-17A

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Phone jack, 0.141"

Sensor Output: 7 - 13 mV

Response Time: < 30 seconds

Warranty: 12 months



0110121
R-21A

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Molex, 3 pin plug

Sensor Output: 7 - 13 mV

Response Time: < 30 seconds

Warranty: 12 months



0110122
R-22A

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Molex, 3 pin plug

Sensor Output: 7 - 13 mV

Response Time: < 30 seconds

Warranty: 12 months



0110127
R-17AV

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Phone jack, 0.141"

Sensor Output: 9 - 13 mV

Response Time: < 30 seconds

Warranty: 12 months



0110131
R-21AV

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Molex, 3 pin plug

Sensor Output: 9 - 13 mV

Response Time: < 30 seconds

Warranty: 12 months



0110132
R-22AV

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Molex, 3 pin plug

Sensor Output: 9 - 13 mV

Response Time: < 30 seconds

Warranty: 12 months



0110137
R-17AH

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS



Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Phone jack, 0.141"

Sensor Output: 10.5 - 13.5 mV

Response Time: < 30 seconds

Warranty: 12 months



0110142
R-22AH

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS

Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Molex, 3 pin plug

Sensor Output: 10.5 - 13.5 mV

Response Time: < 30 seconds

Warranty: 12 months



0110950
N-33

 **TELEDYNE**
ANALYTICAL
INSTRUMENTS

**for use with AN300
Nitrogen Analyser**

Main OEM: ?

OEM Sensor Part No.: ?

Output Connector: Molex, 3 pin plug

Sensor Output: 10.5 - 13.5 mV

Response Time: < 30 seconds

Warranty: 12 months

AN-300 Nitrogen Analyser

Features of the AN300 include:

- Microprocessor controlled for enhanced performance
- Large, easily-read backlit LCD display
- Auto calibration
- Battery strength indicator
- Auto diagnostics with fault codes
- Auto power off-function after ten minutes
- Coiled sensor cable extendable to 3 metres
- Supplied with 8 mm Twin Hold-On Connector for most automotive tyres
- Optional 12 mm In-Line Hold-On Connector available for aircraft tyres



The AN300 Derived Nitrogen Analyser is a hand-held device designed to analyse the balance of nitrogen in vehicle tyres where nitrogen has been used as an inflation gas.

Nitrogen inflation is becoming increasingly popular for road use, as well as being used extensively in specialist applications such as aircraft and motorsport tyres.

The AN300 offers a low-cost, easy to use nitrogen analysing solution.

Range	0% to 100% N	
Full scale accuracy	± 2% at constant temperature and pressure	
Response time	90% of final value in less than 10 seconds	
Operating temperature range	0° to +40°C	
Power requirements	3 x AA/LR6/MN1500 1.5V alkaline batteries	
Battery life	2000 hours minimum (12,000 10-minute on/off cycles)	
Sensor type	Teledyne class N-33	
Sensor life	24 months in air	
Sensor cable	Extendable to 3 metres	
Weight	420g	
Dimensions	140 mm (H) x 88 mm (W) x 76 mm (D)	
Approvals	CE	
Connectivity	1/4" NPT threaded sensor holder	
Part Number	AN300 Nitrogen Analyser	0111205
Accessories included:		
	N-33 Sensor	0110950
	8v1 Twin Hold-On Connector for 8 mm valves (Commonly used for automotive tyres)	0121251
	1/4 NPT Thread Convertor	0121250
	3 x AA/LR6/MN1500 1.5V alkaline batteries	
Optional accessories	12v1 In-Line Hold-On Connector for 12 mm valves (Commonly used for aircraft tyres)	0121252
	Universal mounting clamp	0121200

The AN300 includes the following standard accessories:



Additional Accessories for use with Teledyne AN300 Nitrogen Analyser

0121252



12v1 In-Line Hold-On
Connector for 12 mm
valves (commonly used for
aircraft tyres)

0121180



0121181



0121182



0121184



0121197



0121199



Table Top
Swivel Mount*

0121200



Universal
Mounting Clamp
Attaches to the threaded
socket at the rear of the unit



VIAMED

Viamed Limited · 15 Station Road · Cross Hills
Keighley · West Yorkshire · BD20 7DT · United Kingdom
Tel: +44 (0)1535 634 542 Fax: +44 (0)1535 635 582
Email: info@viamed.co.uk Website: www.viamed.co.uk



Part Number: ???????

Date: 12/15