

DVM Calibration record

| | | |
|----|---|----------------------|
| 1 | DVM Calibration Index Number | CE111 |
| 2 | DVM Bar code | 102095 |
| 3 | Equipment Used | MICROCAL |
| 4 | Serial number Test Equipment | 6839K6 |
| 5 | Calibration Certificate Number | N/A |
| 6 | Test Equipment Calibration Index Number | CE076 |
| | | |
| | Micro Cal @ | DVM Reading |
| 7 | 0mV +/- 0.1 | 0.0 - 0.1 |
| 8 | 5mV +/- 0.1 | 5.0 |
| 9 | 10mV +/- 0.1 | 10.0 |
| 10 | 15mV +/- 0.1 | 15.0 |
| 11 | 20mV +/- 0.1 | 20.0 |
| 12 | 25mV +/- 0.1 | 25.0 |
| 13 | 30mV +/- 0.1 | 30.0 |
| 14 | 35mV +/- 0.1 | 35.0 |
| 15 | 40mv +/- 0.1 | 40.0 |
| 16 | Pass / Fail | PASS |
| 17 | Tested By | M. GREEN |
| 18 | Tested On | 18-10-2016 |
| 19 | Signed | M. Green |

1. Enter the details of the unit being tested in boxes 1 – 2

2. Enter the details of the calibrated Micro Cal unit being used to test against the equipment. In to boxes 3 -6

Ensure the calibrated unit is still inside its calibration period before you begin.

3. set the micro cal to the required settings (7 – 15) and enter the readings on the DVM in the Boxes

4. Assuming the units passes the tests, date and sign the form (17 – 19). Scan the form and upload to the issue requesting calibration and complete the Issue.

If the unit fails the test return the Unit to RS for calibration