CP0175 v3.9 RS 850-990

SAFETY DATA SHEET

GENERAL PURPOSE ADHESIVE

Page: 1

Compilation date: 23/03/2021

Revision No: 12

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: GENERAL PURPOSE ADHESIVE

Product code: RS850-990

UFI: 9RM0-90DN-K00S-J9A1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: RS Components Ltd

Birchington Road

Glenview Industrial Estate

Corby

Herberton Road

Northamptonshire

Rialto

NN17 9RS

Dublin 12

England

Tel: +44 (0) 845 850 9900

Tel No +353 (0) 1 415 3100

Email: RCustomerServicesUK@rs-components.com

enquiries.ie@rs-components.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1865 407333 (24hr)

+44 (0) 1235 239670 (24hr)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and

vapour. Causes serious eye irritation. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





GENERAL PURPOSE ADHESIVE

Page: 2

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P243: Take action to prevent static discharges.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTRE or doctor if you feel unwell.

P370+P378: In case of fire: Use media other than water to extinguish.

Haz. ingredients (label): ACETONE; ETHYL METHYL KETONE

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1		Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%

ETHYL METHYL KETONE

201-159-0	78-93-3	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	30-50%
			STOT SE 3: H336; -: EUH066	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Consult a doctor. If conscious, give half a litre of water to drink immediately. Do not

induce vomiting. Transfer to hospital as soon as possible.

GENERAL PURPOSE ADHESIVE

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be vomiting. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Vapour may travel considerable distance to source of ignition and flash back. Highly flammable. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

GENERAL PURPOSE ADHESIVE

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600mg/m3	900mg/m3		

Hazardous ingredients:

ACETONE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3		

ETHYL METHYL KETONE

UK	600 mg/m3	899 mg/m3	

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour

filter, type A: organic vapours (EN141). Compressed airline breathing apparatus

(EN139).

Hand protection: Protective gloves. Viton gloves.

GENERAL PURPOSE ADHESIVE

Page: 5

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colourless

Odour: Perceptible odour

Evaporation rate: Fast

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: 56

Flammability limits %: lower: 0.6

upper: 13

Flash point°C: -19

Autoflammability°C: 515

Relative density: 0.86

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

GENERAL PURPOSE ADHESIVE

Page: 6

Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	>5000	mg/kg

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	
ORL	RAT	LD50		

ETHYL METHYL KETONE

IDD					
IDD					
1 11 11 11	_		I .		
		_			
			_	_	

Relevant hazards for product:

Hazard	Route	Basis	
Serious eye damage/irritation	OPT	Hazardous: calculated	
STOT-single exposure		Hazardous: calculated	

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be vomiting. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Volatile.

GENERAL PURPOSE ADHESIVE

Page: 7

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

(ACETONE; ETHYL METHYL KETONE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

GENERAL PURPOSE ADHESIVE

Page: 8

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.