

pulse oximetry

VM-2105

Silicone Finger Oximeter

Incorporating the latest technology; a clear and bright colour OLED display encapsulated in a unique durable, soft silicone housing.

- Unique soft silicone housing for superior comfort and fit
- Robust - no hinge assembly
- 16 bit processing facilitates low perfusion capabilities
- Clear and bright, colour OLED display
- Display can be viewed in 4 rotations
- Large and clear, usable Pleth waveform displayed on 2 rotations
- Colour coded signal quality and signal strength indicator
- Adjustable brightness
- Meets ISO 9919:2005 Standards; shock, vibration, drop and water ingress tests...



The hygienic and easy to clean, soft silicone housing, of the VM-2105, offers superior comfort and fit, allowing for a more accurate and reliable reading, and with no hinge assembly to break this unit is extremely robust and able to withstand even the toughest of environments.

The VM-2105 is an extremely economical piece of equipment for the spot monitoring of SpO_2 and pulse rates. It can be used in a variety of applications, from use in hospitals, paramedic applications, clinics and dental surgeries.

Utilising 16 bit processing technology the VM-2105 gives a fast 'true reading' response, even in cases of low perfusion.

The bright Organic LED display offers superb visibility in all lighting conditions, including direct sunlight.



VM-2105 Silicone Finger Oximeter

Measuring Range

SpO ₂	0 - 100%
Pulse rate	20 - 300 bpm

Accuracy

SpO ₂ (70 - 100%)	0012105: 1.5 A _{RMS} *
	0012106: <3.0 A _{RMS} *
Pulse rate	+/- 1 bpm (≤100 bpm) +/- 1% (>100 bpm)

Optical Specifications

Red emitter	660 nm, typ. 3.5 mW
Infrared emitter	905 nm, typ. 3.5 mW

Display

Features	Colour OLED, adjustable brightness (6 levels), 20 mm x 26 mm, 262,000 colours, 128 x 96 pixels
----------	---

Data displayed	Oxygen saturation, pulse rate, Plethysmogram, pulse indicator, bar graph
----------------	---

Indicators	Pulse signal quality & signal strength, battery status
Digit height (max)	10 mm
Pleth waveform height (max)	10 mm

Environmental Conditions

Operating temperature	-20 - 50 °C at 15 - 95% RH, 600 - 1300 hPa
Storage temperature	-30 - 70 °C at 10 - 95% RH, 600 - 1500 hPa

Regulatory Approvals

Standards	CE Class IIa in accordance with MDD 93/42/EEC BS EN 60601-1:2006, BS EN 60601-1-1:2001 BS EN 60601-1-2:2007, BS EN ISO 9919:2005 Class II, Type BF
-----------	---

Safety

Assembly

Construction	Water ingress protection IPX2
Dimensions	65 mm (l) x 50 mm (w) x 34 mm (h)
Weight	approx. 49 g (including batteries)
Power supply	2 x 1.5 Volt, AAA batteries
Battery life	Approx. 24 hours of continuous operation

Part Numbers

VM-2105 (Grey)	0012105
EAN-13 (GTIN-13) barcode: 5051826000854	
NATO Stock Number: 6515-99-488-8273	
VM-2105 (Orange)	0012106
EAN-13 (GTIN-13) barcode: 5051826002605	
NATO Stock Number: 6515-99-286-0026	
Standard accessories included:	
Lanyard	0022175
2 x AAA Batteries	9950047

Optional Accessories

Hard Carry Case, with belt loop, colour - black	0022180
Hard Carry Case, with belt loop, colour - orange	0022181
Soft Carry Case, with belt loop, colour - black	0022190
Soft Carry Case, with belt loop, colour - orange	0022191
Soft Carry Case, with belt loop, colour - green	0022192

* In accordance with ISO 9919:2005 Standards.
CE 0086



VM-2105 - Grey



VM-2105 - Orange



Pleth waveform display



Large digit display

Specifications subject to change.

Distributed by:



Viamed Limited • 15 Station Road • Cross Hills
Keighley • West Yorkshire • BD20 7DT • United Kingdom
Tel: +44 (0)1535 634542/636757 Fax: +44 (0)1535 635582
Email: info@viamed.co.uk www.viamed-online.com



BS EN ISO 9001:2000
ISO 13485:2003
ISO 13485:2003 CMDCAS Recognised